

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Sulphuric acid 96 %, VLSI Grade

article number: **9789**  
Version: **GHS 5.0 en**  
Replaces version of: 2019-11-22  
Version: (GHS 4)

date of compilation: 2016-04-29  
Revision: 2021-08-24

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Identification of the substance **Sulphuric acid 96 %, VLSI Grade**  
Article number 9789  
CAS number 7664-93-9

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical  
Laboratory and analytical use  
Uses advised against: Do not use for squirting or spraying. Do not use for products which come into direct contact with the skin. Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

### 1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG  
Schoemperlenstr. 3-5  
D-76185 Karlsruhe  
Germany

**Telephone:**+49 (0) 721 - 56 06 0  
**Telefax:** +49 (0) 721 - 56 06 149  
**e-mail:** sicherheit@carlroth.de  
**Website:** www.carlroth.de

Competent person responsible for the safety data sheet: :Department Health, Safety and Environment

**e-mail (competent person):** **sicherheit@carlroth.de**

### 1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 Westmead, NSW	131126	

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.16	Substance or mixture corrosive to metals	1	Met. Corr. 1	H290
3.2	Skin corrosion/irritation	1	Skin Corr. 1	H314
3.3	Serious eye damage/eye irritation	1	Eye Dam. 1	H318

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Sulphuric acid 96 %, VLSI Grade

article number: 9789

For full text of abbreviations: see SECTION 16

### The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis.

## 2.2 Label elements

### Labelling

#### Signal word

**Danger**

#### Pictograms

GHS05



#### Hazard statements

H290

May be corrosive to metals

H314

Causes severe skin burns and eye damage

#### Precautionary statements

##### Precautionary statements - prevention

P260

Do not breathe dusts or mists

P280

Wear eye protection/face protection

##### Precautionary statements - response

P303+P361+P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P390

Absorb spillage to prevent material damage

##### Precautionary statements - disposal

P501

Dispose of contents/container to industrial combustion plant

## 2.3 Other hazards

### Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Name of substance

Sulphuric acid

Molecular formula

H<sub>2</sub>O<sub>4</sub>S

Molar mass

98.07 g<sub>mol</sub>

CAS No

7664-93-9

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Sulphuric acid 96 %, VLSI Grade

article number: 9789

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures



##### General notes

Take off immediately all contaminated clothing. Self-protection of the first aider.

##### Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

##### Following skin contact

Remove mechanically (e.g. dab away using wadding or cellulose material) then thoroughly wash the affected skin with a mild cleansing agent and water. Immediate medical treatment required because corrosive injuries that are not treated are hard to cure.

##### Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

##### Following ingestion

Rinse mouth immediately and drink plenty of water. Call a physician immediately. If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

#### 4.2 Most important symptoms and effects, both acute and delayed

Corrosion, Gastric perforation, Risk of serious damage to eyes, Risk of blindness

#### 4.3 Indication of any immediate medical attention and special treatment needed

none

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media



##### Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings  
water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO<sub>2</sub>)

##### Unsuitable extinguishing media

water jet

#### 5.2 Special hazards arising from the substance or mixture

Non-combustible.

##### Hazardous combustion products

In case of fire may be liberated: Sulphur oxides (SO<sub>x</sub>)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus. Wear full chemical protective clothing.

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



**Sulphuric acid 96 %, VLSI Grade**

article number: 9789

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures



#### For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. The product is an acid. Before discharge into sewage plants the product normally needs to be neutralised.

### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

#### Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### Other information relating to spills and releases

Place in appropriate containers for disposal.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Handle and open container with care. Clear contaminated areas thoroughly.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed. Store in a dry place. Hygroscopic.

#### Incompatible substances or mixtures

Observe hints for combined storage.

#### Protect against external exposure, such as

humidity

#### Consideration of other advice:

#### Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

### 7.3 Specific end use(s)

No information available.

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Sulphuric acid 96 %, VLSI Grade

article number: 9789

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### National limit values

##### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
AU	sulfuric acid	7664-93-9	WES		1		3				WES

##### Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

##### Human health values

Relevant DNELs and other threshold levels				
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	0.05 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
DNEL	0.1 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects

##### Environmental values

Relevant PNECs and other threshold levels				
Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
PNEC	0.003 mg/l	aquatic organisms	freshwater	short-term (single instance)
PNEC	0 mg/l	aquatic organisms	marine water	short-term (single instance)
PNEC	8.8 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	0.002 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	0.002 mg/kg	aquatic organisms	marine sediment	short-term (single instance)

#### 8.2 Exposure controls

##### Individual protection measures (personal protective equipment)

##### Eye/face protection



Use safety goggle with side protection. Wear face protection.

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Sulphuric acid 96 %, VLSI Grade

article number: 9789

### Skin protection



#### • hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

#### • type of material

FKM (fluoro rubber)

#### • material thickness

≥0,4 mm

#### • breakthrough times of the glove material

>480 minutes (permeation: level 6)

#### • Splash protection - Protective gloves

• type of material: Butyl caoutchouc (butyl rubber)


• material thickness: 0,7mm

• breakthrough times of the glove material: >120 minutes (permeation: level 4)

#### • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

### Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: E (against acidic gases like sulphur dioxide or hydrogen chloride, colour code: Yellow). Type: B-P2 (combined filters for acidic gases and particles, colour code: Grey/White).

### Environmental exposure controls

Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	odourless
Melting point/freezing point	-15 °C

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Sulphuric acid 96 %, VLSI Grade

article number: 9789

Boiling point or initial boiling point and boiling range	295 – 315 °C
Flammability	non-combustible
Lower and upper explosion limit	not determined
Flash point	not determined
Auto-ignition temperature	not determined
Decomposition temperature	338 °C
pH (value)	<1 (20 °C)
Kinematic viscosity	14.62 mm <sup>2</sup> /s at 20 °C
<u>Solubility(ies)</u>	
Water solubility	(soluble)
<u>Partition coefficient</u>	
Partition coefficient n-octanol/water (log value):	not relevant (inorganic)
Vapour pressure	<0.01 hPa at 20 °C
Density	1.84 g/cm <sup>3</sup> at 20 °C
Relative vapour density	information on this property is not available
Particle characteristics	not relevant (liquid)
<u>Other safety parameters</u>	
Oxidising properties	none

**9.2 Other information**

Information with regard to physical hazard classes:

Corrosive to metals	category 1: corrosive to metals
Other safety characteristics:	There is no additional information.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

It's a reactive substance. Substance or mixture corrosive to metals.

### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Sulphuric acid 96 %, VLSI Grade

article number: 9789

### 10.3 Possibility of hazardous reactions

**Violent reaction with:** Aldehydes, Alkali (lye), Alkali metals, Ammonia (NH<sub>3</sub>), Bromates, Carbide, Chlorates, Alkaline earth metal, Halogenated hydrocarbons, Metals, Metal powder, Nitrate, Nitriles, Nitro compound, Organic substances, Perchlorates, Permanganates, Peroxides, Phosphorus, Phosphorus oxides (e.g. P<sub>2</sub>O<sub>5</sub>), Acids, Strong alkali, Water, Hydrogen peroxide

### 10.4 Conditions to avoid

Keep away from heat. Decomposition takes place from temperatures above: 338 °C.

### 10.5 Incompatible materials

different metals

### 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

**Classification acc. to GHS**

#### Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	2,140 mg/kg	rat		ECHA

#### Skin corrosion/irritation

Causes severe skin burns and eye damage.

#### Serious eye damage/eye irritation

Causes serious eye damage.

#### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

#### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

#### Carcinogenicity

Shall not be classified as carcinogenic.

#### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

#### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

#### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

#### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.



## Sulphuric acid 96 %, VLSI Grade

article number: 9789

### Symptoms related to the physical, chemical and toxicological characteristics

- **If swallowed**

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects)

- **If in eyes**

causes burns, Causes serious eye damage, risk of blindness

- **If inhaled**

cough, pain, choking, and breathing difficulties

- **If on skin**

causes severe burns, causes poorly healing wounds

- **Other information**

none

### 11.2 Endocrine disrupting properties

Not listed.

## SECTION 12: Ecological information

### 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)				
Endpoint	Value	Species	Source	Exposure time
EC50	>100 mg/l	aquatic invertebrates	ECHA	48 h
ErC50	>100 mg/l	algae	ECHA	72 h

### Biodegradation

The methods for determining the biological degradability are not applicable to inorganic substances.

### 12.2 Process of degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Endocrine disrupting properties

Not listed.

### 12.7 Other adverse effects

Data are not available.

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Sulphuric acid 96 %, VLSI Grade

article number: 9789

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

##### Sewage disposal-relevant information

Do not empty into drains.

##### Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

##### Relevant provisions relating to waste(Basel Convention)

##### Properties of waste which render it hazardous

H8 Corrosives

#### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

### SECTION 14: Transport information

#### 14.1 UN number

UN RTDG	UN 1830
IMDG-Code	UN 1830
ICAO-TI	UN 1830

#### 14.2 UN proper shipping name

UN RTDG	SULPHURIC ACID
IMDG-Code	SULPHURIC ACID
ICAO-TI	Sulphuric acid

#### 14.3 Transport hazard class(es)

UN RTDG	8
IMDG-Code	8
ICAO-TI	8

#### 14.4 Packing group

UN RTDG	II
IMDG-Code	II
ICAO-TI	II

#### 14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Sulphuric acid 96 %, VLSI Grade

article number: 9789

### 14.6 Special precautions for user


There is no additional information.

### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

### 14.8 Information for each of the UN Model Regulations

#### Transport information National regulations Additional information (UN RTDG)

UN number	1830
Class	8
Packing group	II
Danger label(s)	8
	
Special provisions (SP)	- UN RTDG
Excepted quantities (EQ)	E2 UN RTDG
Limited quantities (LQ)	1 L UN RTDG

#### International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name	SULPHURIC ACID
Particulars in the shipper's declaration	UN1830, SULPHURIC ACID, 8, II
Marine pollutant	-
Danger label(s)	8



Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-A, S-B
Stowage category	C
Segregation group	1 - Acids

#### International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name	Sulphuric acid
Particulars in the shipper's declaration	UN1830, Sulphuric acid, 8, II
Danger label(s)	8



Excepted quantities (EQ)	E2
Limited quantities (LQ)	0,5 L

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Sulphuric acid 96 %, VLSI Grade

article number: 9789

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

##### National regulations(Australia)

##### Australian Inventory of Chemical Substances(AICS)

Substance is listed.

##### Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

##### UN Convention against Illicit Traffic in Narcotic Drugs and Psychotropic Substances

Name of substance	CAS No	Listed in	HS code
Sulphuric acid	7664-93-9	Table II	2807.00

##### National inventories

Country	Inventory	Status
AU	AICS	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed

##### Legend

AICS	Australian Inventory of Chemical Substances
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

#### 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Sulphuric acid 96 %, VLSI Grade

article number: 9789

### SECTION 16: Other information

#### Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1		The most important adverse physicochemical, human health and environmental effects: Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis.	yes
2.2		Precautionary statements - response: change in the listing (table)	yes
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Danger		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB.	yes

#### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Sulphuric acid 96 %, VLSI Grade

article number: 9789

Abbr.	Descriptions of used abbreviations
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
STEL	Short-term exposure limit
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne conatminants

### Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.