acc. to Safe Work Australia - Code of Practice



date of compilation: 2016-05-30

Revision: 2024-03-02

Tungsten ≥99 %, ~325 mesh powder

article number: **9835** Version: **GHS 3.0 en** Replaces version of: 2021-12-23 Version: (GHS 2)

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

# 1.1 Product identifier

Identification of the substance

Article number CAS number **Tungsten** powder, ≥99 %, ~325 mesh 9835

7440-33-7

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Laboratory chemical Laboratory and analytical use

Uses advised against:

Do not use for private purposes (household). Food, drink and animal feedingstuffs.

# 1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

**Telephone:**+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data Department Health, Safety and Environment sheet:

# e-mail (competent person):

# sicherheit@carlroth.de

# 1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

# **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

# Classification acc. to GHS

Section	Hazard class		Hazard class and category	Hazard statement
2.7	Flammable solid	1	Flam. Sol. 1	H228
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	Serious eye damage/eye irritation	2A	Eye Irrit. 2A	H319

For full text of abbreviations: see SECTION 16

# 2.2 Label elements

acc. to Safe Work Australia - Code of Practice

# Tungsten ≥99 %, ~325 mesh powder

article number: 9835

Labelling



# Signal wordDangerPictogramsGHS02, GHS07

# **Hazard statements**

H228	Flammable solid
H315	Causes skin irritation
H319	Causes serious eye irritation

### **Precautionary statements**

# **Precautionary statements - prevention**

P210	Keep away from heat/sparks/open flames/hot surfaces No smoking
P280	Wear protective gloves

### **Precautionary statements - response**

P302+P352	IF ON SKIN: Wash with plenty of soap and water
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing
P337+P313	If eye irritation persists: Get medical advice/attention
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

# 2.3 Other hazards

# Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

# **Endocrine disrupting properties**

Does not contain an endocrine disruptor (ED) at a concentration of  $\ge 0,1\%$ .

# **SECTION 3: Composition/information on ingredients**

# 3.1 Substances

Name of substance	Tungsten
Molecular formula	W
Molar mass	183.8 <sup>g</sup> / <sub>mol</sub>
CAS No	7440-33-7

acc. to Safe Work Australia - Code of Practice

8

# Tungsten ≥99 %, ~325 mesh powder

article number: 9835

# **SECTION 4: First aid measures**

# 4.1 Description of first aid measures



# **General notes**

Take off contaminated clothing.

# **Following inhalation**

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

### Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

### Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

### **Following ingestion**

Let water be drunken in little sips (dilution effect). Call a doctor if you feel unwell.

# **4.2 Most important symptoms and effects, both acute and delayed** Irritation

# **4.3 Indication of any immediate medical attention and special treatment needed** none

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media



# Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings foam, dry extinguishing powder, ABC-powder

# Unsuitable extinguishing media

water, carbon dioxide (CO<sub>2</sub>), water jet

# 5.2 Special hazards arising from the substance or mixture

None.

# 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

acc. to Safe Work Australia - Code of Practice

® §POTH

Tungsten ≥99 %, ~325 mesh powder

article number: 9835

# **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures



# For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe dust.

# 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

# 6.3 Methods and material for containment and cleaning up

# Advice on how to contain a spill

Covering of drains. Take up mechanically.

### Advice on how to clean up a spill

Take up mechanically. Control of dust.

### Other information relating to spills and releases

Place in appropriate containers for disposal.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

# **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

Avoid dust formation.

# Measures to prevent fire as well as aerosol and dust generation

Removal of dust deposits.

# Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

# 7.2 Conditions for safe storage, including any incompatibilities

Store in a dry place.

# Incompatible substances or mixtures

Observe hints for combined storage.

# Consideration of other advice:

### **Ventilation requirements**

Use local and general ventilation.

# Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

# 7.3 Specific end use(s)

No information available.

acc. to Safe Work Australia - Code of Practice



# Tungsten ≥99 %, ~325 mesh powder

article number: 9835

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

# **National limit values**

# **Occupational exposure limit values (Workplace Exposure Limits)**

Coun try	Name of agent	CAS No	Identifi- er	TWA [mg/ m³]	STEL [mg/ m³]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
AU	nuisance dusts		WES	10			i	WES

### Notation

 Ceiling-C
 Ceiling value is a limit value above which exposure should not occur

 i
 Inhalable fraction

 STEL
 Short-term exposure limit: a limit value above which exposure should not occur and which

 

 STEL
 Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15minute period (unless otherwise specified)

 TWA
 Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8

VA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

# Human health values

Relevant DNELs and other threshold levels						
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time		
DNEL	5.8 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects		
DNEL	1.7 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic effects		

# **Environmental values**

Relevant PNECs and other threshold levels						
End- point	Threshold level	Organism	Environmental com- partment	Exposure time		
PNEC	0.338 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single instance)		
PNEC	0.034 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	marine water	short-term (single instance)		
PNEC	0.31 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	water	intermittent release		
PNEC	5.86 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)		
PNEC	960 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	freshwater sediment	short-term (single instance)		
PNEC	96 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	marine sediment	short-term (single instance)		
PNEC	2.17 <sup>mg</sup> / <sub>kg</sub>	terrestrial organisms	soil	short-term (single instance)		

# 8.2 Exposure controls

# Individual protection measures (personal protective equipment)

# Eye/face protection



acc. to Safe Work Australia - Code of Practice

# Tungsten ≥99 %, ~325 mesh powder

article number: 9835



Use safety goggle with side protection.

# Skin protection



### hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a consider-able reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

### • type of material

NBR (Nitrile rubber)

### • material thickness

>0,11 mm

# breakthrough times of the glove material

>480 minutes (permeation: level 6)

# • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

# **Respiratory protection**



Respiratory protection necessary at: Dust formation. Particulate filter device (EN 143). P1 (filters at least 80 % of airborne particles, colour code: White).

# **Environmental exposure controls**

Keep away from drains, surface and ground water.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Physical state	solid
Form	powder
Colour	black
Odour	odourless
Melting point/freezing point	3,410 °C
Boiling point or initial boiling point and boiling range	5,660 °C
Flammability	flammable solid in accordance with GHS criteria

acc. to Safe Work Australia - Code of Practice

# Tungsten ≥99 %, ~325 mesh powder

article number	: 9835



	Lower and upper explosion limit	not determined
	Flash point	not applicable
	Auto-ignition temperature	≥100 °C (ECHA) (relative self-ignition temperat- ure for solids)
	Decomposition temperature	not relevant
	pH (value)	not applicable
	Kinematic viscosity	not relevant
	Solubility(ies)	
	Water solubility	(practically insoluble)
	Partition coefficient	
	Partition coefficient n-octanol/water (log value):	not relevant (inorganic)
	Vapour pressure	not determined
	Density and/or relative density	
	Density	19.3 <sup>g</sup> / <sub>cm³</sub> at 20 °C
	Relative vapour density	Information on this property is not available.
	Particle characteristics	No data available.
	Other safety parameters	
	Oxidising properties	none
9.2	Other information	
	Information with regard to physical hazard classes:	There is no additional information.
	Other safety characteristics:	There is no additional information.

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

It's a reactive substance. Risk of ignition.

# If heated

Risk of ignition.

# 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

# 10.3 Possibility of hazardous reactions

**Violent reaction with:** strong oxidiser, Chlorine, Fluorine, Hydrogen peroxide, Bromine, Hydrogen sulphide ( $H_2S$ )

acc. to Safe Work Australia - Code of Practice



# Tungsten ≥99 %, ~325 mesh powder

article number: 9835

# 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- **10.5 Incompatible materials** There is no additional information.
- **10.6 Hazardous decomposition products** Hazardous combustion products: see section 5.

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

# **Classification acc. to GHS**

# Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4. May be harmful if swallowed or in contact with skin.

Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	>2,000 <sup>mg</sup> / <sub>kg</sub>	rat		ECHA
dermal	LD50	>2,000 <sup>mg</sup> / <sub>kg</sub>	rat		ECHA

# Skin corrosion/irritation

Causes skin irritation.

# Serious eye damage/eye irritation

Causes serious eye irritation.

# **Respiratory or skin sensitisation**

Shall not be classified as a respiratory or skin sensitiser.

# Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

# Carcinogenicity

Shall not be classified as carcinogenic.

# **Reproductive toxicity**

Shall not be classified as a reproductive toxicant.

# Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

# Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

# Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

# Symptoms related to the physical, chemical and toxicological characteristics

### If swallowed

Data are not available.

acc. to Safe Work Australia - Code of Practice

# Tungsten ≥99 %, ~325 mesh powder

article number: 9835

# • If in eyes

Causes serious eye irritation

# If inhaled

Data are not available.

# • If on skin

causes skin irritation

# • Other information

none

# 11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\ge 0,1\%$ .

# **SECTION 12: Ecological information**

# 12.1 Toxicity

Harmful to aquatic life.

Aquatic toxicity (acute)				
Endpoint	Value	Species	Source	Exposure time
LC50	>200 <sup>mg</sup> / <sub>l</sub>	fish	ECHA	96 h
EC50	>163 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	ECHA	24 h
ErC50	≥54.1 <sup>mg</sup> / <sub>l</sub>	algae	ECHA	72 h

# Aquatic toxicity (chronic)

Endpoint	Value	Species	Source	Exposure time
EC50	>100 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	ECHA	21 d
EbC50	>100 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	ECHA	21 d

# 12.2 Persistence and degradability

Data are not available.

# 12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

BCF
-----

# >0 – <1.23 (ECHA)

# 12.4 Mobility in soil

Data are not available.

# 12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

# 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\ge 0,1\%$ .



acc. to Safe Work Australia - Code of Practice



# Tungsten ≥99 %, ~325 mesh powder

article number: 9835

# 12.7 Other adverse effects

Data are not available.

# **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Recycling/reclamation of metals and metal compounds.

# Sewage disposal-relevant information

Do not empty into drains.

# Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

### Relevant provisions relating to waste(Basel Convention)

# Properties of waste which render it hazardous

H4.1 Flammable solids

### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

# **SECTION 14: Transport information**

UN number	
UN RTDG	UN 3089
IMDG-Code	UN 3089
ICAO-TI	UN 3089
UN proper shipping name	
UN RTDG	METAL POWDER, FLAMMABLE, N.O.S.
IMDG-Code	METAL POWDER, FLAMMABLE, N.O.S.
ICAO-TI	Metal powder, flammable, n.o.s.
Transport hazard class(es)	
UN RTDG	4.1
IMDG-Code	4.1
ICAO-TI	4.1
Packing group	
UN RTDG	II
IMDG-Code	II
	UN RTDG IMDG-Code ICAO-TI UN proper shipping name UN RTDG IMDG-Code ICAO-TI Transport hazard class(es) UN RTDG IMDG-Code ICAO-TI Packing group UN RTDG

# Safety data sheet Safety data sheet acc. to Safe Work Australia - Code of Practice

Tungsten ≥99 %, ~325 mesh powder



	e number: <b>9835</b>			
	ICAO-TI	II		
14.5	Environmental hazards	non-environmentally hazardous acc. to the dan- gerous goods regulations		
14.6	<b>Special precautions for user</b> There is no additional information.			
14.7	<b>Transport in bulk according to IMO instrun</b> The cargo is not intended to be carried in bulk			
14.8	Information for each of the UN Model Regu	ulations		
	Transport informationNational regulations	sAdditional information(UN RTDG)		
	UN number	3089		
	Class	4.1		
	Packing group	II		
	Danger label(s)	4.1		
	Special provisions (SP)	- UN RTDG		
	Excepted quantities (EQ)	E2 UN RTDG		
	Limited quantities (LQ)	1 kg UN RTDG		
	Emergency Action Code	4Y		
	International Maritime Dangerous Goods Code (IMDG) - Additional information			
	Proper shipping name	METAL POWDER, FLAMMABLE, N.O.S.		
	Particulars in the shipper's declaration	UN3089, METAL POWDER, FLAMMABLE, N.O.S., 4.1, II		
	Marine pollutant	-		
	Danger label(s)	4.1		
	Excepted quantities (EQ)	E2		
	Limited quantities (LQ)	1 kg		
	EmS	F-G, S-G		
	Stowage category	В		
	Segregation group	7 - Heavy metals and their salts 15 - Powdered metals		

acc. to Safe Work Australia - Code of Practice

# Tungsten ≥99 %, ~325 mesh powder

article number: 9835



International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information		
Proper shipping name	Metal powder, flammable, n.o.s.	
Particulars in the shipper's declaration	UN3089, Metal powder, flammable, n.o.s., 4.1, II	
Danger label(s)	4.1	
Special provisions (SP)	A3	
Excepted quantities (EQ)	E2	
Limited quantities (LQ)	5 kg	

# **SECTION 15: Regulatory information**

**15.1** Safety, health and environmental regulations/legislation specific for the substance or mixture There is no additional information.

# National regulations(Australia)

# Australian Inventory of Chemical Substances(AICS)

Substance is listed.

# **Other information**

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

# **National inventories**

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

# Legend

AIIC DSL ECSI IECSC INSQ KECI NCI NZIOC Australian Inventory of Industrial Chemicals Domestic Substances List (DSL) EC Substance Inventory (EINECS, ELINCS, NLP) Inventory of Existing Chemical Substances Produced or Imported in China National Inventory of Chemical Substances Korea Existing Chemicals Inventory National Chemical Inventory New Zealand Inventory of Chemicals

acc. to Safe Work Australia - Code of Practice

# Tungsten ≥99 %, ~325 mesh powder



### article number: 9835

Legend	
	Philippine Inventory of Chemicals and Chemical Substances (PICCS) REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

# 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

# **SECTION 16: Other information**

# Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
14.8		Emergency Action Code: 4Y	yes
15.1		National inventories: change in the listing (table)	yes

# Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
BCF	Bioconcentration factor
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EbC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions
ΙΑΤΑ	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air

acc. to Safe Work Australia - Code of Practice



# Tungsten ≥99 %, ~325 mesh powder

### article number: 9835

Abbr.	Descriptions of used abbreviations
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
NLP	No-Longer Polymer
РВТ	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
STEL	Short-term exposure limit
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants

# Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

# List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H228	Flammable solid.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

# Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.