acc. to Regulation (EC) No. 1907/2006 (REACH)

## 

#### article number: **AE04** Version: **5.0 en** Replaces version of: 2023-09-28 Version: (4)

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

## 1.1 Product identifier

Identification of the substance	<b>Diethyl ether</b> ROTIDRY $ \ge 99,5 $ % ( $\le 60 $ ppm $H_2O$ ), stabilized
Article number	AE04
Index No (GB CLP)	603-022-00-4
EC number	200-467-2
CAS number	60-29-7

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified us	ses:
nerevanie laenenea a.	

Laboratory chemical Laboratory and analytical use

sicherheit@carlroth.de

Uses advised against:

Do not use for private purposes (household). Food, drink and animal feedingstuffs.

## 1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

**Telephone:**+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data Department Health, Safety and Environment sheet:

## e-mail (competent person):

## 1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

**Classification acc. to GHS** 



date of compilation: 2015-12-07 Revision: 2024-03-04

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Diethyl ether ROTIDRY $\otimes$ 299,5 % ( $\leq$ 60 ppm H<sub>2</sub>O), stabilized

article number: **AE04** 

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	1	Flam. Liq. 1	H224
3.10	Acute toxicity (oral)	4	Acute Tox. 4	H302
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

## Supplemental hazard information

Code	Supplemental hazard information
EUH019	may form explosive peroxides
EUH066	repeated exposure may cause skin dryness or cracking

For full text of abbreviations: see SECTION 16

## The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

## 2.2 Label elements

## Labelling

Signal word Danger

## **Pictograms**

GHS02, GHS07



## **Hazard statements**

H224	Extremely flammable liquid and vapour
H302	Harmful if swallowed
H336	May cause drowsiness or dizziness

## **Precautionary statements**

## **Precautionary statements - prevention**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P243 Take action to prevent static discharges
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray

## **Precautionary statements - response**

P303+P361+P353IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin<br/>with water [or shower]P304+P340IF INHALED: Remove person to fresh air and keep comfortable for breathing<br/>Call a POISON CENTRE/doctor if you feel unwell

## Supplemental hazard information

EUH019	May form explosive peroxides.
EUH066	Repeated exposure may cause skin dryness or cracking.

acc. to Regulation (EC) No. 1907/2006 (REACH)

## Diethyl ether ROTIDRY $\otimes 299,5 \%$ ( $\leq 60 \text{ ppm H}_2O$ ), stabilized

article number: **AE04** 

## 2.3 Other hazards

## Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

## **Endocrine disrupting properties**

Does not contain an endocrine disruptor (ED) at a concentration of  $\ge 0,1\%$ .

## **SECTION 3: Composition/information on ingredients**

## 3.1 Substances

Name of substance	Diethyl ether
Molecular formula	$C_4H_{10}O$
Molar mass	74,12 <sup>g</sup> / <sub>mol</sub>
CAS No	60-29-7
EC No	200-467-2
Index No (GB CLP)	603-022-00-4

## To stabilise:

Name of substance	Identifier	Wt%
Butylated hydroxytoluene	CAS No 128-37-0	< 0,1
	EC No 204-881-4	

Substance, Specific Conc. Limits, M-factors, ATE							
Specific Conc. Limits     M-Factors     ATE     Exposure route							
-	-	1.215 <sup>mg</sup> / <sub>kg</sub>	oral				

## Remarks

For full text of abbreviations: see SECTION 16

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures



## **General notes**

Take off contaminated clothing.

## **Following inhalation**

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

## Following skin contact

Rinse skin with water/shower.



acc. to Regulation (EC) No. 1907/2006 (REACH)



## Diethyl ether ROTIDRY $\otimes 299,5 \%$ ( $\leq 60 \text{ ppm H}_2O$ ), stabilized

article number: AE04

## Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

## **Following ingestion**

Rinse mouth with water (only if the person is conscious). Call a doctor.

# **4.2** Most important symptoms and effects, both acute and delayed Irritant effects, Vomiting, Vertigo, Dizziness, Drowsiness, Narcosis

# **4.3 Indication of any immediate medical attention and special treatment needed** none

## **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media



## Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO<sub>2</sub>)

## Unsuitable extinguishing media

water jet

## 5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapourair mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

#### Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

## **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures



## For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

## 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

acc. to Regulation (EC) No. 1907/2006 (REACH)

## Diethyl ether ROTIDRY $@>99,5 % (\leq 60 \text{ ppm H}_2O)$ , stabilized

article number: AE04

## 6.3 Methods and material for containment and cleaning up

## Advice on how to contain a spill

Covering of drains.

## Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

## Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

## 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

Provision of sufficient ventilation.

## Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

## Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

#### Incompatible substances or mixtures

Observe hints for combined storage.

## Protect against external exposure, such as

humidity, UV-radiation/sunlight, contact with air/oxygen

## Consideration of other advice:

Ground/bond container and receiving equipment.

#### Ventilation requirements

Use local and general ventilation.

## Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

## 7.3 Specific end use(s)

No information available.



acc. to Regulation (EC) No. 1907/2006 (REACH)

## Diethyl ether ROTIDRY® $\geq$ 99,5 % ( $\leq$ 60 ppm H<sub>2</sub>O), stabilized



article number: AE04

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 **Control parameters**

## National limit values

## **Occupational exposure limit values (Workplace Exposure Limits)**

Co nt y		CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
El	diethyl ether	60-29-7	IOELV	100	308	200	616				2000/39/ EC
G	3 diethyl ether	60-29-7	WEL	100	310	200	620				EH40/ 2005

Notation

STEL

TWA

Ceiling-C

Ceiling value is a limit value above which exposure should not occur Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

## Human health values

Relevant DNI	Relevant DNELs and other threshold levels								
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time					
DNEL	308 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects					
DNEL	616 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects					
DNEL	44 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic effects					

## **Relevant DNELs of components**

Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time	
Butylated hydroxy- toluene	128-37-0	DNEL	19 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects	
Butylated hydroxy- toluene	128-37-0	DNEL	18 mg/m <sup>3</sup>	human, inhalat- ory	worker (industry)	acute - systemic effects	
Butylated hydroxy- toluene	128-37-0	DNEL	3,5 mg/m <sup>3</sup>	human, inhalat- ory	worker (industry)	chronic - systemic effects	
Butylated hydroxy- toluene	128-37-0	DNEL	0,5 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects	

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Diethyl ether ROTIDRY $\otimes$ 299,5 % ( $\leq$ 60 ppm H<sub>2</sub>O), stabilized

article number: **AE04** 

Environm	invironmental values									
Relevant	Relevant PNECs and other threshold levels									
End- point	Threshold level	Organism	Environmental com- partment	Exposure time						
PNEC	2 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single instance)						
PNEC	0,2 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	marine water	short-term (single instance)						
PNEC	4,2 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)						
PNEC	9,14 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	freshwater sediment	short-term (single instance)						
PNEC	0,914 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	marine sediment	short-term (single instance)						
PNEC	0,66 <sup>mg</sup> / <sub>kg</sub>	terrestrial organisms	soil	short-term (single instance)						

## **Relevant PNECs of components**

·						
Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time
Butylated hydroxy- toluene	128-37-0	PNEC	8,33 <sup>mg</sup> / <sub>kg</sub>	aquatic organ- isms	water	short-term (single instance)
Butylated hydroxy- toluene	128-37-0	PNEC	1,99 <sup>µg</sup> / <sub>l</sub>	aquatic organ- isms	water	intermittent re- lease
Butylated hydroxy- toluene	128-37-0	PNEC	0,199 <sup>µg</sup> / <sub>l</sub>	aquatic organ- isms	freshwater	short-term (single instance)
Butylated hydroxy- toluene	128-37-0	PNEC	0,02 <sup>µg</sup> / <sub>l</sub>	aquatic organ- isms	marine water	short-term (single instance)
Butylated hydroxy- toluene	128-37-0	PNEC	0,17 <sup>mg</sup> / <sub>l</sub>	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
Butylated hydroxy- toluene	128-37-0	PNEC	99,6 <sup>µg</sup> / <sub>kg</sub>	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
Butylated hydroxy- toluene	128-37-0	PNEC	9,96 <sup>µg</sup> / <sub>kg</sub>	aquatic organ- isms	marine sediment	short-term (single instance)
Butylated hydroxy- toluene	128-37-0	PNEC	47,69 <sup>µg</sup> / <sub>kg</sub>	terrestrial organ- isms	soil	short-term (single instance)

## 8.2 Exposure controls

Individual protection measures (personal protective equipment)

## **Eye/face protection**




Use safety goggle with side protection.

**Skin protection** 



acc. to Regulation (EC) No. 1907/2006 (REACH)



® ROTH

## article number: **AE04**

## hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a consider-able reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

#### • type of material

FKM (fluoro rubber)

material thickness

0,65 mm

## • breakthrough times of the glove material

>30 minutes (permeation: level 2)

## • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

## **Respiratory protection**



Respiratory protection necessary at: Aerosol or mist formation. Type: AX (gas filters and combined filters against low-boiling point organic compounds, colour code: Brown).

## **Environmental exposure controls**

Keep away from drains, surface and ground water.

# **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	mild sweet
Melting point/freezing point	-116 °C
Boiling point or initial boiling point and boiling range	34,58 – 34,59 °C at 1.013 hPa (ECHA)
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	50 g/m³ (LEL) - 1.100 g/m³ (UEL) / 1,7 vol% (LEL) - 39 vol% (UEL)
Flash point	-40 °C (c.c.)
Auto-ignition temperature	175 °C at 1.013 hPa (ECHA)
Decomposition temperature	not relevant

acc. to Regulation (EC) No. 1907/2006 (REACH)

## Diethyl ether ROTIDRY® $\geq$ 99,5 % ( $\leq$ 60 ppm H<sub>2</sub>O), stabilized



#### article number: AE04

pH (value)	not determined
Kinematic viscosity	0,331 <sup>mm²</sup> / <sub>s</sub> at 293,2 K
Dynamic viscosity	0,235 mPa s at 293,2 K
Solubility(ies)	
Water solubility	64,9 <sup>g</sup> / <sub>l</sub> at 20 °C (ECHA)
Partition coefficient	
Partition coefficient n-octanol/water (log value):	1,19 (pH value: 7, 25 °C) (ECHA)
Soil organic carbon/water (log KOC)	0,987 (ECHA)
Vapour pressure	589,6 hPa at 20 °C
Density and/or relative density	
Density	0,71 <sup>g</sup> / <sub>cm³</sub> at 20 °C (ECHA)
Relative vapour density	2,56 (air = 1)
Particle characteristics	not relevant (liquid)
Other safety parameters	
Oxidising properties	none
Other information	
Information with regard to physical hazard classes:	There is no additional information.
Other safety characteristics:	
Gas group (explosion group)	IIB Maximum Experimental Safe Gap value; 0,5 mm ≤ MESG ≤ 0,9 mm
Maximum explosion pressure	9,2 bar

# **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

9.2

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air. May form explosive peroxides.

## If heated

Risk of ignition.

## 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Diethyl ether ROTIDRY $\circledast \ge 99,5 \%$ ( $\le 60 \text{ ppm H}_2O$ ), stabilized

#### article number: AE04

## 10.3 Possibility of hazardous reactions

**Violent reaction with:** strong oxidiser, Nitrate, Perchlorates, Peroxides, Nitric acid, Oxygen, Sulphuric acid, Nitrogen oxides (NOx), Hydrogen peroxide, => Explosive properties

#### 10.4 Conditions to avoid

UV-radiation/sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from moisture.

## 10.5 Incompatible materials

Rubber articles, different plastics

## 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5. Peroxides.

## **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

## **Classification acc. to GHS**

## Acute toxicity

Harmful if swallowed.

Acute toxicity								
Exposure route	Endpoint	Value	Species	Method	Source			
oral	LD50	1.215 <sup>mg</sup> / <sub>kg</sub>	rat		TOXNET			

## Acute toxicity of components

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Butylated hydroxytoluene	128-37-0	oral	LD50	>6.000 <sup>mg</sup> / <sub>kg</sub>	rat
Butylated hydroxytoluene	128-37-0	dermal	LD50	>2.000 <sup>mg</sup> / <sub>kg</sub>	rat

## Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

## Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

## Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

## Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

## Carcinogenicity

Shall not be classified as carcinogenic.

## **Reproductive toxicity**

Shall not be classified as a reproductive toxicant.

acc. to Regulation (EC) No. 1907/2006 (REACH)

## Diethyl ether ROTIDRY $\circledast \ge 99,5 \%$ ( $\le 60 \text{ ppm H}_2O$ ), stabilized

#### article number: AE04

## Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

## Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

## Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

## Symptoms related to the physical, chemical and toxicological characteristics

## • If swallowed

vomiting

## • If in eyes

Data are not available.

## • If inhaled

Inebriation, vertigo, dizziness, fatigue, narcosis

## • If on skin

Frequently or prolonged contact with skin may cause dermal irritation, has degreasing effect on the skin, repeated exposure may cause skin dryness or cracking

## Other information

Other adverse effects: Circulatory collapse

## **11.2** Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\ge 0,1\%$ .

#### 11.3 Information on other hazards

There is no additional information.

## **SECTION 12: Ecological information**

## 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)								
Endpoint	Value		Species		Source		Exposure time	
ErC50	>100 <sup>mg</sup> /	>100 <sup>mg</sup> / <sub>l</sub>		algae			72 h	
Aquatic toxicity (acute) of components								
Name of sub- stance	CAS No	End	point	Value	Spe	cies	Exposure time	
Butylated hydroxy- toluene	128-37-0	L	250	>0,57 <sup>mg</sup> / <sub>l</sub>	fis	sh	96 h	
Butylated hydroxy- toluene	128-37-0	EC50		0,48 <sup>mg</sup> / <sub>l</sub>	aquatic inv	ertebrates	48 h	
Butylated hydroxy- toluene	128-37-0	Er	C50	>0,4 <sup>mg</sup> / <sub>l</sub>	alg	ae	72 h	



acc. to Regulation (EC) No. 1907/2006 (REACH)



## Diethyl ether ROTIDRY® $\geq$ 99,5 % ( $\leq$ 60 ppm H<sub>2</sub>O), stabilized

article number: AE04

Endpoint	Value	Species	Source	Exposure time
EC50	>100 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	ECHA	21 d

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
Butylated hydroxy- toluene	128-37-0	EC50	0,096 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	21 d

## 12.2 Persistence and degradability

Theoretical Oxygen Demand: 2,59 <sup>mg</sup>/<sub>mg</sub> Theoretical Carbon Dioxide: 2,375 <sup>mg</sup>/<sub>mg</sub>

## Biodegradation

Not readily biodegradable.

Degradability of components								
Name of substance	CAS No	Process	Degrada- tion rate	Time	Method	Source		
Butylated hy- droxytoluene	128-37-0	biotic/abiotic	<10 %	20 d				

## 12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)			1,19 (pH value: 7, 25 °C) (ECHA)			
BCF		2,2	2,29			
Bioaccumulative potential of components						
Name of substance	CAS No	BCF	Log KOW	BOD5/COD		
Butylated hydroxytoluene	128-37-0	598,4	5,1			

## 12.4 Mobility in soil

The Organic Carbon normalised adsorption coefficient	0,987 (ECHA)
--	--------------

## 12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

## 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\ge 0,1\%$ .

## 12.7 Other adverse effects

Data are not available.

acc. to Regulation (EC) No. 1907/2006 (REACH)



Diethyl ether ROTIDRY®  $\geq$ 99,5 % ( $\leq$ 60 ppm H<sub>2</sub>O), stabilized

article number: **AE04** 

## **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

## Sewage disposal-relevant information

Do not empty into drains.

## Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

## 13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

## Properties of waste which render it hazardous

- HP 3 flammable
- **HP 15** waste capable of exhibiting a hazardous property listed above not directly displayed by the original waste
- **HP 6** acute toxicity

## 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

## **SECTION 14: Transport information**

## 14.1 UN number or ID number

	ADRRID	UN 1155
	IMDG-Code	UN 1155
	ICAO-TI	UN 1155
14.2	UN proper shipping name	
	ADRRID	DIETHYL ETHER
	IMDG-Code	DIETHYL ETHER
	ICAO-TI	Diethyl ether
14.3	Transport hazard class(es)	
	ADRRID	3
	IMDG-Code	3
	ICAO-TI	3
14.4	Packing group	
	ADRRID	Ι

acc. to Regulation (EC) No. 1907/2006 (REACH)

# E % (//60 ppm H O) stabilized



# Diethyl ether ROTIDRY® ≥99,5 % (≤60 ppm H<sub>2</sub>O), stabilized

article	le number: AE04					
	IMDG-Code	Ι				
	ICAO-TI	Ι				
14.5	Environmental hazards	non-environmentally hazardous acc. to the dan- gerous goods regulations				
14.6	Special precautions for user					
	Provisions for dangerous goods (ADR) should be complied within the premises.					
14.7	Maritime transport in bulk according to IMO instruments					
	The cargo is not intended to be carried in bul	k.				
14.8	Information for each of the UN Model Reg	ulations				
	Agreement concerning the International C information	arriage of Dangerous Goods by Road (ADR)Additional				
	Proper shipping name	DIETHYL ETHER				
	Particulars in the transport document	UN1155, DIETHYL ETHER, 3, I, (D/E)				
	Classification code	F1				
	Danger label(s)	3				
	Excepted quantities (EQ)	E3				
	Transport category (TC)	1				
	Tunnel restriction code (TRC)	D/E				
	Hazard identification No	33				
	Emergency Action Code	3YE				
Regulations concerning the International Carriage of Dangerous Goods by Ra information		Carriage of Dangerous Goods by Rail (RID)Additional				
	Classification code	F1				
	Danger label(s)	3				
	Excepted quantities (EQ)	E3				
	Transport category (TC)	1				
	Hazard identification No	33				
International Maritime Dangerous Goods Code (IMDG) - Additional informa		Code (IMDG) - Additional information				
	Proper shipping name	DIETHYL ETHER				
	Particulars in the shipper's declaration	UN1155, DIETHYL ETHER, 3, I, -40°C c.c.				
	Marine pollutant	-				
	Danger label(s)	3				

acc. to Regulation (EC) No. 1907/2006 (REACH)

## Diethyl ether ROTIDRY® $\geq$ 99,5 % ( $\leq$ 60 ppm H<sub>2</sub>O), stabilized



article number: AE04 

Special provisions (SP)	-
Excepted quantities (EQ)	E3
Limited quantities (LQ)	0
EmS	F-E, S-D
Stowage category	E
International Civil Aviation Organization (	ICAO-IATA/DGR) - Additional information
Proper shipping name	Diethyl ether
Particulars in the shipper's declaration	UN1155, Diethyl ether, 3, I
Danger label(s)	3
Excepted quantities (EQ)	E3

## SECTION 15: Regulatory information

#### Safety, health and environmental regulations/legislation specific for the substance or mixture 15.1

**Relevant provisions of the European Union (EU)** 

## **Seveso Directive**

2012/18/EU (Seveso III)				
No	Dangerous substance/hazard categories	Qualifying quantity plication of lower quiren		Notes
P5a	flammable liquids (cat. 1)	10	50	49)

#### Notation

49)

Flammable liquids, category 1, or
flammable liquids category 2 or 3 maintained at a temperature above their boiling point, or
other liquids with a flash point ≤ 60 °C, maintained at a temperature above their boiling point

## **Deco-Paint Directive**

VOC content	100 %
VOC content	710 <sup>g</sup> /l

## Industrial Emissions Directive (IED)

VOC content	100 %
VOC content	710 <sup>g</sup> / <sub>l</sub>

#### Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

acc. to Regulation (EC) No. 1907/2006 (REACH)



article number: **AE04** 

# Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

## Water Framework Directive (WFD)

#### List of pollutants (WFD) **CAS No** Listed in Name of substance Name acc. to inventory **Remarks** Diethyl ether Substances and preparations, or a) the breakdown products of such, which have been proved to possess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrinerelated functions in or via the aquatic environment

Legend

a) Indicative list of the main pollutants

## Regulation on the marketing and use of explosives precursors

not listed

## **Regulation on drug precursors**

Name of substance	CAS No	Wt%	Classification	CN Code	Threshold level
Diethyl ether	60-29-7	100	Category 3	2909 11 00	

## Regulation on substances that deplete the ozone layer (ODS)

not listed

## Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

## **Regulation on persistent organic pollutants (POP)**

not listed

## National regulations(GB)

# List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list not listed

Restrictions according to GB REACH, Annex 17

Dangerous substances with restrictions (GB REACH, Annex 17)			
Name of substance	Name acc. to inventory	CAS No	Νο
Diethyl ether	this product meets the criteria for classi- fication in accordance with Regulation No 1272/2008/EC		3
Diethyl ether	flammable / pyrophoric		40


## **Other information**

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.



acc. to Regulation (EC) No. 1907/2006 (REACH)





## UN Convention against Illicit Traffic in Narcotic Drugs and Psychotropic Substances

Name of substance	CAS No	Listed in	HS code
Diethyl ether	60-29-7	Table II	2909.11

## **National inventories**

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
ΤW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

## Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NCI	National Chemical Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

## 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance.

# **SECTION 16: Other information**

Indication of changes (revised safety data sheet)



acc. to Regulation (EC) No. 1907/2006 (REACH)



## Diethyl ether ROTIDRY $\otimes$ 299,5 % ( $\leq$ 60 ppm H<sub>2</sub>O), stabilized

article number: AE04

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3	Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of ≥ 0,1%.	Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
15.1		National inventories: change in the listing (table)	yes

## Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations	
2000/39/EC	Commission Directive establishing a first list of indicative occupational exposure limit values in imple- mentation of Council Directive 98/24/EC	
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concern- ing the International Carriage of Dangerous Goods by Road)	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BOD	Biochemical Oxygen Demand	
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)	
Ceiling-C	Ceiling value	
CN Code	Combined Nomenclature	
COD	Chemical oxygen demand	
DGR	Dangerous Goods Regulations (see IATA/DGR)	
DNEL	Derived No-Effect Level	
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval	
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identi- fier of substances commercially available within the EU (European Union)	
ED	Endocrine disruptor	
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-li- cence/)	
EINECS	European Inventory of Existing Commercial Chemical Substances	
ELINCS	European List of Notified Chemical Substances	
EmS	Emergency Schedule	
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control	
GB CLP	The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/720 (as amended)	
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)	
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions	
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)	
IATA	International Air Transport Association	

acc. to Regulation (EC) No. 1907/2006 (REACH)

## Diethyl ether ROTIDRY $\otimes 299,5 \%$ ( $\leq 60 \text{ ppm H}_2O$ ), stabilized

# ® Foth

## article number: **AE04**

Abbr.	Descriptions of used abbreviations
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
log KOW	n-Octanol/water
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)
STEL	Short-term exposure limit
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

## Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

## List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H224	Extremely flammable liquid and vapour.
H302	Harmful if swallowed.
H336	May cause drowsiness or dizziness.

acc. to Regulation (EC) No. 1907/2006 (REACH)



## Diethyl ether ROTIDRY $\otimes$ 299,5 % ( $\leq$ 60 ppm H<sub>2</sub>O), stabilized

## article number: AE04

## Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.