acc. to Safe Work Australia - Code of Practice

### 2-Propanol ROTISOLV® ≥99,95 %, LC-MS-Grade

article number: AE73 date of compilation: 2016-04-28 Version: GHS 6.0 en

Replaces version of: 2022-12-20

Version: (GHS 5)

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### **Product identifier** 1.1

Identification of the substance **2-Propanol** ROTISOLV® ≥99,95 %, LC-MS-Grade

Article number AE73 CAS number 67-63-0

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for private purposes (household).

Food, drink and animal feedingstuffs.

#### Details of the supplier of the safety data sheet 1.3

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

sheet:

e-mail (competent person): sicherheit@carlroth.de

#### 1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

# **SECTION 2: Hazards identification**

### Classification of the substance or mixture

### Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

For full text of abbreviations: see SECTION 16

Australia (en) Page 1 / 15



Revision: 2024-03-02

acc. to Safe Work Australia - Code of Practice

### 2-Propanol ROTISOLV® ≥99,95 %, LC-MS-Grade

article number: AE73



### The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

### 2.2 Label elements

### Labelling

Signal word Danger

### **Pictograms**

GHS02, GHS07



### **Hazard statements**

H225 Highly flammable liquid and vapour
 H319 Causes serious eye irritation
 H336 May cause drowsiness or dizziness

### **Precautionary statements**

## **Precautionary statements - prevention**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking

### **Precautionary statements - response**

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P312 Call a POISON CENTER or doctor/physician if you feel unwell

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

### **Precautionary statements - storage**

P403+P233 Store in a well-ventilated place. Keep container tightly closed

P403+P235 Store in a well-ventilated place. Keep cool

### **Precautionary statements - disposal**

P501 Dispose of contents/container to industrial combustion plant

### 2.3 Other hazards

### Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

### **Endocrine disrupting properties**

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq 0.1\%$ .

Australia (en) Page 2 / 15

acc. to Safe Work Australia - Code of Practice

### 2-Propanol ROTISOLV® ≥99,95 %, LC-MS-Grade

article number: AE73



# **SECTION 3: Composition/information on ingredients**

### 3.1 Substances

Name of substance 2-Propanol

Molecular formula C<sub>3</sub>H<sub>8</sub>O

Molar mass  $60.1 \, \mathrm{g/_{mol}}$ 

CAS No 67-63-0

## **SECTION 4: First aid measures**

### 4.1 Description of first aid measures



### **General notes**

Take off contaminated clothing.

### Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

### **Following skin contact**

Rinse skin with water/shower. In all cases of doubt, or when symptoms persist, seek medical advice.

### Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

### **Following ingestion**

Rinse mouth. Call a doctor if you feel unwell.

### 4.2 Most important symptoms and effects, both acute and delayed

Vomiting, Irritation, Dizziness, Drowsiness, Narcosis

### 4.3 Indication of any immediate medical attention and special treatment needed

none

# **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media



### Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO<sub>2</sub>)

### Unsuitable extinguishing media

water jet

Australia (en) Page 3 / 15

acc. to Safe Work Australia - Code of Practice

### 2-Propanol ROTISOLV® ≥99,95 %, LC-MS-Grade

article number: AE73



### 5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

### **Hazardous combustion products**

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

## **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures



### For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

### 6.3 Methods and material for containment and cleaning up

### Advice on how to contain a spill

Covering of drains.

### Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

# **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Provision of sufficient ventilation.

### Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

Australia (en) Page 4 / 15

acc. to Safe Work Australia - Code of Practice

### 2-Propanol ROTISOLV® ≥99,95 %, LC-MS-Grade

article number: AE73



of vapours into cellars, flues and ditches.

# Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

### **Incompatible substances or mixtures**

Observe hints for combined storage.

### Consideration of other advice:

Ground/bond container and receiving equipment.

### **Ventilation requirements**

Use local and general ventilation.

### Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

#### Specific end use(s) 7.3

No information available.

# SECTION 8: Exposure controls/personal protection

#### 8.1 **Control parameters**

### **National limit values**

### **Occupational exposure limit values (Workplace Exposure Limits)**

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
AU	isopropyl alcohol (propan-2-ol)	67-63-0	WES	400	983	500	1,230				WES

### Notation

Ceiling-C

Ceiling value is a limit value above which exposure should not occur Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-STEL

minute period (unless otherwise specified)

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

### **Human health values**

### **Relevant DNELs and other threshold levels**

Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	500 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	1,000 mg/m³	human, inhalatory	worker (industry)	acute - systemic effects
DNEL	888 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic effects

Australia (en) Page 5 / 15

acc. to Safe Work Australia - Code of Practice

### 2-Propanol ROTISOLV® ≥99,95 %, LC-MS-Grade

article number: AE73



### **Environmental values**

### **Relevant PNECs and other threshold levels**

End- point	Threshold level	Organism	Environmental compartment	Exposure time
PNEC	140.9 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single instance)
PNEC	140.9 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	marine water	short-term (single instance)
PNEC	2,251 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	552 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	552 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	marine sediment	short-term (single instance)
PNEC	28 <sup>mg</sup> / <sub>kg</sub>	terrestrial organisms	soil	short-term (single instance)

### 8.2 Exposure controls

### Individual protection measures (personal protective equipment)

### **Eye/face protection**





Use safety goggle with side protection.

### Skin protection





### hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

### type of material

NBR (Nitrile rubber)

material thickness

0.4 mm

### breakthrough times of the glove material

>480 minutes (permeation: level 6)

### other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Australia (en) Page 6 / 15

acc. to Safe Work Australia - Code of Practice

### 2-Propanol ROTISOLV® ≥99,95 %, LC-MS-Grade

article number: AE73

### **Respiratory protection**





Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

## **Environmental exposure controls**

Keep away from drains, surface and ground water.

# **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state liquid

Colour colourless
Odour like: - alcohol
Odour threshold 1 – 196 ppm

Melting point/freezing point -89 °C

Boiling point or initial boiling point and boiling

range

82 – 83 °C at 1,013 hPa

Flammability flammable liquid in accordance with GHS criteria

Lower and upper explosion limit 2 vol% (LEL) - 13.4 vol% (UEL)

Flash point 12 °C (c.c.)

Auto-ignition temperature 425 °C (DIN 51794)

Decomposition temperature not relevant pH (value) 7 (20 °C)

Kinematic viscosity  $2.785 \, ^{\text{mm}^2} /_{\text{s}}$  at 20 °C Dynamic viscosity  $2.2 \, \text{mPa}$  s at 20 °C

Solubility(ies)

Water solubility miscible in any proportion

Partition coefficient

Partition coefficient n-octanol/water (log value): 0.05

Vapour pressure 43 hPa at 20 °C

Density and/or relative density

Density  $0.79 \, {}^{\rm g}/{}_{\rm cm^3}$  at 20  ${}^{\rm o}{\rm C}$ 

Relative vapour density 2.07 (air = 1)

Australia (en) Page 7 / 15



acc. to Safe Work Australia - Code of Practice

### 2-Propanol ROTISOLV® ≥99,95 %, LC-MS-Grade

article number: AE73

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard

classes:

There is no additional information.

Other safety characteristics:

Miscibility completely miscible with water

# SECTION 10: Stability and reactivity

### 10.1 Reactivity

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air. May form explosive peroxides.

### If heated

Risk of ignition.

### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

### 10.3 Possibility of hazardous reactions

**Exothermic reaction with:** strong oxidiser, Iron, Nitric acid, Strong acid, Aldehydes, Aluminium, Amines

Danger of explosion: Chlorates, Nitro compound, Hydrogen peroxide, Phosgene

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5 Incompatible materials

plastic and rubber

### 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5. Peroxides.

# **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

### Classification acc. to GHS

### **Acute toxicity**

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4. May be harmful if inhaled.

Australia (en) Page 8 / 15



acc. to Safe Work Australia - Code of Practice

### 2-Propanol ROTISOLV® ≥99,95 %, LC-MS-Grade

article number: AE73



Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
inhalation: vapour	LC50	37.5 <sup>mg</sup> / <sub>l</sub> /4h	rat		OECD-403
oral	LD50	5,045 <sup>mg</sup> / <sub>kg</sub>	rat		RTECS
dermal	LD50	12,800 <sup>mg</sup> / <sub>kg</sub>	rabbit		RTECS

### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

### **Germ cell mutagenicity**

Shall not be classified as germ cell mutagenic.

### Carcinogenicity

Shall not be classified as carcinogenic.

### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

### **Aspiration hazard**

Shall not be classified as presenting an aspiration hazard.

### Symptoms related to the physical, chemical and toxicological characteristics

### If swallowed

vomiting, nausea

### • If in eyes

Causes serious eye irritation

### • If inhaled

dizziness, fatigue, narcosis

### • If on skin

repeated exposure may cause skin dryness or cracking

### Other information

Other adverse effects: Headache, Vertigo, Dyspnoea

### 11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq$  0,1%.

Australia (en) Page 9 / 15

acc. to Safe Work Australia - Code of Practice

### 2-Propanol ROTISOLV® ≥99,95 %, LC-MS-Grade

article number: AE73



# **SECTION 12: Ecological information**

### 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

### **Aquatic toxicity (acute)**

Endpoint	Value	Species	Source	Exposure time
LC50	10,000 <sup>mg</sup> / <sub>l</sub>	fish	ECHA	96 h

### 12.2 Persistence and degradability

Theoretical Oxygen Demand:  $2.396 \frac{\text{mg}}{\text{mg}}$ Theoretical Carbon Dioxide:  $2.197 \frac{\text{mg}}{\text{mg}}$ 

### **Biodegradation**

The substance is readily biodegradable.

### **Process of degradability**

Process	Degradation rate	Time
biotic/abiotic	95 %	21 d
oxygen depletion	53 %	5 d

### 12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	0.05
---------------------------	------

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq$  0,1%.

### 12.7 Other adverse effects

Data are not available.

# **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

## Sewage disposal-relevant information

Do not empty into drains.

Australia (en) Page 10 / 15

acc. to Safe Work Australia - Code of Practice

### 2-Propanol ROTISOLV® ≥99,95 %, LC-MS-Grade

article number: AE73



### Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

### Relevant provisions relating to waste(Basel Convention)

### Properties of waste which render it hazardous

**H3** Flammable liquids

### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

# **SECTION 14: Transport information**

### 14.1 UN number

UN 1219
IMDG-Code UN 1219
ICAO-TI UN 1219

### 14.2 UN proper shipping name

UN RTDG ISOPROPANOL IMDG-Code ISOPROPANOL ICAO-TI Isopropanol

### 14.3 Transport hazard class(es)

UN RTDG 3
IMDG-Code 3
ICAO-TI 3

### 14.4 Packing group

UN RTDG II
IMDG-Code II
ICAO-TI II

# **14.5 Environmental hazards** non-environmentally hazardous acc. to the dan-

gerous goods regulations

### 14.6 Special precautions for user

There is no additional information.

## 14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

### 14.8 Information for each of the UN Model Regulations

Australia (en) Page 11 / 15

acc. to Safe Work Australia - Code of Practice

### 2-Propanol ROTISOLV® ≥99,95 %, LC-MS-Grade

article number: AE73

Transport informationNational regulationsAdditional information(UN RTDG)

UN number 1219
Class 3
Packing group II
Danger label(s) 3

Special provisions (SP)

**UN RTDG** 

Excepted quantities (EQ) E2

**UN RTDG** 

Limited quantities (LQ)

UN RTDG

**Emergency Action Code** 2YE

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name ISOPROPANOL

Particulars in the shipper's declaration UN1219, ISOPROPANOL, 3, II, 12°C c.c.

Marine pollutant -

Danger label(s) 3

3

Special provisions (SP)

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

EmS F-E, S-D

Stowage category B

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Isopropanol

Particulars in the shipper's declaration UN1219, Isopropanol, 3, II

Danger label(s) 3

Special provisions (SP) A180
Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

Australia (en) Page 12 / 15



acc. to Safe Work Australia - Code of Practice

### 2-Propanol ROTISOLV® ≥99,95 %, LC-MS-Grade

article number: AE73



# **SECTION 15: Regulatory information**

### Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

### National regulations(Australia)

### Australian Inventory of Chemical Substances(AICS)

Substance is listed.

### Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

### **National inventories**

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
JP	ISHA-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

### Legend

AIIC

CICR CSCL-ENCS DSL ECSI IECSC

Australian Inventory of Industrial Chemicals
Chemical Inventory and Control Regulation
List of Existing and New Chemical Substances (CSCL-ENCS)
Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China
National Inventory of Chemical Substances
Inventory of Existing and New Chemical Substances (ISHA-ENCS)

INSQ ISHA-ENCS Inventory of Existing and New Chemical Substances (ISHA-ENCS)

KECI Korea Existing Chemicals Inventory NCI National Chemical Inventory
NZIOC New Zealand Inventory of Chemicals
PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg. REACH registered substances

Taiwan Chemical Substance Inventory

**TSCA Toxic Substance Control Act** 

### 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

Australia (en) Page 13 / 15

acc. to Safe Work Australia - Code of Practice

## 2-Propanol ROTISOLV® ≥99,95 %, LC-MS-Grade

article number: AE73



# **SECTION 16: Other information**

# Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
15.1		National inventories: change in the listing (table)	yes

### **Abbreviations and acronyms**

Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
STEL	Short-term exposure limit
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)

Australia (en) Page 14 / 15

acc. to Safe Work Australia - Code of Practice

### 2-Propanol ROTISOLV® ≥99,95 %, LC-MS-Grade

article number: AE73



Abbr.	Descriptions of used abbreviations
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants

### Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Australia (en) Page 15 / 15