acc. to Safe Work Australia - Code of Practice

Wijs-solution 0,1 mol ICl/l - 0,2 N

article number: CN36 Version: GHS 2.0 en

Replaces version of: 2019-06-03

Version: (GHS 1)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance Wijs-solution 0,1 mol ICl/l - 0,2 N

Article number **CN36**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for squirting or spraying. Do not use

for products which come into direct contact with the skin. Do not use for products which come into contact with foodstuffs. Do not use for private

purposes (household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr, 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

e-mail (competent person): sicherheit@carlroth.de

1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class		Hazard class and category	Hazard statement
2.6	Flammable liquid	3	Flam. Liq. 3	H226
2.16	16 Substance or mixture corrosive to metals		Met. Corr. 1	H290
3.2	Skin corrosion/irritation	1	Skin Corr. 1	H314
3.3	Serious eye damage/eye irritation	1	Eye Dam. 1	H318

Page 1 / 16 Australia (en)



date of compilation: 2019-06-03

Revision: 2022-07-25

acc. to Safe Work Australia - Code of Practice

Wijs-solution 0,1 mol ICl/l - 0,2 N

article number: CN36

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS02, GHS05





Hazard statements

H226 Flammable liquid and vapour H290 May be corrosive to metals

H314 Causes severe skin burns and eye damage

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P260 Do not breathe dusts or mists
P280 Wear eye protection/face protection

Precautionary statements - response

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

Precautionary statements - storage

P403+P235 Store in a well-ventilated place. Keep cool

Hazardous ingredients for labelling: Acetic acid ... %, Iodine trichloride

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Australia (en) Page 2 / 16



acc. to Safe Work Australia - Code of Practice

Wijs-solution 0,1 mol ICl/l - 0,2 N

article number: CN36



SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Acetic acid %	CAS No 64-19-7	95 – < 100	Flam. Liq. 3 / H226 Skin Corr. 1A / H314 Eye Dam. 1 / H318		B(a)

Notes

B(a): The classification refers to an aqueous solution

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off immediately all contaminated clothing. Self-protection of the first aider.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

After contact with skin, wash immediately with plenty of water. Immediate medical treatment required because corrosive injuries that are not treated are hard to cure.

Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

Following ingestion

Rinse mouth immediately and drink plenty of water. Call a physician immediately. If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

4.2 Most important symptoms and effects, both acute and delayed

Corrosion, Risk of blindness, Gastric perforation, Risk of serious damage to eyes, Dyspnoea, Gastrointestinal complaints, Vomiting, Circulatory collapse, Corneal opacity

4.3 Indication of any immediate medical attention and special treatment needed

none

Australia (en) Page 3 / 16

acc. to Safe Work Australia - Code of Practice

Wijs-solution 0,1 mol ICl/l - 0,2 N

article number: CN36



SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours may form explosive mixtures with air.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂), May produce toxic fumes of carbon monoxide if burning.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus. Wear full chemical protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. The product is an acid. Before discharge into sewage plants the product normally needs to be neutralised. Danger of explosion.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

Australia (en) Page 4 / 16

acc. to Safe Work Australia - Code of Practice

Wijs-solution 0,1 mol ICl/l - 0,2 N

article number: CN36



6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation. Use extractor hood (laboratory). Handle and open container with care. Clear contaminated areas thoroughly.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
AU	acetic acid	64-19-7	WES	10	25	15	37				WES
AU	iodine	7553-56- 2	WES					0.1	1		WES

Australia (en) Page 5 / 16

acc. to Safe Work Australia - Code of Practice

Wijs-solution 0,1 mol ICl/l - 0,2 N

article number: CN36



Ceiling-C STEL

Ceiling value is a limit value above which exposure should not occur Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-

minute period (unless otherwise specified)

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8

hours time-weighted average (unless otherwise specified)

8.2 **Exposure controls**

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection. Wear face protection.

Skin protection





hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

type of material

Butyl caoutchouc (butyl rubber)

material thickness

0,3 mm

breakthrough times of the glove material

>480 minutes (permeation: level 6)

Splash protection - Protective gloves

• type of material: FKM: fluoro-elastomer

material thickness: 0,7mm

• breakthrough times of the glove material: >60 minutes (permeation: level 3)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection





Page 6 / 16 Australia (en)



acc. to Safe Work Australia - Code of Practice

Wijs-solution 0,1 mol ICl/l - 0,2 N

article number: CN36



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Colour red brown
Odour stinging
Melting point/freezing point 16.64 °C

Boiling point or initial boiling point and boiling

range

118 °C

Flammability flammable liquid in accordance with GHS criteria

Lower and upper explosion limit 148 g/m³ (LEL) - 430 g/m³ (UEL) /

4 vol% (LEL) - 17 vol% (UEL)

Flash point 40 °C
Auto-ignition temperature 485 °C

Decomposition temperature not relevant pH (value) $<1 (20 \, ^{\circ}\text{C})$

Kinematic viscosity not determined

Solubility(ies)

Water solubility miscible in any proportion

Partition coefficient

Partition coefficient n-octanol/water (log value): this information is not available

Vapour pressure 16 hPa at 20 °C

Density and/or relative density

Density 1.062 ^g/_{cm³} at 20 °C

Relative vapour density information on this property is not available

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

Australia (en) Page 7 / 16

acc. to Safe Work Australia - Code of Practice

Wijs-solution 0,1 mol ICl/l - 0,2 N

article number: CN36



9.2 Other information

Information with regard to physical hazard

classes:

Corrosive to metals category 1: corrosive to metals

Other safety characteristics:

Miscibility completely miscible with water

SECTION 10: Stability and reactivity

10.1 Reactivity

The mixture contains reactive substance(s). Risk of ignition. Substance or mixture corrosive to metals.

If heated

Risk of ignition. Vapours may form explosive mixtures with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Strong alkali, Peroxides, for example hydrogen peroxide, Permanganates, for example potassium permanganate, Oxidisers, Metal, Iron and steel, Zinc, Aldehyde, Alcohol, Nitric acid

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

different metals

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Acetic acid %	64-19-7	oral	LD50	3,310 ^{mg} / _{kg}	rat

Australia (en) Page 8 / 16

acc. to Safe Work Australia - Code of Practice

Wijs-solution 0,1 mol ICl/l - 0,2 N

article number: CN36



Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects)

• If in eyes

causes burns, Causes serious eye damage, risk of blindness

• If inhaled

Data are not available.

• If on skin

causes severe burns, causes poorly healing wounds

Other information

Irritant, Corrosive, Dyspnoea, Gastrointestinal complaints, Vomiting, Circulatory collapse, Corneal opacity, Liver and kidney damage

11.2 Endocrine disrupting properties

None of the ingredients are listed.

Australia (en) Page 9 / 16

acc. to Safe Work Australia - Code of Practice

Wijs-solution 0,1 mol ICl/l - 0,2 N

article number: CN36



SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life.

Aquatic toxicity (acute) of components of the mixture

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
Acetic acid %	64-19-7	LC50	>300.8 ^{mg} / _l	fish	96 h
Acetic acid %	64-19-7	EC50	>300.8 ^{mg} / _l	aquatic invertebrates	48 h
Acetic acid %	64-19-7	ErC50	>300.8 ^{mg} / _l	algae	72 h

Biodegradation

Data are not available.

12.2 Process of degradability

Degradability of components of the mixture Name of substance CAS No Process Degradation rate Time Method Source Acetic acid ... % 64-19-7 biotic/abiotic 99 % 30 d

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Acetic acid %	64-19-7	3.16	-0.17 (pH value: 7, 25 °C)	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

Australia (en) Page 10 / 16

acc. to Safe Work Australia - Code of Practice

Wijs-solution 0,1 mol ICl/l - 0,2 N

article number: CN36



SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H3 Flammable liquids

H8 Corrosives

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number

UN RTDG UN 2789

IMDG-Code UN 2789 ICAO-TI UN 2789

14.2 UN proper shipping name

UN RTDGACETIC ACID SOLUTIONIMDG-CodeACETIC ACID SOLUTIONICAO-TIAcetic acid solution

14.3 Transport hazard class(es)

UN RTDG 8 (3)

IMDG-Code 8 (3) ICAO-TI 8 (3)

14.4 Packing group

UN RTDG II
IMDG-Code II
ICAO-TI II

14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

gerous goods regulations

Australia (en) Page 11 / 16

acc. to Safe Work Australia - Code of Practice

Wijs-solution 0,1 mol ICl/l - 0,2 N

article number: CN36



There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport informationNational regulationsAdditional information(UN RTDG)

UN number 2789
Class 8
Subsidiary risk(s) 3
Packing group II
Danger label(s) 8+3





Special provisions (SP)

UN RTDG

Excepted quantities (EQ)

UN RTDG

Limited quantities (LQ)

UN RTDG

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name ACETIC ACID SOLUTION

Particulars in the shipper's declaration UN2789, ACETIC ACID SOLUTION, 8 (3), II, 40°C

c.c.

Marine pollutant -

Danger label(s) 8+3





Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L
EmS F-E, S-C

Stowage category A

Segregation group 1 - Acids

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Acetic acid solution

Particulars in the shipper's declaration UN2789, Acetic acid solution, 8 (3), II

Danger label(s) 8+3





Australia (en) Page 12 / 16



acc. to Safe Work Australia - Code of Practice

Wijs-solution 0,1 mol ICl/l - 0,2 N

article number: CN36

Excepted quantities (EQ) E2 0,5 L Limited quantities (LQ)



SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

All ingredients are listed or exempt from listing.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	not all ingredients are listed
CA	NDSL	not all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

AIIC CICR CSCL-ENCS DSL ECSI

Australian Inventory of Industrial Chemicals
Chemical Inventory and Control Regulation
List of Existing and New Chemical Substances (CSCL-ENCS)
Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China
National Inventory of Chemical Substances
Korea Existing Chemicals Inventory **IECSC**

NATION INVENTION OF CHEMICAL SUBSTANCES

KECI Korea Existing Chemicals Inventory

NDSL Non-domestic Substances List (NDSL)

NZIOC New Zealand Inventory of Chemicals

PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)

REACH Reg. REACH registered substances

Taiwan Chemical Substance Inventory Toxic Substance Control Act

Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

Page 13 / 16 Australia (en)

acc. to Safe Work Australia - Code of Practice

Wijs-solution 0,1 mol ICl/l - 0,2 N

article number: CN36



SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals

("Purple book").

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1		The most important adverse physicochemical, human health and environmental effects: Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. The product is combustible and can be ignited by potential ignition sources.	yes
2.2		Hazard statements: change in the listing (table)	yes
2.2		Precautionary statements - response: change in the listing (table)	yes
2.2	Hazardous ingredients for labelling: Acetic acid	Hazardous ingredients for labelling: Acetic acid %, Iodine trichloride	yes
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Danger		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2	contains: Acetic acid		yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
COD	Chemical oxygen demand

Australia (en) Page 14 / 16

Safety data sheet Safety data sheet acc. to Safe Work Australia - Code of Practice

Wijs-solution 0,1 mol ICl/l - 0,2 N

article number: CN36



Abbr.	Descriptions of used abbreviations	
DGR	Dangerous Goods Regulations (see IATA/DGR)	
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval	
EINECS	European Inventory of Existing Commercial Chemical Substances	
ELINCS	European List of Notified Chemical Substances	
EmS	Emergency Schedule	
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control	
Eye Dam.	Seriously damaging to the eye	
Eye Irrit.	Irritant to the eye	
Flam. Liq.	Flammable liquid	
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations	
IATA	International Air Transport Association	
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)	
ICAO	International Civil Aviation Organization	
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air	
IMDG	International Maritime Dangerous Goods Code	
IMDG-Code	International Maritime Dangerous Goods Code	
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval	
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval	
LEL	Lower explosion limit (LEL)	
log KOW	n-Octanol/water	
NLP	No-Longer Polymer	
PBT	Persistent, Bioaccumulative and Toxic	
ppm	Parts per million	
Skin Corr.	Corrosive to skin	
Skin Irrit.	Irritant to skin	
STEL	Short-term exposure limit	
TWA	Time-weighted average	
UEL	Upper explosion limit (UEL)	
UN RTDG	UN Recommendations on the Transport of Dangerous Good	
vPvB	Very Persistent and very Bioaccumulative	
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants	

Page 15 / 16 Australia (en)

acc. to Safe Work Australia - Code of Practice

Wijs-solution 0,1 mol ICl/l - 0,2 N

article number: CN36



Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Australia (en) Page 16 / 16