acc. to Regulation (EC) No. 1907/2006 (REACH)



Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80 Version: 6.0 en Replaces version of: 2022-12-20 Version: (5)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance	Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure
Article number	CN80
Index No (GB CLP)	601-022-00-9
EC number	215-535-7
CAS number	1330-20-7
Alternative name(s)	Dimethylbenzol
	• • • • • •

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Uses advised against:

Laboratory chemical Laboratory and analytical use Industrial uses Professional uses

Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household). Food, drink and animal feedingstuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 Telefax: +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data Department Health, Safety and Environment sheet:

e-mail (competent person):

sicherheit@carlroth.de

Emergency telephone number 1.4

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

date of compilation: 2016-06-28

Revision: 2024-03-02

acc. to Regulation (EC) No. 1907/2006 (REACH)



Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80

SECTION 2: Hazards identification

Classification of the substance or mixture 2.1

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	3	Flam. Liq. 3	H226
3.1D	Acute toxicity (dermal)	4	Acute Tox. 4	H312
3.1I	Acute toxicity (inhal.)		Acute Tox. 4	H332
3.2	2 Skin corrosion/irritation		Skin Irrit. 2	H315
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.8R	3.8R Specific target organ toxicity - single exposure (respirat- ory tract irritation)		STOT SE 3	H335
3.9	3.9 Specific target organ toxicity - repeated exposure		STOT RE 2	H373
3.10	Aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS08



Hazard statements

H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H312+H332	Harmful in contact with skin or if inhaled
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H373	May cause damage to organs (central nervous system, liver, kidney) through
H373	May cause damage to organs (central nervous system, liver, kidney) through prolonged or repeated exposure

Precautionary statements

Precautionary statements - prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P260	Do not breathe mist/vapours
P280	Wear protective gloves/protective clothing/eye protection/face protection

acc. to Regulation (EC) No. 1907/2006 (REACH)

Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure



article number: CN80

Precautionary statements - response

P301+P310 P303+P361+P353	IF SWALLOWED: Immediately call a POISON CENTER/doctor IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin
	with water [or shower]
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\ge 0,1\%$.

SECTION 3: Composition/information on ingredients

Substances	
Name of substance	Xylene (isomers)
Molecular formula	C ₈ H ₁₀
Molar mass	106,2 ^g / _{mol}
CAS No	1330-20-7
EC No	215-535-7
Index No (GB CLP)	601-022-00-9

Substance, Specific Conc. Linnes, M-factors, Are					
Specific Conc. Limits	M-Factors	ATE	Exposure route		
-	-	1.100 ^{mg} / _{kg} >11 ^{mg} / _l /4h	dermal inhalation: vapour		

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

acc. to Regulation (EC) No. 1907/2006 (REACH)

Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure



article number: CN80

Following ingestion

Call a physician immediately. Observe aspiration hazard if vomiting occurs.

4.2 Most important symptoms and effects, both acute and delayed

Irritation, Cough, Dyspnoea, Headache, Dizziness, Vertigo, Unconsciousness, Nausea, Vomiting, Aspiration hazard

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapourair mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

acc. to Regulation (EC) No. 1907/2006 (REACH)

Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure



article number: CN80

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Keep any substance that emits harmful vapours or gases in a place that allows these to be permanently extracted. Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

acc. to Regulation (EC) No. 1907/2006 (REACH)



Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
EU	xylene	1330-20- 7	IOELV	50	221	100	442			pure, H	2000/39/ EC
GB	xylene, mixture of isomers	1330-20- 7	WEL	50	220	100	441				EH40/ 2005

Notation

Ceiling value is a limit value above which exposure should not occur Absorbed through the skin Pure substance Ceiling-C

Н pure STEL

Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified) TWA

Biological limit values

Coun try	Name of agent	CAS No	Parameter	Nota tion	Identi- fier	Value	Material	Source
GB	xylene, mixture of isomers	1330-20- 7	methylhippuric acids	crea	BMGV	650 mmol/ mol	urine	EH40/ 2005

Notation

Creatinine crea

Human health values

Relevant DNELs and other threshold levels							
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time			
DNEL	221 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects			
DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects			
DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects			
DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - local effects			
DNEL	212 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic effects			

Environmental values

acc. to Regulation (EC) No. 1907/2006 (REACH)

Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure



article number: CN80

Relevant PNECs and other threshold levels							
End- point	Threshold level	Organism	Exposure time				
PNEC	0,327 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)			
PNEC	0,327 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)			
PNEC	6,58 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)			
PNEC	12,46 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)			
PNEC	12,46 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)			
PNEC	2,31 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)			

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a consider-able reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

FKM: fluoro-elastomer

material thickness

0,4 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

acc. to Regulation (EC) No. 1907/2006 (REACH)

Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure



article number: CN80

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 $^{\circ}$ C, colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	characteristic
Melting point/freezing point	-47,8 °C at 1.013 hPa (ECHA)
Boiling point or initial boiling point and boiling range	139,1 °C at 1.013 hPa (ECHA)
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	1,1 vol% (LEL) - 7 vol% (UEL)
Flash point	27 °C at 1.013 hPa (ECHA)
Auto-ignition temperature	463 °C at 1.013 hPa (ECHA) (auto-ignition temper- ature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	not determined
Dynamic viscosity	0,76 mPa s at 25 °C
Solubility(ies)	
Water solubility	156 ^{mg} / _l at 25 °C (ECHA)
Partition coefficient	
Partition coefficient n-octanol/water (log value):	3,15 (pH value: 7, 20 °C) (ECHA)
Soil organic carbon/water (log KOC)	2,73 (ECHA)
Vapour pressure	8,21 hPa at 20 °C
Density and/or relative density	
Density	0,85 – 0,88 ^g / _{cm³} at 20 °C
Relative vapour density	3,66 at 20 °C (air = 1)

acc. to Regulation (EC) No. 1907/2006 (REACH)

Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure



article number: CN80

	Particle characteristics	not relevant (liquid)
	Other safety parameters	
	Oxidising properties	none
2	Other information	
	Information with regard to physical hazard classes:	There is no additional information.
	Other safety characteristics:	
	Surface tension	28,7 ^N / _m

SECTION 10: Stability and reactivity

10.1 Reactivity

9.2

It's a reactive substance. Risk of ignition.

If heated

Risk of ignition. Vapours may form explosive mixtures with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Nitric acid, Sulphur, Sulphuric acid

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

Rubber articles, different plastics

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Harmful in contact with skin. Harmful if inhaled. GHS of the United Nations, annex 4. May be harmful if swallowed.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
inhalation: vapour	LC50	29 ^{mg} / _l /4h	rat		ECHA
oral	LD50	3.523 ^{mg} / _{kg}	rat		ECHA

acc. to Regulation (EC) No. 1907/2006 (REACH)

Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure



article number: CN80

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

May cause damage to organs (central nervous system, liver, kidney) through prolonged or repeated exposure.

Hazard category	Target organ	Exposure route
2	central nervous system	if exposed
2	liver	if exposed
2	kidney	if exposed

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

vomiting, nausea, aspiration hazard

• If in eyes

Causes serious eye irritation

• If inhaled

vertigo, dizziness, unconsciousness, headache, Irritation to respiratory tract, cough, Dyspnoea

• If on skin

causes skin irritation, risk of absorption via the skin

Other information

Other adverse effects: Liver and kidney damage

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\ge 0,1\%$.

11.3 Information on other hazards

There is no additional information.

acc. to Regulation (EC) No. 1907/2006 (REACH)



Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)

Aquatic toxicity (acute)				
Endpoint	Value	Species	Source	Exposure time
LC50	2,6 ^{mg} / _l	rainbow trout	ECHA	96 h
ErC50	4,7 ^{mg} / _l	algae	ECHA	72 h

Aquatic toxicity (chronic)

Endpoint	Value	Species	Source	Exposure time
EC50	2,2 ^{mg} / _l	algae	ECHA	73 h

12.2 Persistence and degradability

Theoretical Oxygen Demand: 3,165 ^{mg}/_{mg} Theoretical Carbon Dioxide: 3,316 ^{mg}/_{mg}

Biodegradation

The substance is readily biodegradable.

Process of degradability		
Process	Degradation rate	Time
oxygen depletion	98 %	28 d

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	3,15 (pH value: 7, 20 °C) (ECHA)	
BCF	>5,5 – <12,2 (ECHA)	

12.4 Mobility in soil

Henry's law constant	623 ^{Pa m³} / _{mol} at 25 °C (ECHA)
The Organic Carbon normalised adsorption coefficient	2,73 (ECHA)

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

12.7 Other adverse effects

Data are not available.

acc. to Regulation (EC) No. 1907/2006 (REACH)



Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Properties of waste which render it hazardous

- **HP 3** flammable
- HP 4 irritant skin irritation and eye damage
- HP 5 specific target organ toxicity (STOT)/aspiration toxicity
- HP 6 acute toxicity

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number or ID number

	ADRRID	UN 1307
	IMDG-Code	UN 1307
	ICAO-TI	UN 1307
14.2	UN proper shipping name	
	ADRRID	XYLENES
	IMDG-Code	XYLENES
	ICAO-TI	Xylenes
14.3	Transport hazard class(es)	
	ADRRID	3
	IMDG-Code	3
	ICAO-TI	3
14.4	Packing group	
	ADRRID	III

acc. to Regulation (EC) No. 1907/2006 (REACH)



Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80	

	IMDG-Code	III			
	ICAO-TI	III			
14.5	Environmental hazards	non-environmentally hazardous acc. to the dan- gerous goods regulations			
14.6	Special precautions for user				
	Provisions for dangerous goods (ADR) should b	be complied within the premises.			
14.7	Maritime transport in bulk according to IMC) instruments			
	The cargo is not intended to be carried in bulk.				
14.8	Information for each of the UN Model Regul	ations			
	Agreement concerning the International Ca information	rriage of Dangerous Goods by Road (ADR)Additiona			
	Proper shipping name	XYLENES			
	Particulars in the transport document	UN1307, XYLENES, 3, III, (D/E)			
	Classification code	F1			
	Danger label(s)	3			
	Excepted quantities (EQ)	E1			
	Limited quantities (LQ)	5 L			
	Transport category (TC)	3			
	Tunnel restriction code (TRC)	D/E			
	Hazard identification No	30			
	Emergency Action Code	3Y			
	Regulations concerning the International Carriage of Dangerous Goods by Rail (RID)Additional information				
	Classification code	F1			
	Danger label(s)	3			
	Excepted quantities (EQ)	E1			
	Limited quantities (LQ)	5 L			
	Transport category (TC)	3			
	Hazard identification No	30			

acc. to Regulation (EC) No. 1907/2006 (REACH)

Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure



article number: CN80

International Maritime Dangerous Goods C	ode (IMDG) - Additional information
Proper shipping name	XYLENES
Particulars in the shipper's declaration	UN1307, XYLENES, 3, III, 27°C c.c.
Marine pollutant	-
Danger label(s)	3
Special provisions (SP)	223
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-E, S-D
Stowage category	А
International Civil Aviation Organization (I	CAO-IATA/DGR) - Additional information
Proper shipping name	Xylenes
Particulars in the shipper's declaration	UN1307, Xylenes, 3, III
Danger label(s)	3
Special provisions (SP)	A3
Excepted quantities (EQ)	E1
Limited quantities (LQ)	10 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Seveso Directive

2012/	18/EU (Seveso III)			
Νο	Dangerous substance/hazard categories	Qualifying quantity plication of lower quirer	and upper-tier re-	Notes
P5c	flammable liquids (cat. 2, 3)	5.000	50.000	51)

Notation

51) Flammable liquids, categories 2 or 3 not covered by P5a and P5b

Deco-Paint Directive

acc. to Regulation (EC) No. 1907/2006 (REACH)

Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure



article number: CN80

VOC content	100 %
VOC content	880 ^g / _l

Industrial Emissions Directive (IED)

VOC content	100 %
VOC content	880 ^g /l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

Pollutant release and transfer registers (PRTR)			
Name of substance	CAS No	Remarks	Threshold for releases to air (kg/year)
Xylene (isomers)	1330-20-7	(17) (11)	

Legend

Single pollutants are to be reported if the threshold for BTEX (the sum parameter of benzene, toluene, ethyl benzene, xy-(11)

lenes) is exceeded Total mass of xylene (ortho-xylene, meta-xylene, para-xylene) (17)

Water Framework Directive (WFD)

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
Xylene (isomers)	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment		a)	

Legend

a) Indicative list of the main pollutants

Regulation on the marketing and use of explosives precursors

not listed

Regulation on drug precursors

not listed

Regulation on substances that deplete the ozone layer (ODS)

not listed

Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

Regulation on persistent organic pollutants (POP)

not listed

acc. to Regulation (EC) No. 1907/2006 (REACH)



Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80

National regulations(GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list not listed

Restrictions according to GB REACH, Annex 17

gerous substances with restrictions (GB REACH, Annex 17)			
Name of substance	Name acc. to inventory	CAS No	No
Xylene (isomers)	this product meets the criteria for classi- fication in accordance with Regulation No 1272/2008/EC		3
Xylene (isomers)	flammable / pyrophoric		40

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status	
AU	AIIC	substance is listed	
СА	DSL	substance is listed	
CN	IECSC	substance is listed	
EU	ECSI	substance is listed	
EU	REACH Reg.	substance is listed	
JP	CSCL-ENCS	substance is listed	
KR	KECI	substance is listed	
MX	INSQ	substance is listed	
NZ	NZIoC	substance is listed	
PH	PICCS	substance is listed	
TR	CICR	substance is listed	
TW	TCSI	substance is listed	
US	TSCA	substance is listed (ACTIVE)	
VN	NCI	substance is listed	
VN	NCI	substance is listed	

Legend

Legena	
AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NCI	National Chemical Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

acc. to Regulation (EC) No. 1907/2006 (REACH)

Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure



article number: CN80

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
15.1	VOC content: 100 % 860 ^g / _l	VOC content: 100 %	yes
15.1		VOC content: 880 ^g / _l	yes
15.1	VOC content: 860 ^g / _l	VOC content: 880 ^g / _l	yes
15.1		National inventories: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2000/39/EC	Commission Directive establishing a first list of indicative occupational exposure limit values in imple- mentation of Council Directive 98/24/EC
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concern- ing the International Carriage of Dangerous Goods by Road)
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identi- fier of substances commercially available within the EU (European Union)
ED	Endocrine disruptor
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-li- cence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control

acc. to Regulation (EC) No. 1907/2006 (REACH)

® §ROTH

Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80

Abbr.	Descriptions of used abbreviations
GB CLP	The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/720 (as amended)
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)
STEL	Short-term exposure limit
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

acc. to Regulation (EC) No. 1907/2006 (REACH)

Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure



article number: CN80

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs (central nervous system, liver, kidney) through prolonged or repeated expos- ure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.