

Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: **CN80** Version: **6.0 en** Replaces version of: 20.12.2022 Version: (5)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Identification of the substanceXylene (isomers) ≥98,5 %, Ph.Helv., extra pureArticle numberCN80Registration number (REACH)01-2119488216-32-xxxxIndex number in CLP Annex VI601-022-00-9EC number215-535-7CAS number1330-20-7Alternative name(s)Dimethylbenzol

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Laboratory chemical Laboratory and analytical use Industrial uses Professional uses

Uses advised against:

Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household). Food, drink and animal feedingstuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data Department Health, Safety and Environment sheet:

e-mail (competent person):

sicherheit@carlroth.de

1.4 Emergency telephone number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

date of compilation: 28.06.2016 Revision: 02.03.2024

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	3	Flam. Liq. 3	H226
3.1D	Acute toxicity (dermal)	4	Acute Tox. 4	H312
3.1I	Acute toxicity (inhal.)	4	Acute Tox. 4	H332
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.8R	Specific target organ toxicity - single exposure (respirat- ory tract irritation)	3	STOT SE 3	H335
3.9	Specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
3.10	Aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word Danger

Pictograms



Hazard statements

H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H312+H332	Harmful in contact with skin or if inhaled
H315	Causes skin irritation
H319	Causes serious eye irritation
H335 H373	May cause respiratory irritation May cause damage to organs (central nervous system, liver, kidney) through prolonged or repeated exposure

Precautionary statements

Precautionary statements - prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking
P260	Do not breathe mist/vapours
P280	Wear protective gloves/protective clothing/eye protection/face protection

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80

Precautionary statements - response

P301+P310 P303+P361+P353	IF SWALLOWED: Immediately call a POISON CENTER/doctor IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin
	with water [or shower]
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger



H304May be fatal if swallowed and enters airways.H335May cause respiratory irritation.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\ge 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance	Xylene (isomers)		
Molecular formula	C ₈ H ₁₀		
Molar mass	106,2 ^g / _{mol}		
REACH Reg. No	01-2119488216-32-xxxx		
CAS No	1330-20-7		
EC No	215-535-7		
Index No	601-022-00-9		

Substance, Specific Conc. Limits, M-factors, ATE						
Specific Conc. Limits M-Factors ATE Exposure rou						
-	-	1.100 ^{mg} / _{kg} >11 ^{mg} / _l /4h	dermal inhalation: vapour			



according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

Following ingestion

Call a physician immediately. Observe aspiration hazard if vomiting occurs.

4.2 Most important symptoms and effects, both acute and delayed

Irritation, Cough, Dyspnoea, Headache, Dizziness, Vertigo, Unconsciousness, Nausea, Vomiting, Aspiration hazard

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapourair mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight.

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Keep any substance that emits harmful vapours or gases in a place that allows these to be permanently extracted. Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
EU	xylene	1330-20- 7	IOELV	50	221	100	442			pure, H	2000/39/ EC
MT	xylene, mixture of isomers	1330-20- 7	OELV	50	221	100	442			H, pure	CAP. 424

Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur H Absorbed through the skin pure Pure substance STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15minute period (unless otherwise specified) TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Human health values

Relevant DNELs and other threshold levels							
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time			
DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects			
DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects			
DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects			
DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - local effects			
DNEL	212 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic effects			



according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80

Environm	nvironmental values						
Relevant PNECs and other threshold levels							
End- point	Threshold level	Organism	Environmental com- partment	Exposure time			
PNEC	0,327 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)			
PNEC	0,327 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)			
PNEC	6,58 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)			
PNEC	12,46 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)			
PNEC	12,46 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)			
PNEC	2,31 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)			

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a consider-able reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

FKM: fluoro-elastomer

material thickness

0,4 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 $^{\circ}$ C, colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	characteristic
Melting point/freezing point	-47,8 °C at 1.013 hPa (ECHA)
Boiling point or initial boiling point and boiling range	139,1 °C at 1.013 hPa (ECHA)
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	1,1 vol% (LEL) - 7 vol% (UEL)
Flash point	27 °C at 1.013 hPa (ECHA)
Auto-ignition temperature	463 °C at 1.013 hPa (ECHA) (auto-ignition temper- ature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	not determined
Dynamic viscosity	0,76 mPa s at 25 °C
Solubility(ies)	
Water solubility	156 ^{mg} / _l at 25 °C (ECHA)
Partition coefficient	
Partition coefficient n-octanol/water (log value):	3,15 (pH value: 7, 20 °C) (ECHA)
Soil organic carbon/water (log KOC)	2,73 (ECHA)
Vapour pressure	8,21 hPa at 20 °C
Density and/or relative density	
Density	0,85 – 0,88 ^g / _{cm³} at 20 °C
Relative vapour density	3,66 at 20 °C (air = 1)

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80

	Particle characteristics	not relevant (liquid)
	Other safety parameters	
	Oxidising properties	none
9.2	Other information	
	Information with regard to physical hazard classes:	There is no additional information.
	Other safety characteristics:	
	Surface tension	28,7 ^N / _m
	Temperature class (EU, acc. to ATEX)	T1 Maximum permissible surface temperature on the equipment: 450°C

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition.

If heated

Risk of ignition. Vapours may form explosive mixtures with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Nitric acid, Sulphur, Sulphuric acid

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

Rubber articles, different plastics

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Harmful in contact with skin. Harmful if inhaled.

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80

Acute toxicity							
Exposure route	Endpoint	Value	Species	Method	Source		
inhalation: vapour	LC50	29 ^{mg} / _l /4h	rat		ECHA		
oral	LD50	3.523 ^{mg} / _{kg}	rat		ECHA		

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

May cause damage to organs (central nervous system, liver, kidney) through prolonged or repeated exposure.

Hazard category	Target organ	Exposure route
2	central nervous system	if exposed
2	liver	if exposed
2	kidney	if exposed

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

vomiting, nausea, aspiration hazard

• If in eyes

Causes serious eye irritation

If inhaled

vertigo, dizziness, unconsciousness, headache, Irritation to respiratory tract, cough, Dyspnoea

• If on skin

causes skin irritation, risk of absorption via the skin

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80

Other information

Other adverse effects: Liver and kidney damage

- **11.2** Endocrine disrupting properties Does not contain an endocrine disruptor (ED) at a concentration of $\ge 0,1\%$.
- 11.3 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)					
Endpoint	Value	Species	Source	Exposure time	
LC50	2,6 ^{mg} / _l	rainbow trout	ECHA	96 h	
ErC50	4,7 ^{mg} / _l	algae	ECHA	72 h	

Aquatic toxicity (chronic)

Endpoint	Value	Species	Source	Exposure time
EC50	2,2 ^{mg} / _l	algae	ECHA	73 h

12.2 Persistence and degradability

Theoretical Oxygen Demand: 3,165 ^{mg}/_{mg} Theoretical Carbon Dioxide: 3,316 ^{mg}/_{mg}

Biodegradation

The substance is readily biodegradable.

Process of degradability		
Process	Degradation rate	Time
oxygen depletion	98 %	28 d

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	3,15 (pH value: 7, 20 °C) (ECHA)
BCF	>5,5 – <12,2 (ECHA)

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80

12.4 Mobility in soil

ſ	Henry's law constant	623 ^{Pa m³} / _{mol} at 25 °C (ECHA)
	The Organic Carbon normalised adsorption coefficient	2,73 (ECHA)

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\ge 0,1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Properties of waste which render it hazardous

- **HP3** flammable
- HP 4 irritant skin irritation and eye damage
- HP 5 specific target organ toxicity (STOT)/aspiration toxicity
- HP 6 acute toxicity

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80

14.1UN number or ID numberADRUN 1307IMDG-CodeUN 1307ICAO-TIUN 130714.2UN proper shipping nameADRXYLENESIMDG-CodeXYLENESICAO-TIXylenes1CAO-TIXylenes1CAO-TISinger shippingIMDG-Code3ICAO-TI3IMDG-Code3IMDG-Code3IMDG-Code3ICAO-TI3IMDG-Code3ICAO-TI3ICAO-T	SEC	SECTION 14: Transport information			
IMDG-CodeUN 1307ICAO-TIUN 1307 HAP VI 1307ADRVILENESICAO-TIVILENESADRJolenesIMDG-CodeSilenesICAO-TISilenes <th>14.1</th> <th>UN number or ID number</th> <th></th>	14.1	UN number or ID number			
ICAO-TIUN 1307 14.2 IN proper shipping nameVI LENESADRXYLENESIMDG-CodeXYLENESICAO-TIXylenes 17.1 ADRXylenesIMDG-CodeXylen		ADR	UN 1307		
14.2UN proper shipping nameADRXYLENESIMDG-CodeXYLENESICAO-TIXylenes1ADRXansport hazard class(es)IMDG-Code3IMDG-Code3IMDG-Code3ICAO-TI3ICAO-TIAnternameICAO-TI3		IMDG-Code	UN 1307		
ADRXYLENESIMDG-CodeXYLENESICAO-TIXylenes14.3Transport hazard class(es)ADR3IMDG-Code3ICAO-TI3ICAO-TI3ADR3ICAO-TI3ICA		ICAO-TI	UN 1307		
IMDG-CodeXYLENESICAO-TIXylenes14.3Transport hazard class(es)ADR3IMDG-Code3IMDG-Code3ICAO-TI3ADRADRICAO-TI3ADR3ICAO-TI3ICAO-	14.2	UN proper shipping name			
ICAO-TIXylenes 14.0Transport hazard class(es) JADR3IMDG-Code3ICAO-TI3 Packing group JADRIII		ADR	XYLENES		
14.3 Transport hazard class(es) ADR 3 IMDG-Code 3 ICAO-TI 3 14.4 Packing group ADR III		IMDG-Code	XYLENES		
ADR 3 IMDG-Code 3 ICAO-TI 3 14.4 Packing group ADR III		ICAO-TI	Xylenes		
IMDG-Code 3 ICAO-TI 3 Packing group III	14.3	Transport hazard class(es)			
ICAO-TI 3 14.4 Packing group ADR III		ADR	3		
14.4 Packing group ADR III		IMDG-Code	3		
ADR III		ICAO-TI	3		
	14.4	Packing group			
		ADR	III		
IMDG-Code III		IMDG-Code	III		
ICAO-TI III		ICAO-TI	III		
14.5 Environmental hazardsnon-environmentally hazardous acc. to the dan- gerous goods regulations	14.5	Environmental hazards	non-environmentally hazardous acc. to the dan- gerous goods regulations		
14.6 Special precautions for user	14.6	Special precautions for user			
Provisions for dangerous goods (ADR) should be complied within the premises.					
14.7 Maritime transport in bulk according to IMO instruments	14.7		struments		
The cargo is not intended to be carried in bulk.		The cargo is not intended to be carried in bulk.			
14.8 Information for each of the UN Model Regulations	14.8	Information for each of the UN Model Regulation	ons		
Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)Additional information		Agreement concerning the International Carria information	ge of Dangerous Goods by Road (ADR)Additional		
Proper shipping name XYLENES		Proper shipping name	XYLENES		
Particulars in the transport document UN1307, XYLENES, 3, III, (D/E)		Particulars in the transport document	UN1307, XYLENES, 3, III, (D/E)		
Classification code F1		Classification code	F1		
Danger label(s) 3		Danger label(s)	3		



•	
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
Transport category (TC)	3
Tunnel restriction code (TRC)	D/E

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article	number:	CN80
untitie	number.	01100

Hazard identification No	30
International Maritime Dangerous Goods Code	(IMDG) - Additional information
Proper shipping name	XYLENES
Particulars in the shipper's declaration	UN1307, XYLENES, 3, III, 27°C c.c.
Marine pollutant	-
Danger label(s)	3
(
Special provisions (SP)	223
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-E, S-D
Stowage category	A
International Civil Aviation Organization (ICAO	-IATA/DGR) - Additional information
Proper shipping name	Xylenes
Particulars in the shipper's declaration	UN1307, Xylenes, 3, III
Danger label(s)	3
Special provisions (SP)	A3
Excepted quantities (EQ)	E1
Limited quantities (LQ)	10 L

SECTION 15: Regulatory information

15.1	Safety, health and envir	onmental regulations/leg	islation specific for the	substance or mixture

Relevant provisions of the European Union (EU)

Restrictions according to REACH, Annex XVII

angerous substances with restrictions (REACH, Annex XVII)				
Name of substance	Name acc. to inventory	CAS No	Restriction	No
Xylene (isomers)	this product meets the criteria for classification in accordance with Reg- ulation No 1272/2008/EC		R3	3
Xylene (isomers)	flammable / pyrophoric		R40	40
Xylene (isomers)	substances in tattoo inks and perman- ent make-up		R75	75

Legend R3

^{1.} Shall not be used in:

⁻ ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
tricks and jokes,
games for one or more participants, or any article intended to be used as such, even with ornamental aspects,

Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure



article number: CN80

Legend

 Articles not complying with paragraph 1 shall not be placed on the market.
 Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they

can be used as fuel in decorative oil lamps for supply to the general public, and

present an aspiration hazard and are labelled with H304.
 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation

 (CEN).
 5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and pack 5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:

(a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil – or even sucking the wick of lamps – may lead to life-threatening lung damage";
(b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter fluid may lead to life threatening lung damage';
(c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.';
1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended

1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:
 - metallic glitter intended mainly for decoration,
 - artificial snow and frost,

- 'whoopee' cushions,

- silly string aerosols,

- imitation excrement,

horns for parties,
decorative flakes and foams,

- artificial cobwebs,

- stink bombs.

2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

For professional users only. 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).

4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

R40

Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure



article number: CN80



8. Mixtures that do not contain the statement "Mixture for use in tattoos or permanent make-up" shall not be used for tattooing purposes.



Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80

Legend

9. This entry does not apply to substances that are gases at temperature of 20 °C and pressure of 101,3 kPa, or generate a vapour pressure of more than 300 kPa at temperature of 50 °C, with the exception of formaldehyde (CAS No 50-00-0, EC No 200-001-8).

10. This entry does not apply to the placing on the market of a mixture for use for tattooing purposes, or to the use of a mixture for tattooing purposes, when placed on the market exclusively as a medical device or an accessory to a medical device, within the meaning of Regulation (EU) 2017/745, or when used exclusively as a medical device or an accessory to a medical device, within the same meaning. Where the placing on the market or use may not be exclusively as a medical device or an accessory to a medical device or an accessory to a medical device, within the same meaning. Where the placing on the market or use may not be exclusively as a medical device or an accessory to a medical device, the requirements of Regulation (EU) 2017/745 and of this Regulation shall apply cumulatively.

List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list

Not listed.

Seveso Directive

2012/18/EU (Seveso III)				
Νο	Dangerous substance/hazard categories	Qualifying quantity plication of lower quire	(tonnes) for the ap- and upper-tier re- ments	Notes
P5c	flammable liquids (cat. 2, 3)	5.000	50.000	51)

Notation

51) Flammable liquids, categories 2 or 3 not covered by P5a and P5b

Deco-Paint Directive

VOC content	100 %
VOC content	880 ^g /l

Industrial Emissions Directive (IED)

VOC content	100 %
VOC content	880 ^g /l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

Pollutant release and transfer registers (PRTR)			
Name of substance	CAS No	Remarks	Threshold for releases to air (kg/year)
Xylene (isomers)	1330-20-7	(17) (11)	

Legend

(11) Single pollutants are to be reported if the threshold for BTEX (the sum parameter of benzene, toluene, ethyl benzene, xylenes) is exceeded

(17) Total mass of xylene (ortho-xylene, meta-xylene, para-xylene)

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

Water Framework Directive (WFD)

article number: CN80

ist of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
Xylene (isomers)	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment		a)	

Legend

a) Indicative list of the main pollutants

Regulation on the marketing and use of explosives precursors

not listed

Regulation on drug precursors

not listed

Regulation on substances that deplete the ozone layer (ODS)

not listed

Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

Regulation on persistent organic pollutants (POP)

not listed

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80

Country	Inventory	Status
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed
CICR CSCL-ENCS DSL ECSI IECSC INSQ KECI NCI NZIoC PICCS	Domestic Substances List EC Substance Inventory (E Inventory of Existing Chen National Inventory of Che Korea Existing Chemicals National Chemical Invent New Zealand Inventory of	Control Regulation Chemical Substances (CSCL-ENCS) (DSL) EINECS, ELINCS, NLP) mical Substances Produced or Imported in China emical Substances Inventory ory of Chemicals nemicals and Chemical Substances (PICCS) news ces ce Inventory

15.2 Chemical safety assessment

According to REACH, Article 14 (1) a chemical safety assessment has been carried out for this substance or components of this mixture when the substance has been registered in quantities of 10 tonnes or more per year per registrant.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
15.1	VOC content: 100 % 860 ^g / ₁	VOC content: 100 %	yes
15.1		VOC content: 880 ^g / _l	yes
15.1	VOC content: 860 ^g / _l	VOC content: 880 ^g / _l	yes
15.1		National inventories: change in the listing (table)	yes
15.2	Chemical Safety Assessment: No Chemical Safety Assessment has been car- ried out for this substance.	Chemical safety assessment: According to REACH, Article 14 (1) a chemical safety assessment has been carried out for this substance or components of this mixture when the substance has been registered in quantities of 10 tonnes or more per year per registrant.	yes

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2000/39/EC	Commission Directive establishing a first list of indicative occupational exposure limit values in imple- mentation of Council Directive 98/24/EC
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concern- ing the International Carriage of Dangerous Goods by Road)
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CAP. 424	Occupational Health and Safety Authority Act (CAP. 424)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identi- fier of substances commercially available within the EU (European Union)
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



Xylene (isomers) ≥98,5 %, Ph.Helv., extra pure

article number: CN80

Abbr.	Descriptions of used abbreviations
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
STEL	Short-term exposure limit
SVHC	Substance of Very High Concern
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs (central nervous system, liver, kidney) through prolonged or repeated expos- ure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.