acc. to Safe Work Australia - Code of Practice

Nickel powder ≥99 %, <63 µm

article number: CP22 date of compilation: 2017-07-31 Version: GHS 4.0 en

Replaces version of: 2022-08-05

Version: (GHS 3)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance Nickel powder ≥99 %, <63 µm

Article number CP22

CAS number 7440-02-0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for products which come into contact

with foodstuffs. Do not use for private purposes (household). Food, drink and animal feeding-

stuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 Telefax: +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data Department Health, Safety and Environment

sheet:

sicherheit@carlroth.de e-mail (competent person):

Emergency telephone number 1.4

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital			131126	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
3.45	Skin sensitisation	1	Skin Sens. 1	H317
3.6	Carcinogenicity		Carc. 2	H351
3.9	Specific target organ toxicity - repeated exposure		STOT RE 1	H372

For full text of abbreviations: see SECTION 16

Australia (en) Page 1 / 13



Revision: 2024-03-02

acc. to Safe Work Australia - Code of Practice

Nickel powder ≥99 %, <63 µm

article number: CP22



The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure.

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS07, GHS08





Hazard statements

H317 May cause an allergic skin reaction H351 Suspected of causing cancer

H372 Causes damage to organs (respiratory system, skin) through prolonged or re-

peated exposure

Precautionary statements

Precautionary statements - prevention

P260 Do not breathe dust/fume/gas/mist/vapours/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary statements - response

P302+P352 IF ON SKIN: Wash with plenty of soap and water
P308+P313 IF exposed or concerned: Get medical advice/attention

P314 Get medical advice/attention if you feel unwell

P333+P313 If skin irritation or rash occurs: Get medical advice/attention

Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant

For professional users only

2.3 Other hazards

Dust explosion hazards.

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0.1\%$.

Australia (en) Page 2 / 13

acc. to Safe Work Australia - Code of Practice

Nickel powder ≥99 %, <63 µm

article number: CP22



SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance Nickel powder

Molecular formula Ni

Molar mass $58.69 \, ^{9}/_{mol}$ CAS No 7440-02-0

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In case of skin reactions, consult a physician.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water, foam, dry extinguishing powder, ABC-powder

Unsuitable extinguishing media

water jet

Australia (en) Page 3 / 13

acc. to Safe Work Australia - Code of Practice

Nickel powder ≥99 %, <63 µm

article number: CP22



5.2 Special hazards arising from the substance or mixture

Danger of dust explosion.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe dust.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains. Take up mechanically.

Advice on how to clean up a spill

Take up mechanically. Control of dust.

Other information relating to spills and releases

Place in appropriate containers for disposal.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid exposure. Avoid dust formation. Provide adequate ventilation as well as local exhaustion at critical locations.

Measures to prevent fire as well as aerosol and dust generation

Removal of dust deposits.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Store in a dry place. Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Australia (en) Page 4 / 13

acc. to Safe Work Australia - Code of Practice

Nickel powder ≥99 %, <63 µm

article number: CP22

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

Specific end use(s) 7.3

No information available.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Identifi- er	TWA [mg/ m³]	STEL [mg/ m³]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
AU	nuisance dusts		WES	10			i	WES
AU	nickel	7440-02-0	WES	1				WES
AU	nickel	7440-02-0	WES	1				WES

Notation

Powder

Ceiling-C Ceiling value is a limit value above which exposure should not occur

Inhalable fraction

STEL

Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified) TWA

Human health values

Relevant DNELs and other threshold levels Threshold **Endpoint Used in Exposure time** Protection goal, level route of exposure DNEL 0.05 mg/m³ human, inhalatory worker (industry) chronic - systemic effects DNEL 0.05 mg/m³ human, inhalatory worker (industry) chronic - local effects DNEL 11.9 mg/m³ human, inhalatory worker (industry) acute - local effects

Environmental values

Relevant	Relevant PNECs and other threshold levels			
End- point	Threshold level	Organism	Environmental com- partment	Exposure time
PNEC	7.1 ^{µg} / _l	aquatic organisms	freshwater	short-term (single instance)
PNEC	8.6 ^{µg} / _I	aquatic organisms	marine water	short-term (single instance)
PNEC	0.33 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	109 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)

Australia (en) Page 5 / 13



acc. to Safe Work Australia - Code of Practice

Nickel powder ≥99 %, <63 µm

article number: CP22



Relevant	Relevant PNECs and other threshold levels			
End- point	Threshold level	Organism	Environmental com- partment	Exposure time
PNEC	109 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)
PNEC	29.9 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection.

Skin protection





hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

type of material

NBR (Nitrile rubber)

material thickness

>0,11 mm

breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection





Respiratory protection necessary at: Dust formation. Particulate filter device (EN 143). P2 (filters at least 94 % of airborne particles, colour code: White).

Australia (en) Page 6 / 13

acc. to Safe Work Australia - Code of Practice

Nickel powder ≥99 %, <63 µm

article number: CP22



Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state solid Form powder Colour

silver grey Odour odourless

Melting point/freezing point 1,455 °C (ECHA)

Boiling point or initial boiling point and boiling 2,832 °C

range

this material is combustible, but will not ignite **Flammability**

readily

Lower and upper explosion limit not determined Flash point not applicable

Auto-ignition temperature not determined

Decomposition temperature not relevant pH (value) not applicable Kinematic viscosity not relevant

Solubility(ies)

Water solubility (practically insoluble)

Partition coefficient

Partition coefficient n-octanol/water (log value): not relevant (inorganic)

Vapour pressure not determined

Density and/or relative density

 $8.9 \, {\rm ^{9}/_{cm^{3}}}$ at 25 °C (ECHA) Density

Relative vapour density Information on this property is not available.

1,600 – 2,600 kg/_{m³} **Bulk density**

Particle characteristics

Particle size <63 µm

Other safety parameters

Oxidising properties none

Australia (en) Page 7 / 13

acc. to Safe Work Australia - Code of Practice

Nickel powder ≥99 %, <63 µm

article number: CP22



9.2 Other information

Information with regard to physical hazard

classes:

hazard classes acc. to GHS (physical hazards): not relevant

Other safety characteristics:

There is no additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

Dust can form an explosive mixture with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Acetone, Alcohols, Hydrazine, Perchlorates, Nitric acid, Sulphur, Strong acid, Organic solvents, Selenium

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity

Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	>9,000 ^{mg} / _{kg}	rat		ECHA

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Suspected of causing cancer.

Australia (en) Page 8 / 13

acc. to Safe Work Australia - Code of Practice

Nickel powder ≥99 %, <63 µm

article number: CP22



Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Causes damage to organs (respiratory system, skin) through prolonged or repeated exposure.

Hazard category	Target organ	Exposure route
1	respiratory system	if exposed
1	skin	if exposed

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

Data are not available.

• If in eyes

Data are not available.

If inhaled

Inhalation of dust may cause irritation of the respiratory system, varying degrees of pulmonary injury

• If on skin

May produce an allergic reaction, pruritis, localised redness

Other information

none

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of \geq 0,1%.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute)				
Endpoint	Value	Species	Source	Exposure time
LC50	15.3 ^{mg} / _l	fish	ECHA	96 h

Aquatic toxicity (chronic)				
Endpoint	Value	Species	Source	Exposure time
EC50	≤108 ^{µg} / _I	aquatic invertebrates	ECHA	21 d

Australia (en) Page 9 / 13

acc. to Safe Work Australia - Code of Practice

Nickel powder ≥99 %, <63 µm

article number: CP22



12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

BCF	45 (ECHA)
-----	-----------

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of \geq 0,1%.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Recycling/reclamation of metals and metal compounds.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H11 Toxic (Delayed or chronic)

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

Australia (en) Page 10 / 13

acc. to Safe Work Australia - Code of Practice

Nickel powder ≥99 %, <63 µm

article number: CP22



SECTION 14: Transport information

14.1 UN number not subject to transport regulations

14.2 UN proper shipping name not assigned
 14.3 Transport hazard class(es) not assigned
 14.4 Packing group not assigned

14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

gerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport informationNational regulationsAdditional information(UN RTDG)

Not subject to transport regulations. UN RTDG

International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

Substance is listed.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed

Australia (en) Page 11 / 13

acc. to Safe Work Australia - Code of Practice

Nickel powder ≥99 %, <63 µm

article number: CP22



Country	Inventory	Status
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

Legend

Australian Inventory of Industrial Chemicals
Chemical Inventory and Control Regulation
Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China
National Inventory of Chemical Substances AIIC CICR DSL ECSI IECSC

National Inventory of Chemical Substances
KECI Korea Existing Chemicals Inventory
NCI National Chemical Inventory
NZIOC New Zealand Inventory of Chemicals
PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg. REACH registered substances
TCSI Taiwan Chemical Substance Inventory
TCCA Taiwan Chemical Substance Inventory

Toxic Substance Control Act

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
15.1		National inventories: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations	
BCF	Bioconcentration factor	
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)	
Ceiling-C	Ceiling value	
DGR	Dangerous Goods Regulations (see IATA/DGR)	
DNEL	Derived No-Effect Level	
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval	
ED	Endocrine disruptor	
EINECS	European Inventory of Existing Commercial Chemical Substances	
ELINCS	European List of Notified Chemical Substances	

Australia (en) Page 12 / 13

acc. to Safe Work Australia - Code of Practice

Nickel powder ≥99 %, <63 µm

article number: CP22



Abbr.	Descriptions of used abbreviations	
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations	
IATA	International Air Transport Association	
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)	
ICAO	International Civil Aviation Organization	
IMDG	International Maritime Dangerous Goods Code	
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval	
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval	
NLP	No-Longer Polymer	
PBT	Persistent, Bioaccumulative and Toxic	
PNEC	Predicted No-Effect Concentration	
STEL	Short-term exposure limit	
TWA	Time-weighted average	
UN RTDG	UN Recommendations on the Transport of Dangerous Good	
vPvB	Very Persistent and very Bioaccumulative	
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants	

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H372	Causes damage to organs (respiratory system, skin) through prolonged or repeated exposure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Australia (en) Page 13 / 13