

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



**Methanol ≥99,5 %, Ph.Eur., extra pure**

article number: **CP43**  
Version: **GHS 5.0 en**  
Replaces version of: 2020-08-04  
Version: (GHS 4)

date of compilation: 2016-04-29  
Revision: 2021-06-16

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Identification of the substance	<b>Methanol</b> ≥99,5 %, Ph.Eur., extra pure
Article number	CP43
CAS number	67-56-1

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:	Laboratory chemical Laboratory and analytical use Industrial use Professional use Formulation [mixing] of preparations and/or re-packaging (excluding alloys)
Uses advised against:	Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

### 1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG  
Schoemperlenstr. 3-5  
D-76185 Karlsruhe  
Germany

**Telephone:** +49 (0) 721 - 56 06 0  
**Telefax:** +49 (0) 721 - 56 06 149  
**e-mail:** [sicherheit@carlroth.de](mailto:sicherheit@carlroth.de)  
**Website:** [www.carlroth.de](http://www.carlroth.de)

Competent person responsible for the safety data sheet: :Department Health, Safety and Environment

**e-mail (competent person):** [sicherheit@carlroth.de](mailto:sicherheit@carlroth.de)

### 1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 Westmead, NSW	131126	

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification acc. to GHS

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



**Methanol  $\geq 99,5$  %, Ph.Eur., extra pure**

article number: **CP43**

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.1O	Acute toxicity (oral)	3	Acute Tox. 3	H301
3.1D	Acute toxicity (dermal)	3	Acute Tox. 3	H311
3.1I	Acute toxicity (inhal.)	3	Acute Tox. 3	H331
3.8	Specific target organ toxicity - single exposure	1	STOT SE 1	H370

For full text of abbreviations: see SECTION 16

## The most important adverse physicochemical, human health and environmental effects

Immediate effects can be expected after short-term exposure. The product is combustible and can be ignited by potential ignition sources.

## 2.2 Label elements

### Labelling

#### Signal word

**Danger**

#### Pictograms

GHS02, GHS06,  
GHS08



#### Hazard statements

H225 Highly flammable liquid and vapour  
H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled  
H370 Causes damage to organs (eye)

#### Precautionary statements

##### Precautionary statements - prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
P260 Do not breathe dust/fume/gas/mist/vapours/spray  
P280 Wear protective gloves/protective clothing

##### Precautionary statements - response

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
P302+P352 IF ON SKIN: Wash with plenty of soap and water  
P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor  
P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

##### Precautionary statements - storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed  
P403+P235 Store in a well-ventilated place. Keep cool

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



**Methanol  $\geq 99,5\%$  , Ph.Eur., extra pure**

article number: **CP43**

## 2.3 Other hazards

### Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Name of substance	Methanol
Molecular formula	CH <sub>4</sub> O
Molar mass	32.04 g/mol
CAS No	67-56-1

## SECTION 4: First aid measures

### 4.1 Description of first aid measures



#### General notes

Take off immediately all contaminated clothing. Self-protection of the first aider.

#### Following inhalation

Call a physician immediately. If breathing is irregular or stopped, administer artificial respiration.

#### Following skin contact

After contact with skin, wash immediately with plenty of water.

#### Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

#### Following ingestion

Rinse mouth immediately and drink plenty of water. Call a physician immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

Following inhalation: Cough, Vertigo, Headache,

Following skin contact: Has degreasing effect on the skin,

After eye contact: Conjunctival redness of the eyes, Conjunctivitis (pink eye),

Following ingestion: Abdominal pain, Malaise, Vomiting, Poisoning effect on central nervous system can cause convulsions, laboured breathing and loss of consciousness, Loss of righting reflex, and ataxia, Serious physical decay of vision, Risk of blindness, Large doses may result in coma and death

### 4.3 Indication of any immediate medical attention and special treatment needed

none

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Methanol  $\geq 99,5$  %, Ph.Eur., extra pure

article number: CP43

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media



#### Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings  
water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

water jet

### 5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

#### Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus. Wear full chemical protective clothing.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures



#### For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Danger of explosion.

### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

#### Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



**Methanol  $\geq 99,5$  %, Ph.Eur., extra pure**

article number: **CP43**

## 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Provision of sufficient ventilation. Use extractor hood (laboratory). Handle and open container with care. Clear contaminated areas thoroughly.

#### Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

#### Advice on general occupational hygiene

When using do not eat or drink. Thorough skin-cleansing after handling the product. When using do not smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight.

#### Incompatible substances or mixtures

Observe hints for combined storage.

#### Consideration of other advice:

Store locked up. Ground/bond container and receiving equipment.

#### Ventilation requirements

Keep any substance that emits harmful vapours or gases in a place that allows these to be permanently extracted. Use local and general ventilation.

#### Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

### 7.3 Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



**Methanol ≥99,5 %, Ph.Eur., extra pure**

article number: **CP43**

## National limit values

### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
AU	methyl alcohol (methanol)	67-56-1	WES	200	262	250	328				WES

#### Notation

Ceiling-C  
STEL

Ceiling value is a limit value above which exposure should not occur  
Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

## Human health values

Relevant DNELs and other threshold levels				
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	130 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	130 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
DNEL	130 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
DNEL	130 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
DNEL	20 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
DNEL	20 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects

## Environmental values

Relevant PNECs and other threshold levels				
Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
PNEC	20.8 mg/l	aquatic organisms	freshwater	short-term (single instance)
PNEC	2.08 mg/l	aquatic organisms	marine water	short-term (single instance)
PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	77 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	7.7 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
PNEC	100 mg/kg	terrestrial organisms	soil	short-term (single instance)

## 8.2 Exposure controls

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



**Methanol  $\geq 99,5$  %, Ph.Eur., extra pure**

article number: **CP43**

## Individual protection measures (personal protective equipment)

### Eye/face protection



Use safety goggle with side protection.

### Skin protection



#### • hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

#### • type of material

Butyl caoutchouc (butyl rubber)

#### • material thickness

0,7mm

#### • breakthrough times of the glove material


>480 minutes (permeation: level 6)

#### • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

### Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

### Environmental exposure controls

Keep away from drains, surface and ground water.

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



**Methanol ≥99,5 %, Ph.Eur., extra pure**

article number: **CP43**

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	like: - alcohol
Melting point/freezing point	-98 °C (ECHA)
Boiling point or initial boiling point and boiling range	65 °C at 1,013 hPa (ECHA)
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	5.5 vol% - 44 vol%
Flash point	9.7 °C at 1,013 hPa (ECHA)
Auto-ignition temperature	455 °C at 1,013 hPa (ECHA)
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	0.7595 mm <sup>2</sup> /s at 20 °C

#### Solubility(ies)

Water solubility miscible in any proportion

#### Partition coefficient

Partition coefficient n-octanol/water (log value): -0.77 (ECHA)

Vapour pressure 128 hPa at 20 °C  
200 hPa at 30 °C

Density 0.79 g/cm<sup>3</sup> at 20 °C

Relative vapour density 1.11 (air = 1)

Particle characteristics not relevant (liquid)

#### Other safety parameters

Oxidising properties none

### 9.2 Other information

Information with regard to physical hazard classes: There is no additional information.

Other safety characteristics:

Miscibility completely miscible with water



# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Methanol  $\geq 99,5\%$ , Ph.Eur., extra pure

article number: CP43

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air.

#### If heated

Risk of ignition.

### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

### 10.3 Possibility of hazardous reactions

**Danger of explosion:** Oxidisers, Perchlorates, Nitrogen oxides (NOx), Chlorates, Halogenated hydrocarbons, Hydrogen peroxide, Nitric acid, Sulphuric acid,

**Exothermic reaction with:** Reducing agents, Acids, Chlorine, Chloroform, Acid chlorides, inorganic,

**Dangerous/dangerous reactions with:** Fluorine, Alkali metals, Alkaline earth metal, strong oxidiser

### 10.4 Conditions to avoid

UV-radiation/sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5 Incompatible materials

aluminium, iron, zinc, different plastics, Rubber articles

### 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Classification acc. to GHS

#### Acute toxicity

Toxic if swallowed. Toxic in contact with skin. Toxic if inhaled.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
inhalation: vapour	LC50	131 mg/l/4h	rat		ECHA
oral	LD50	5,628 mg/kg	rat		TOXNET
oral	LDLo	143 mg/kg	human		TOXNET
dermal	LD50	15,800 mg/kg	rabbit		TOXNET

#### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

#### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

#### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



**Methanol ≥99,5 %, Ph.Eur., extra pure**

article number: **CP43**

## Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

## Carcinogenicity

Shall not be classified as carcinogenic.

## Reproductive toxicity

Shall not be classified as a reproductive toxicant.

## Specific target organ toxicity - single exposure

Causes damage to organs (eye).

Hazard category	Target organ	Exposure route
1	eye	if exposed

## Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

## Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

## Symptoms related to the physical, chemical and toxicological characteristics

### • If swallowed

abdominal pain, vomiting, loss of righting reflex, and ataxia, poisoning effect on central nervous system can cause convulsions, laboured breathing and loss of consciousness, risk of blindness, large doses may result in coma and death

### • If in eyes

conjunctivitis (pink eye)

### • If inhaled

vertigo, cough, headache

### • If on skin

has degreasing effect on the skin

### • Other information

none

## 11.2 Endocrine disrupting properties

Not listed.

## SECTION 12: Ecological information

### 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)				
Endpoint	Value	Species	Source	Exposure time
LC50	15,400 mg/l	fish	ECHA	96 h
ErC50	22,000 mg/l	algae	ECHA	96 h

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



**Methanol  $\geq 99,5$  %, Ph.Eur., extra pure**

article number: **CP43**

## Biodegradation

The substance is readily biodegradable.

### 12.2 Process of degradability

Theoretical Oxygen Demand: 1.498 mg/mg

Theoretical Carbon Dioxide: 1.374 mg/mg

Biochemical Oxygen Demand: 1,236 mg/g at 5 d

Process of degradability		
Process	Degradation rate	Time
biotic/abiotic	99 %	30 d
oxygen depletion	69 %	5 d

### 12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	-0.77 (ECHA)
---------------------------	--------------

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Endocrine disrupting properties

Not listed.

### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Sewage disposal-relevant information

Do not empty into drains.

#### Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

#### Relevant provisions relating to waste(Basel Convention)

##### Properties of waste which render it hazardous

**H3** Flammable liquids

**H11** Toxic (Delayed or chronic)

### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Methanol  $\geq 99,5\%$  , Ph.Eur., extra pure

article number: CP43

## SECTION 14: Transport information

### 14.1 UN number

<b>UN RTDG</b>	UN 1230
IMDG-Code	UN 1230
ICAO-TI	UN 1230

### 14.2 UN proper shipping name

<b>UN RTDG</b>	METHANOL
IMDG-Code	METHANOL
ICAO-TI	Methanol

### 14.3 Transport hazard class(es)

<b>UN RTDG</b>	3 (6.1)
IMDG-Code	3 (6.1)
ICAO-TI	3 (6.1)

### 14.4 Packing group

<b>UN RTDG</b>	II
IMDG-Code	II
ICAO-TI	II

### 14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

### 14.6 Special precautions for user

There is no additional information.

### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

### 14.8 Information for each of the UN Model Regulations

#### Transport information National regulations Additional information (UN RTDG)

<b>UN number</b>	1230
<b>Class</b>	3
<b>Subsidiary risk(s)</b>	6.1
<b>Packing group</b>	II
<b>Danger label(s)</b>	3+6.1



<b>Special provisions (SP)</b>	279 UN RTDG
<b>Excepted quantities (EQ)</b>	E2 UN RTDG

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Methanol $\geq 99,5\%$ , Ph.Eur., extra pure

article number: CP43

### Limited quantities (LQ)

1 L  
UN RTDG

### International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name: METHANOL  
Particulars in the shipper's declaration: UN1230, METHANOL, 3 (6.1), II, 9.7°C c.c.  
Marine pollutant: -  
Danger label(s): 3+6.1



Special provisions (SP): 279  
Excepted quantities (EQ): E2  
Limited quantities (LQ): 1 L  
EmS: F-E, S-D  
Stowage category: B

### International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name: Methanol  
Particulars in the shipper's declaration: UN1230, Methanol, 3 (6.1), II  
Danger label(s): 3+6.1



Special provisions (SP): A113  
Excepted quantities (EQ): E2  
Limited quantities (LQ): 1 L

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

#### National regulations(Australia)

##### Australian Inventory of Chemical Substances(AICS)

Substance is listed.

#### National inventories

Country	Inventory	Status
AU	AICS	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Methanol ≥99,5 %, Ph.Eur., extra pure

article number: CP43

Country	Inventory	Status
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed

### Legend

AICS	Australian Inventory of Chemical Substances
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

## 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

## SECTION 16: Other information

### Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1		The most important adverse physicochemical, human health and environmental effects: Immediate effects can be expected after short-term exposure. The product is combustible and can be ignited by potential ignition sources.	yes
2.2		Precautionary statements - response: change in the listing (table)	yes
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Danger		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



**Methanol ≥99,5 %, Ph.Eur., extra pure**

article number: **CP43**

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB.	yes

## Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
STEL	Short-term exposure limit
TWA	Time-weighted average

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



**Methanol  $\geq 99,5$  %, Ph.Eur., extra pure**

article number: **CP43**

Abbr.	Descriptions of used abbreviations
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne conatminants

## Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

## List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs (eye).

## Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.