

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Toluene D8 99,5 Atom%D

article number: **CP95**
Version: **GHS 3.0 en**
Replaces version of: 2022-08-02
Version: (GHS 2)

date of compilation: 2019-06-27
Revision: 2024-03-02

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance **Toluene D8 99,5 Atom%D**
Article number CP95
CAS number 2037-26-5

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical
Laboratory and analytical use
Uses advised against: Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household). Food, drink and animal feeding-stuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG
Schoemperlenstr. 3-5
D-76185 Karlsruhe
Germany

Telephone:+49 (0) 721 - 56 06 0
Telefax: +49 (0) 721 - 56 06 149
e-mail: sicherheit@carlroth.de
Website: www.carlroth.de

Competent person responsible for the safety data sheet: Department Health, Safety and Environment

e-mail (competent person): **sicherheit@carlroth.de**

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 Westmead, NSW	131126	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.7	Reproductive toxicity	2	Repr. 2	H361d
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Toluene D8 99,5 Atom%D

article number: CP95

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
3.9	Specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
3.10	Aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling

Signal word

Danger

Pictograms

GHS02, GHS07,
GHS08



Hazard statements

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H361d	Suspected of damaging the unborn child
H373	May cause damage to organs through prolonged or repeated exposure

Precautionary statements

Precautionary statements - prevention

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P260	Do not breathe dust/fume/gas/mist/vapours/spray

Precautionary statements - response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P302+P352	IF ON SKIN: Wash with plenty of soap and water
P331	Do NOT induce vomiting
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

Precautionary statements - storage

P403+P233	Store in a well-ventilated place. Keep container tightly closed
P403+P235	Store in a well-ventilated place. Keep cool

For professional users only

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Toluene D8 99,5 Atom%D

article number: CP95

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance	Toluene D8
Molecular formula	C ₇ D ₈
Molar mass	100.1 g/mol
CAS No	2037-26-5

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Call a physician immediately. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Observe aspiration hazard if vomiting occurs.

4.2 Most important symptoms and effects, both acute and delayed

Aspiration hazard, Irritation, Dizziness, Drowsiness, Narcosis

4.3 Indication of any immediate medical attention and special treatment needed

none

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Toluene D8 99,5 Atom%D

article number: **CP95**

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings!
water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Toluene D8 99,5 Atom%D

article number: CP95

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation. Avoid exposure.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

This information is not available.

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Toluene D8 99,5 Atom%D

article number: CP95

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

FKM (fluoro rubber)

• material thickness

0,4 mm

• breakthrough times of the glove material


>480 minutes (permeation: level 6)

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C, colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Toluene D8 99,5 Atom%D

article number: CP95

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	characteristic - aromatic
Melting point/freezing point	-95 °C
Boiling point or initial boiling point and boiling range	111 °C
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	1.2 vol% (LEL) - 7 vol% (UEL)
Flash point	6 °C
Auto-ignition temperature	535 °C
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	not determined

Solubility(ies)

Water solubility 0.47 g/l at 20 °C

Partition coefficient

Partition coefficient n-octanol/water (log value): 2.65 (exp. (IUCLID))

Vapour pressure 29 hPa at 20 °C

Density and/or relative density

Density 0.94 g/cm³

Relative vapour density Information on this property is not available.

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard classes: There is no additional information.

Other safety characteristics: There is no additional information.

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Toluene D8 99,5 Atom%D

article number: CP95

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Nitric acid and nitrous acid, Sulphuric acid, Perchlorates, Nitro compound, Acetic acid, Mineral acids, Sulphur

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

different Rubber articles, plastics

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4. May be harmful if inhaled.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
inhalation: vapour	LC50	49 mg/l/4h	rat		
oral	LD50	636 mg/kg	rat		
dermal	LD50	12,200 mg/kg	rabbit		

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Toluene D8 99,5 Atom%D

article number: CP95

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

aspiration hazard

• If in eyes

conjunctivitis (pink eye), causes slight to moderate irritation

• If inhaled

fatigue, narcosis, causes slight to moderate irritation, cough, headache, poisoning effect on central nervous system can cause convulsions, laboured breathing and loss of consciousness, fatigue

• If on skin

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation), causes skin irritation

• Other information

none

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)				
Endpoint	Value	Species	Source	Exposure time
EC50	6 mg/l	daphnia magna		48 h
EC50	12 mg/l	Pseudokirchneriella subcapitata		72 h
LC50	5.8 mg/l	rainbow trout (Oncorhynchus mykiss)		96 h

12.2 Persistence and degradability

Theoretical Oxygen Demand: 3.13 g/g
Theoretical Carbon Dioxide: 3.076 mg/mg

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Toluene D8 99,5 Atom%D

article number: CP95

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	2.65 (Exp. (IUCLID))
---------------------------	----------------------

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H3 Flammable liquids
H11 Toxic (Delayed or chronic)

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number

UN RTDG	UN 1294
IMDG-Code	UN 1294
ICAO-TI	UN 1294

14.2 UN proper shipping name

UN RTDG	TOLUENE
---------	---------



Safety data sheet

acc. to Safe Work Australia - Code of Practice



Toluene D8 99,5 Atom%D

article number: **CP95**

IMDG-Code	TOLUENE	
ICAO-TI	Toluene	
14.3 Transport hazard class(es)		
UN RTDG	3	
IMDG-Code	3	
ICAO-TI	3	
14.4 Packing group		
UN RTDG	II	
IMDG-Code	II	
ICAO-TI	II	
14.5 Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations	
14.6 Special precautions for user		
There is no additional information.		
14.7 Transport in bulk according to IMO instruments		
The cargo is not intended to be carried in bulk.		
14.8 Information for each of the UN Model Regulations		
Transport information	National regulations	Additional information(UN RTDG)
UN number		1294
Class		3
Packing group		II
Danger label(s)		3
		
Special provisions (SP)		- UN RTDG
Excepted quantities (EQ)		E2 UN RTDG
Limited quantities (LQ)		1 L UN RTDG
Emergency Action Code		3YE
International Maritime Dangerous Goods Code (IMDG) - Additional information		
Proper shipping name		TOLUENE
Particulars in the shipper's declaration		UN1294, TOLUENE, 3, II, 6°C c.c.
Marine pollutant		-
Danger label(s)		3
		

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Toluene D8 99,5 Atom%D

article number: **CP95**

Special provisions (SP)	-
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-E, S-D
Stowage category	B

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name	Toluene
Particulars in the shipper's declaration	UN1294, Toluene, 3, II
Danger label(s)	3



Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

Substance is listed.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
KR	KECI	substance is listed
NZ	NZIoC	substance is listed
TW	TCSI	substance is listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
TCSI	Taiwan Chemical Substance Inventory

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

Toluene D8 99,5 Atom%D

article number: CP95

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.	yes
14.8		Emergency Action Code: 3YE	yes
15.1		National inventories: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
UEL	Upper explosion limit (UEL)
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Toluene D8 99,5 Atom%D

article number: CP95

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.