acc. to Safe Work Australia - Code of Practice

Acetic acid D4 99,5 Atom%D

article number: HN83 date of compilation: 2019-10-14 Version: GHS 3.0 en Revision: 2024-03-03

Replaces version of: 2022-09-21

Version: (GHS 2)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance Acetic acid D4 99,5 Atom%D

Article number **HN83**

CAS number 1186-52-3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for squirting or spraying. Do not use

for products which come into direct contact with the skin. Do not use for private purposes (household). Food, drink and animal feedingstuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data Department Health, Safety and Environment

sheet:

e-mail (competent person):

sicherheit@carlroth.de

1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	3	Flam. Liq. 3	H226
3.2	Skin corrosion/irritation	1B	Skin Corr. 1B	H314
3.3	Serious eye damage/eye irritation	1	Eye Dam. 1	H318

For full text of abbreviations: see SECTION 16

Australia (en) Page 1 / 14



acc. to Safe Work Australia - Code of Practice

Acetic acid D4 99,5 Atom%D

article number: HN83



The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS02, GHS05



Hazard statements

H226 Flammable liquid and vapour

H314 Causes severe skin burns and eye damage

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P260 Do not breathe dusts or mists
P280 Wear eye protection/face protection

Precautionary statements - response

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

Precautionary statements - storage

P403+P235 Store in a well-ventilated place. Keep cool

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of \geq 0,1%.

Australia (en) Page 2 / 14

acc. to Safe Work Australia - Code of Practice

Acetic acid D4 99,5 Atom%D

article number: HN83



SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance Acetic acid D4

Molecular formula ${\rm C_2D_4O_2}$ Molar mass ${\rm 64.08~g/_{mol}}$

CAS No 1186-52-3

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off immediately all contaminated clothing. Self-protection of the first aider.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

After contact with skin, wash immediately with plenty of water. Immediate medical treatment required because corrosive injuries that are not treated are hard to cure.

Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

Following ingestion

Rinse mouth immediately and drink plenty of water. Call a physician immediately. If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

4.2 Most important symptoms and effects, both acute and delayed

Following inhalation: Irritant effects, Cough, pain, choking, and breathing difficulties, Following skin contact: Causes severe burns, Causes poorly healing wounds, After eye contact: Risk of serious damage to eyes, Risk of blindness, Following ingestion: Corrosion, Gastric perforation

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Australia (en) Page 3 / 14

acc. to Safe Work Australia - Code of Practice

Acetic acid D4 99,5 Atom%D

article number: HN83



Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus. Wear full chemical protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Australia (en) Page 4 / 14

acc. to Safe Work Australia - Code of Practice

Acetic acid D4 99,5 Atom%D

article number: HN83



SECTION 7: Handling and storage

Precautions for safe handling

Provision of sufficient ventilation. Use extractor hood (laboratory). Handle and open container with care. Clear contaminated areas thoroughly.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
AU	acetic acid	64-19-7	WES	10	25	15	37				WES

Notation

Ceiling-C STEL

TWA

Ceiling value is a limit value above which exposure should not occur

Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Australia (en) Page 5 / 14

acc. to Safe Work Australia - Code of Practice

Acetic acid D4 99,5 Atom%D

article number: HN83



8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection. Wear face protection.

Skin protection





hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

type of material

Butyl caoutchouc (butyl rubber)

material thickness

0,7mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection





Respiratory protection necessary at: Aerosol or mist formation. Type: E (against acidic gases like sulphur dioxide or hydrogen chloride, colour code: Yellow).

Environmental exposure controls

Keep away from drains, surface and ground water.

Australia (en) Page 6 / 14

acc. to Safe Work Australia - Code of Practice

Acetic acid D4 99,5 Atom%D

article number: HN83



SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Colour colourless

Odour stinging - like: - Acetic acid

Melting point/freezing point 17 °C

Boiling point or initial boiling point and boiling 116 – 118 °C at 1,013 hPa

range

Flammability flammable liquid in accordance with GHS criteria

Lower and upper explosion limit 4 vol% (LEL) - 16 vol% (UEL)

Flash point 39 °C Auto-ignition temperature 485 °C

Decomposition temperature not relevant

pH (value) 2.5 (in aqueous solution: 50 ^g/_l, 20 °C)

Kinematic viscosity 1.089 mm²/s at 20 °C

Dynamic viscosity 1.22 mPa s at 20 °C

Solubility(ies)

Water solubility miscible in any proportion

Partition coefficient

Partition coefficient n-octanol/water (log value): -0.17 (exp.)

Vapour pressure 15 hPa at 20 °C

Density and/or relative density

Density $1.12 \, {}^{9}/_{cm^{3}}$ Relative vapour density $2.21 \, (air = 1)$

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard There is no additional information.

classes:

Other safety characteristics:

Miscibility completely miscible with water

Australia (en) Page 7 / 14

acc. to Safe Work Australia - Code of Practice

Acetic acid D4 99,5 Atom%D

article number: HN83



SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition.

If heated

Risk of ignition. Vapours may form explosive mixtures with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Danger of explosion: Peroxides, Perchlorates, Hydrogen peroxide, Chromium(VI) oxide, Permanganates, for example potassium permanganate, strong oxidiser, **Violent reaction with:** Strong alkali, Aldehydes, Alkali hydroxide (caustic alkali), Alcohols, Nitric acid

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

different plastics, Rubber articles, iron, copper, bronze, brass, zinc

Release of flammable materials with

Metals (due to the release of hydrogen in an acid/alkaline medium)

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Australia (en) Page 8 / 14

acc. to Safe Work Australia - Code of Practice

Acetic acid D4 99,5 Atom%D

article number: HN83



Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects)

• If in eyes

causes burns, Causes serious eye damage, risk of blindness

If inhaled

irritant effects, cough, pain, choking, and breathing difficulties

If on skin

causes severe burns, causes poorly healing wounds

Other information

none

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0.1\%$.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Theoretical Oxygen Demand: 0.4993 ^{mg}/_{mg} Theoretical Carbon Dioxide: 1.374 ^{mg}/_{mg}

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	-0.17 (Exp.)
---------------------------	--------------

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of \geq 0,1%.

12.7 Other adverse effects

Data are not available.

Australia (en) Page 9 / 14

acc. to Safe Work Australia - Code of Practice

Acetic acid D4 99,5 Atom%D

article number: HN83



SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H3 Flammable liquids

H8 Corrosives

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number

UN RTDGUN 2789IMDG-CodeUN 2789ICAO-TIUN 2789

14.2 UN proper shipping name

UN RTDGACETIC ACID, GLACIALIMDG-CodeACETIC ACID, GLACIALICAO-TIAcetic acid, glacial

14.3 Transport hazard class(es)

 UN RTDG
 8 (3)

 IMDG-Code
 8 (3)

 ICAO-TI
 8 (3)

14.4 Packing group

UN RTDG II
IMDG-Code II
ICAO-TI II

Australia (en) Page 10 / 14

acc. to Safe Work Australia - Code of Practice

Acetic acid D4 99,5 Atom%D

article number: HN83



14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

gerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport informationNational regulationsAdditional information(UN RTDG)

UN number 2789
Class 8
Subsidiary risk(s) 3
Packing group II
Danger label(s) 8+3





Special provisions (SP)

UN RTDG

Excepted quantities (EQ)

E2 UN RTDG

Limited quantities (LQ)

1 L UN RTDG

Emergency Action Code 2P

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name ACETIC ACID, GLACIAL

Particulars in the shipper's declaration UN2789, ACETIC ACID, GLACIAL, 8 (3), II, 39°C c.c.

Marine pollutant -

Danger label(s) 8+3





Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

EmS F-E, S-C

Stowage category A


Segregation group 1 - Acids

Australia (en) Page 11 / 14

acc. to Safe Work Australia - Code of Practice

Acetic acid D4 99,5 Atom%D

article number: HN83



Proper shipping name Acetic acid, glacial

Particulars in the shipper's declaration UN2789, Acetic acid, glacial, 8 (3), II

Danger label(s) 8+3





Excepted quantities (EQ) E2
Limited quantities (LQ) 0,5 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
EU	ECSI	substance is listed
NZ	NZIoC	substance is listed
TW	TCSI	substance is listed

Legend

ECSI EC Substance Inventory (EINECS, ELINCS, NLP)
NZIOC New Zealand Inventory of Chemicals
TCSI Taiwan Chemical Substance Inventory

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.2		Precautionary statements - response: change in the listing (table)	yes
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
14.8		Emergency Action Code: 2P	yes

Australia (en) Page 12 / 14



acc. to Safe Work Australia - Code of Practice

Acetic acid D4 99,5 Atom%D

article number: HN83



Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations			
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)			
Ceiling-C	Ceiling value			
DGR	Dangerous Goods Regulations (see IATA/DGR)			
ED	Endocrine disruptor			
EINECS	European Inventory of Existing Commercial Chemical Substances			
ELINCS	European List of Notified Chemical Substances			
EmS	Emergency Schedule			
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na tions			
IATA	International Air Transport Association			
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)			
ICAO	International Civil Aviation Organization			
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air			
IMDG	International Maritime Dangerous Goods Code			
IMDG-Code	International Maritime Dangerous Goods Code			
LEL	Lower explosion limit (LEL)			
NLP	No-Longer Polymer			
PBT	Persistent, Bioaccumulative and Toxic			
ppm	Parts per million			
STEL	Short-term exposure limit			
TWA	Time-weighted average			
UEL	Upper explosion limit (UEL)			
UN RTDG	UN Recommendations on the Transport of Dangerous Good			
vPvB	Very Persistent and very Bioaccumulative			
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants			

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapour.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.

Australia (en) Page 13 / 14

acc. to Safe Work Australia - Code of Practice

Acetic acid D4 99,5 Atom%D

article number: HN83

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Australia (en) Page 14 / 14