according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



#### Toluene ROTISOLV® ≥99,8 %, GC Ultra Grade

article number: KK46 Version: 7.0 en Replaces version of: 25.08.2022 Version: (6)

### **SECTION 1: Identification of the substance/mixture and of the company/** undertaking

KK46

601-021-00-3

203-625-9

108-88-3

#### **Product identifier** 1.1

Identification of the substance

- Article number
- Registration number (REACH)
- Index number in CLP Annex VI
- EC number

CAS number

#### Alternative name(s) Methylbenzene

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Uses advised against:

Laboratory chemical Laboratory and analytical use

01-2119471310-51-xxxx

Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household). Food, drink and animal feedingstuffs.

**Toluene** ROTISOLV® ≥99,8 %, GC Ultra Grade

#### 1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 Telefax: +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data Department Health, Safety and Environment sheet:

#### e-mail (competent person):

sicherheit@carlroth.de

#### **Emergency telephone number** 1.4

### **SECTION 2: Hazards identification**

Classification of the substance or mixture 2.1

#### Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.7	Reproductive toxicity	2	Repr. 2	H361d

date of compilation: 24.09.2015 Revision: 04.03.2024

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



### Toluene ROTISOLV® ≥99,8 %, GC Ultra Grade

#### article number: KK46

Section	Hazard class		Hazard class and category	Hazard statement
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
3.9	Specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
3.10	Aspiration hazard	1	Asp. Tox. 1	H304
4.1C	Hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16

#### The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.

#### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008 (CLP)

**Signal word** Danger

#### Pictograms

GHS08



#### **Hazard statements**

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H361d	Suspected of damaging the unborn child
H373	May cause damage to organs (central nervous system) through prolonged or re- peated exposure (if inhaled)
H412	Harmful to aquatic life with long lasting effects

#### **Precautionary statements**

#### **Precautionary statements - prevention**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking
P280	Wear protective gloves/protective clothing/eye protection/face protection

#### **Precautionary statements - response**

P302+P352	IF ON SKIN: Wash with plenty of soap and water
P308+P313	IF exposed or concerned: Get medical advice/attention
P331	Do NOT induce vomiting

For professional users only

Labelling of packages where the contents do not exceed 125 ml Signal word: Danger

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



#### Toluene ROTISOLV® ≥99,8 %, GC Ultra Grade

#### article number: KK46

Symbol(s)	
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H412	Harmful to aquatic life with long lasting effects.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P331	Do NOT induce vomiting.

#### 2.3 Other hazards

#### Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

#### **Endocrine disrupting properties**

Does not contain an endocrine disruptor (ED) at a concentration of  $\ge 0,1\%$ .

### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Name of substance	Toluene
Molecular formula	C <sub>7</sub> H <sub>8</sub>
Molar mass	92,14 <sup>g</sup> / <sub>mol</sub>
REACH Reg. No	01-2119471310-51-xxxx
CAS No	108-88-3
EC No	203-625-9
Index No	601-021-00-3

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures



#### **General notes**

Take off contaminated clothing.

#### **Following inhalation**

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

#### Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

#### Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



#### Toluene ROTISOLV® ≥99,8 %, GC Ultra Grade

#### article number: KK46

#### **Following ingestion**

Call a physician immediately. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Observe aspiration hazard if vomiting occurs.

## 4.2 Most important symptoms and effects, both acute and delayed

Aspiration hazard, Irritation, Dizziness, Drowsiness, Narcosis

# **4.3 Indication of any immediate medical attention and special treatment needed** none

### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media



#### Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

water jet

#### 5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapourair mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

#### Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Do not allow firefighting water to enter drains or water courses. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures



#### For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



#### Toluene ROTISOLV® ≥99,8 %, GC Ultra Grade

article number: KK46

#### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

#### Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Provision of sufficient ventilation. Avoid exposure.

#### Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed. Keep in a cool place.

#### Incompatible substances or mixtures

Observe hints for combined storage.

#### Consideration of other advice:

Ground/bond container and receiving equipment.

#### Ventilation requirements

Use local and general ventilation.

#### Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

#### 7.3 Specific end use(s)

No information available.

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



#### Toluene ROTISOLV® ≥99,8 %, GC Ultra Grade

#### article number: KK46

### **SECTION 8: Exposure controls/personal protection**

#### 8.1 **Control parameters**

#### National limit values

#### **Occupational exposure limit values (Workplace Exposure Limits)**

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
EU	toluene	108-88-3	IOELV	50	192	100	384			Н	2006/15/ EC
MT	toluene	108-88-3	OELV	50	192	100	384			Н	CAP. 424

#### Notation

Ceiling value is a limit value above which exposure should not occur Absorbed through the skin Ceiling-C Ĥ

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-TWA

minute period (unless otherwise specified) Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

#### Human health values

Relevant DNELs and other threshold levels							
Endpoint Threshold Protection goal, level route of exposure		Used in	Exposure time				
DNEL	192 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects			
DNEL	384 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects			
DNEL	192 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects			
DNEL	384 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects			
DNEL	384 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic effects			

#### **Environmental values**

Relevant	Relevant PNECs and other threshold levels								
End- point	Threshold level	Organism	Exposure time						
PNEC	0,68 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single instance)					
PNEC	0,68 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	marine water	short-term (single instance)					
PNEC	13,61 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)					
PNEC	16,39 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	freshwater sediment	short-term (single instance)					
PNEC	16,39 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	marine sediment	short-term (single instance)					
PNEC	2,89 <sup>mg</sup> / <sub>kg</sub>	terrestrial organisms	soil	short-term (single instance)					

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



#### Toluene ROTISOLV® ≥99,8 %, GC Ultra Grade

article number: KK46

#### 8.2 Exposure controls

#### Individual protection measures (personal protective equipment)

#### Eye/face protection



Use safety goggle with side protection.

#### Skin protection



#### hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a consider-able reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

#### • type of material

FKM (fluoro rubber)

#### • material thickness

≥0,4 mm

#### • breakthrough times of the glove material

>480 minutes (permeation: level 6)

#### other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

#### **Respiratory protection**



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

#### **Environmental exposure controls**

Keep away from drains, surface and ground water.

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

### Toluene ROTISOLV® ≥99,8 %, GC Ultra Grade

#### article number: KK46

## **SECTION 9: Physical and chemical properties**

9.1	Information on basic physical and chemical properties					
	Physical state	liquid				
	Colour	colourless				
	Odour	characteristic				
	Melting point/freezing point	-95 °C at 1.013 hPa (ECHA)				
	Boiling point or initial boiling point and boiling range	110,6 °C at 1.013 hPa (ECHA)				
	Flammability	flammable liquid in accordance with GHS criteria				
	Lower and upper explosion limit	39 g/m³ (LEL) - 300 g/m³ (UEL) / 1,1 vol% (LEL) - 7,1 vol% (UEL)				
	Flash point	4,4 °C at 1.013 hPa (ECHA)				
	Auto-ignition temperature	480 °C at 1.013 hPa (ECHA) (auto-ignition temper- ature (liquids and gases))				
	Decomposition temperature	not relevant				
	pH (value)	not determined				
	Kinematic viscosity	not determined				
	Dynamic viscosity	0,56 mPa s at 25 °C				
	Solubility(ies)					
	Water solubility	0,573 <sup>g</sup> / <sub>l</sub> at 25 °C (ECHA)				
	Partition coefficient					
	Partition coefficient n-octanol/water (log value):	2,73 (pH value: 7, 20 °C) (ECHA)				
	Soil organic carbon/water (log KOC)	2,312 (ECHA)				
	Vapour pressure	29 hPa at 20 °C				
	Density and/or relative density					
	Density	0,87 <sup>g</sup> / <sub>cm³</sub> at 20 °C (ECHA)				
	Relative vapour density	3,18 (air = 1)				
	Particle characteristics	not relevant (liquid)				
	Other safety parameters					
	Oxidising properties	none				
9.2	Other information					
	Information with regard to physical hazard classes:	There is no additional information.				



according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



#### Toluene ROTISOLV® ≥99,8 %, GC Ultra Grade

article number: KK46

Other safety characteristics:

Gas group (explosion group)

Maximum explosion pressure

Surface tension

Temperature class (EU, acc. to ATEX)

IIA

Maximum Experimental Safe Gap value; MESG > 0,9 mm

7,7 bar

27,73 <sup>mN</sup>/<sub>m</sub> (25 °C) (ECHA)

Τ1 Maximum permissible surface temperature on the equipment: 450°C

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air.

#### If heated

Risk of ignition.

#### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

#### 10.3 Possibility of hazardous reactions

Danger of explosion: Perchlorates, Nitric acid, Sulphuric acid, Acetic acid, Violent reaction with: Mineral acids, Strong acid, strong oxidiser

#### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### 10.5 Incompatible materials

different Rubber articles, plastics

#### 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Classification according to GHS (1272/2008/EC, CLP)

#### Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity								
Exposure route	Endpoint	Value	Species	Method	Source			
oral	LD50	5.580 <sup>mg</sup> / <sub>kg</sub>	rat		ECHA			
inhalation: vapour	LC50	28,1 <sup>mg</sup> / <sub>l</sub> /4h	rat		ECHA			
dermal	LD50	>5.000 <sup>mg</sup> / <sub>kg</sub>	rabbit		ECHA			

#### Skin corrosion/irritation

Causes skin irritation.

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



#### Toluene ROTISOLV® ≥99,8 %, GC Ultra Grade

article number: KK46

#### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

#### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

#### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

#### Carcinogenicity

Shall not be classified as carcinogenic.

#### **Reproductive toxicity**

Suspected of damaging the unborn child.

#### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

#### Specific target organ toxicity - repeated exposure

May cause damage to organs (central nervous system) through prolonged or repeated exposure (if inhaled).

Hazard category	Target organ	Exposure route
2	central nervous system	if inhaled

#### **Aspiration hazard**

May be fatal if swallowed and enters airways.

#### Symptoms related to the physical, chemical and toxicological characteristics

#### • If swallowed

aspiration hazard

#### • If in eyes

causes slight to moderate irritation

#### • If inhaled

dizziness, fatigue, narcosis

#### • If on skin

causes skin irritation

#### • Other information

none

#### **11.2** Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\ge 0,1\%$ .

#### 11.3 Information on other hazards

There is no additional information.

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



### Toluene ROTISOLV® ≥99,8 %, GC Ultra Grade

#### article number: KK46

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Harmful to aquatic life with long lasting effects.

#### Aquatic toxicity (acute)

Endpoint	Value	Value Species Source E		Exposure time
LC50	5,5 <sup>mg</sup> / <sub>l</sub>	fish	ECHA	96 h
EC50	84 <sup>mg</sup> / <sub>l</sub>	microorganisms	ECHA	24 h

#### Aquatic toxicity (chronic)

Endpoint	Value			Exposure time
LC50	3,78 <sup>mg</sup> / <sub>l</sub> aquatic invertebrates ECHA		2 d	
EC50	3,23 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	ECHA	7 d

#### 12.2 Persistence and degradability

Theoretical Oxygen Demand: 3,125 <sup>mg</sup>/<sub>mg</sub> Theoretical Carbon Dioxide: 3,343 <sup>mg</sup>/<sub>mg</sub>

#### Biodegradation

The substance is readily biodegradable.

Process of degradability		
Process	Degradation rate	Time
biotic/abiotic	86 %	20 d

#### 12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	2,73 (pH value: 7, 20 °C) (ECHA)
BCF	90 (ECHA)

#### 12.4 Mobility in soil

Henry's law constant	485 <sup>Pa m³</sup> / <sub>mol</sub> (ECHA)
The Organic Carbon normalised adsorption coefficient	2,312 (ECHA)

#### 12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

#### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\ge 0,1\%$ .

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



#### Toluene ROTISOLV® ≥99,8 %, GC Ultra Grade

article number: KK46

#### 12.7 Other adverse effects

Data are not available.

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

#### Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

#### 13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

#### Properties of waste which render it hazardous

- HP 3 flammable
- **HP 4** irritant skin irritation and eye damage
- HP 5 specific target organ toxicity (STOT)/aspiration toxicity
- HP 10 toxic for reproduction
- HP 14 ecotoxic

#### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADR	UN 1294
IMDG-Code	UN 1294
ICAO-TI	UN 1294
UN proper shipping name	
ADR	TOLUENE
IMDG-Code	TOLUENE
ICAO-TI	Toluene
Transport hazard class(es)	
ADR	3
IMDG-Code	3

14.2

14.3

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



#### Toluene ROTISOLV® ≥99,8 %, GC Ultra Grade

#### article number: KK46

	ICAO-TI	3
14.4	Packing group	
	ADR	II
	IMDG-Code	II
	ICAO-TI	II
14.5	Environmental hazards	non-environmentally hazardous acc. to the dan- gerous goods regulations

#### 14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

### 14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

#### 14.8 Information for each of the UN Model Regulations

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)Additional
information

Proper shipping name	TOLUENE
Particulars in the transport document	UN1294, TOLUENE, 3, II, (D/E)
Classification code	F1
Danger label(s)	3
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D/E
Hazard identification No	33
International Maritime Dangerous Goods Code	(IMDG) - Additional information
Proper shipping name	TOLUENE
Particulars in the shipper's declaration	UN1294, TOLUENE, 3, II, 4,4°C c.c.
Marine pollutant	-
Danger label(s)	3
Special provisions (SP)	-
Excepted quantities (EQ)	
	E2
Limited quantities (LQ)	E2 1 L
Limited quantities (LQ)	1 L

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



#### Toluene ROTISOLV® ≥99,8 %, GC Ultra Grade

article number: KK46

International Civil Aviation Organization (ICAO-	IATA/DGR) - Additional information
Proper shipping name	Toluene
Particulars in the shipper's declaration	UN1294, Toluene, 3, II
Danger label(s)	3
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L

### **SECTION 15: Regulatory information**

#### Safety, health and environmental regulations/legislation specific for the substance or mixture 15.1 **Relevant provisions of the European Union (EU)**

**Restrictions according to REACH, Annex XVII** 

Dangerous substances with restrictions (REACH, Annex XVII)				
Name of substance	Name acc. to inventory	CAS No	Restriction	No
Toluene	toluene	108-88-3	R48	48
Toluene	this product meets the criteria for classification in accordance with Reg- ulation No 1272/2008/EC		R3	3
Toluene	flammable / pyrophoric		R40	40
Toluene	substances in tattoo inks and perman- ent make-up		R75	75

Legend R3

1. Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in orna-mental lamps and ashtrays,

- tricks and jokes,

games for one or more participants, or any article intended to be used as such, even with ornamental aspects,

 Articles not complying with paragraph 1 shall not be placed on the market.
 Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they

can be used as fuel in decorative oil lamps for supply to the general public, and present an aspiration hazard and are labelled with H304.

 Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN)

5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and pack-aging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:

(a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil

or even sucking the wick of lamps – may lead to life-threatening lung damage";
(b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter fluid may lead to life threatening lung damage';
(c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.';

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



### Toluene ROTISOLV® ≥99,8 %, GC Ultra Grade

#### article number: KK46

#### Legend R40

- 1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: metallic glitter intended mainly for decoration,
- artificial snow and frost,
- 'whoopee' cushions,
- silly string aerosols,

- imitation excrement, horns for parties, decorative flakes and foams,
- artificial cobwebs, - stink bombs.

2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: (For professional users only.

3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).

4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to

the requirements indicated. Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the gener-R48 al public.

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



#### Toluene ROTISOLV® ≥99,8 %, GC Ultra Grade

#### article number: KK46



graph. 8. Mixtures that do not contain the statement "Mixture for use in tattoos or permanent make-up" shall not be used for tattooing purposes. according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



### Toluene ROTISOLV® ≥99,8 %, GC Ultra Grade

#### article number: KK46

#### Legend

9. This entry does not apply to substances that are gases at temperature of 20 °C and pressure of 101,3 kPa, or generate a vapour pressure of more than 300 kPa at temperature of 50 °C, with the exception of formaldehyde (CAS No 50-00-0, EC No 200-001-8).

10. This entry does not apply to the placing on the market of a mixture for use for tattooing purposes, or to the use of a mixture for tattooing purposes, when placed on the market exclusively as a medical device or an accessory to a medical device, within the meaning of Regulation (EU) 2017/745, or when used exclusively as a medical device or an accessory to a accessory to a medical device, within the same meaning. Where the placing on the market or use may not be exclusively as a medical device or an accessory to a medical device or an accessory to a medical device, the requirements of Regulation (EU) 2017/745 and of this Regulation shall apply cumulatively.

#### List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list

Not listed.

#### **Seveso Directive**

2012/18/EU (Seveso III)					
Νο	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the ap- plication of lower and upper-tier re- quirements		Notes	
P5c	flammable liquids (cat. 2, 3)	5.000	50.000	51)	

#### Notation

51) Flammable liquids, categories 2 or 3 not covered by P5a and P5b

#### **Deco-Paint Directive**

VOC content	100 %
VOC content (Water content was discounted)	870 <sup>g</sup> /l

#### Industrial Emissions Directive (IED)

VOC content	100 %
VOC content (Water content was discounted)	870 <sup>g</sup> /l

# Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

# Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

Pollutant release and transfer registers (PRTR)				
Name of substance	CAS No	Remarks	Threshold for releases to air (kg/year)	
Toluene	108-88-3	(11)		

Legend

(11) Single pollutants are to be reported if the threshold for BTEX (the sum parameter of benzene, toluene, ethyl benzene, xylenes) is exceeded

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



### Toluene ROTISOLV® ≥99,8 %, GC Ultra Grade

Water Framework Directive (WFD)

#### article number: KK46

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
Toluene	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment		a)	

#### Legend

a) Indicative list of the main pollutants

## Regulation on the marketing and use of explosives precursors

not listed

#### **Regulation on drug precursors**

Name of substance	CAS No	Wt%	Classification	CN Code	Threshold level
Toluene	108-88-3	100	Category 3	2902 30 00	

#### Regulation on substances that deplete the ozone layer (ODS)

not listed

#### Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

#### **Regulation on persistent organic pollutants (POP)**

not listed

#### **Other information**

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

#### UN Convention against Illicit Traffic in Narcotic Drugs and Psychotropic Substances

Name of substance	CAS No	Listed in	HS code
Toluene	108-88-3	Table II	2902.30

#### **National inventories**

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



### Toluene ROTISOLV® ≥99,8 %, GC Ultra Grade

#### article number: KK46

Country	Inventory	Status
JP	ISHA-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

#### Legend

Legena	
AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EÌNEĆS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NCI	National Chemical Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Rea.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

#### 15.2 Chemical safety assessment

According to REACH, Article 14 (1) a chemical safety assessment has been carried out for this substance or components of this mixture when the substance has been registered in quantities of 10 tonnes or more per year per registrant.

### **SECTION 16: Other information**

#### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
15.1	VOC content: 100 % 870 <sup>g</sup> / <sub>l</sub>	VOC content: 100 %	yes
15.1		VOC content (Water content was discounted): 870 <sup>g</sup> / <sub>l</sub>	yes
15.1		National inventories: change in the listing (table)	yes

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

# ® Roth

### Toluene ROTISOLV® ≥99,8 %, GC Ultra Grade

#### article number: KK46

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
15.2	Chemical Safety Assessment: No Chemical Safety Assessment has been car- ried out for this substance.	Chemical safety assessment: According to REACH, Article 14 (1) a chemical safety assessment has been carried out for this substance or components of this mixture when the substance has been registered in quantities of 10 tonnes or more per year per registrant.	yes

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2006/15/EC	Commission Directive establishing a second list of indicative occupational exposure limit values in imple- mentation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concern- ing the International Carriage of Dangerous Goods by Road)
BCF	Bioconcentration factor
CAP. 424	Occupational Health and Safety Authority Act (CAP. 424)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
CN Code	Combined Nomenclature
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identi- fier of substances commercially available within the EU (European Union)
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)
ΙΑΤΑ	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



### Toluene ROTISOLV® ≥99,8 %, GC Ultra Grade

#### article number: KK46

Abbr.	Descriptions of used abbreviations
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
STEL	Short-term exposure limit
SVHC	Substance of Very High Concern
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

#### Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs (central nervous system) through prolonged or repeated exposure (if inhaled).
H412	Harmful to aquatic life with long lasting effects.

#### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.