



SAFETY DATA SHEET

Version #: 1,1 Issue date: 24-March-2022 Supersedes date: 24-March-2022 Revision date: 12-May-2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture LABEL OFF 50

Registration number -

UFI:

Austria: 5K2X-285Q-9000-EPUV
Belgium: 5K2X-285Q-9000-EPUV
Bulgaria: 5K2X-285Q-9000-EPUV
Croatia: 5K2X-285Q-9000-EPUV
Cyprus: 5K2X-285Q-9000-EPUV
Czech Republic: 5K2X-285Q-9000-EPUV
Denmark: 5K2X-285Q-9000-EPUV
Estonia: 5K2X-285Q-9000-EPUV
EU: 5K2X-285Q-9000-EPUV
Finland: 5K2X-285Q-9000-EPUV
France: 5K2X-285Q-9000-EPUV
Germany: 5K2X-285Q-9000-EPUV
Great Britain: 5K2X-285Q-9000-EPUV
Greece: 5K2X-285Q-9000-EPUV
Hungary: 5K2X-285Q-9000-EPUV
Iceland: 5K2X-285Q-9000-EPUV
Italy: 5K2X-285Q-9000-EPUV
Latvia: 5K2X-285Q-9000-EPUV
Lithuania: 5K2X-285Q-9000-EPUV
Luxembourg: 5K2X-285Q-9000-EPUV
Malta: 5K2X-285Q-9000-EPUV
Netherlands: 5K2X-285Q-9000-EPUV
Norway: 5K2X-285Q-9000-EPUV
Poland: 5K2X-285Q-9000-EPUV
Portugal: 5K2X-285Q-9000-EPUV
Romania: 5K2X-285Q-9000-EPUV
Slovakia: 5K2X-285Q-9000-EPUV
Slovenia: 5K2X-285Q-9000-EPUV
Spain: 5K2X-285Q-9000-EPUV
Sweden: 5K2X-285Q-9000-EPUV

Synonyms

None.

Product code

BDS001045AE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaners - Precision

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company name CRC Industries Europe bv

Address Touwslagerstraat 1
9240 Zele
Belgium

Telephone +32(0)52/45.60.11

Fax +32(0)52/45.00.34

E-mail hse@crcind.com

Website www.crcind.com

1.4. Emergency telephone number

Tel.: +32(0)52/45.60.11 (office hours: 9-17h CET)

General in EU

112 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Austria National Poisons Information Centre

+431 406 4343 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Belgium National Poisons Control Center

070 245 245 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Lieferant / Supplier:
Carl Roth GmbH + Co KG
Schoemperlenstr. 3-5
76185 Karlsruhe, Germany
+49 721 5606 0
sicherheit@carlroth.de

Bulgaria National Toxicological Information Centre	+359 2 9154233 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Czech Republic National Poisons Information Centre	+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Denmark National Poisons Control Center	+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Estonia National Poisons Information Centre	16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be available for the Emergency Service.)
Finland National Poison Information Center	(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
France National Poisons Control Center	ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Hungary National Emergency Phone Number	36 80 20 11 99 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Lithuania Neatidėliotina informacija apsinuodijus	+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Malta Accident and Emergency Department	2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Netherlands National Poisons Information Center (NVIC)	030-274 88 88 (Only for the purpose of informing medical personnel in cases of acute intoxications)
Norway Norwegian Poison Information Center	22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Portugal Poison Centre	800 250 250 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Romania Număr de telefon care poate fi apelat în caz de urgență:	021 5992300, int. 291 Spitalul Clinic de Urgență București: spital@urgentaflorasca.ro
Romania	0265 212111, 0265 211292, 0265 217235 Spitalul Clinic Județean de Urgență Târgu Mureș: secretariat@spitjudms.ro
Slovakia National Toxicological Information Centre	+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Sweden National Poison Information Center	112 - and ask for Poison Information (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Switzerland Tox Info Suisse	145 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Aerosols	Category 1	H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated.
----------	------------	---

Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Skin sensitisation	Category 1	H317 - May cause an allergic skin reaction.
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.

Environmental hazardsHazardous to the aquatic environment,
long-term aquatic hazard

Category 2

H411 - Toxic to aquatic life with
long lasting effects.**2.2. Label elements****Label according to Regulation (EC) No. 1272/2008 as amended****Contains:** Cyclohexane, Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane, Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics, Orange, sweet, extract**Hazard pictograms****Signal word**

Danger

Hazard statements

H222 Extremely flammable aerosol.
 H229 Pressurized container: May burst if heated.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements**Prevention**

P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing mist/vapours.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves.

Response

Not assigned.

Storage

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label informationRegulation (EC) No 648/2004 on detergents:
aliphatic hydrocarbons > 30 %
perfumes: d-limonene**2.3. Other hazards**

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****General information**

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	25 - 50	EC921-024-6 921-024-6	01-2119475514-35	-	
Classification: Flam. Liq. 2;H225, Skin Irrit. 2;H315, STOT SE 3;H336, Asp. Tox. 1;H304, Aquatic Chronic 2;H411					
Cyclohexane	10 - <25	110-82-7 203-806-2	01-2119463273-41	601-017-00-1	#
Classification: Flam. Liq. 2;H225, Skin Irrit. 2;H315, STOT SE 3;H336, Asp. Tox. 1;H304, Aquatic Acute 1;H400, Aquatic Chronic 1;H410					
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	10 - 25	EC919-857-5 919-857-5	01-2119463258-33	-	
Classification: Flam. Liq. 3;H226, STOT SE 3;H336, Asp. Tox. 1;H304					

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Orange, sweet, extract	10 - 25	8028-48-6 232-433-8	01-2119493353-35	-	
Classification: Flam. Liq. 3;H226, Skin Irrit. 2;H315, Skin Sens. 1;H317, Asp. Tox. 1;H304, Aquatic Chronic 2;H411					
Carbon dioxide	1 - 5	124-38-9 204-696-9	-	-	#
Classification: Press. Gas;H280					

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed May cause drowsiness or dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Extremely flammable aerosol.

5.1. Extinguishing media

Suitable extinguishing media Foam. Powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire fighting procedures Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

For emergency responders Keep unnecessary personnel away. Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

6.2. Environmental precautions Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. The product is immiscible with water and will spread on the water surface. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria

Components

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Type

TWA (MAK)

Value

200 ppm

Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components

Carbon dioxide (CAS 124-38-9)

Type

Ceiling

Value

18000 mg/m³

10000 ppm

MAK

9000 mg/m³

5000 ppm

Cyclohexane (CAS 110-82-7)

MAK

700 mg/m³

200 ppm

STEL

2800 mg/m³

800 ppm

Belgium. Exposure Limit Values

Components

Carbon dioxide (CAS 124-38-9)

Type

STEL

Value

54784 mg/m³

30000 ppm

TWA

9131 mg/m³

5000 ppm

Cyclohexane (CAS 110-82-7)

TWA

350 mg/m³

100 ppm

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components

Carbon dioxide (CAS 124-38-9)

Type

TWA

Value

9000 mg/m³

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value
Cyclohexane (CAS 110-82-7)	TWA	5000 ppm
		700 mg/m ³
		200 ppm

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	MAC	9000 mg/m ³
Cyclohexane (CAS 110-82-7)	MAC	5000 ppm
		700 mg/m ³
		200 ppm

Czech Republic. OELs. Government Decree 361

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	Ceiling	45000 mg/m ³
	TWA	9000 mg/m ³
Cyclohexane (CAS 110-82-7)	Ceiling	2000 mg/m ³
	TWA	700 mg/m ³

Denmark

Components	Type	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA	25 ppm

Denmark. Exposure Limit Values

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TLV	9000 mg/m ³
		5000 ppm
Cyclohexane (CAS 110-82-7)	TLV	172 mg/m ³
		50 ppm

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m ³
		5000 ppm
Cyclohexane (CAS 110-82-7)	TWA	700 mg/m ³
		200 ppm

Finland

Components	Type	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA	500 mg/m ³

Finland. Workplace Exposure Limits

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9100 mg/m ³
		5000 ppm
Cyclohexane (CAS 110-82-7)	STEL	875 mg/m ³
		250 ppm
		350 mg/m ³

Finland. Workplace Exposure Limits

Components	Type	Value
		100 ppm

France

Components	Type	Value
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic s, < 5% n-hexane	STEL	1500 mg/m3
	TWA	1000 mg/m3

France. OELs. Indicative Occupational Exposure Limits as Prescribed by Order of 30 June 2004, as amended

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	VME	9000 mg/m3
		9000 mg/m3
		5000 ppm
		5000 ppm

France. OELs. Occupational Exposure Limits as Prescribed by Art. R.4412-149 of Labor Code, as amended

Components	Type	Value
Cyclohexane (CAS 110-82-7)	VME	700 mg/m3
		200 ppm

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	VME	9000 mg/m3
Regulatory status: Regulatory indicative (VRI)		5000 ppm
Regulatory status: Regulatory indicative (VRI)		
Cyclohexane (CAS 110-82-7)	VLE	1300 mg/m3
Regulatory status: Indicative limit (VL)		375 ppm
Regulatory status: Indicative limit (VL)		
	VME	700 mg/m3
Regulatory status: Regulatory binding (VRC)		200 ppm
Regulatory status: Regulatory binding (VRC)		

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9100 mg/m3
		5000 ppm
Cyclohexane (CAS 110-82-7)	TWA	700 mg/m3
		200 ppm

Germany - TRGS 900

Components	Type	Value
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic s, < 5% n-hexane	TWA	700 mg/m3
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA	300 mg/m3

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	AGW	9100 mg/m3
		5000 ppm
Cyclohexane (CAS 110-82-7)	AGW	700 mg/m3
		200 ppm

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3
		5000 ppm
	TWA	9000 mg/m3
Cyclohexane (CAS 110-82-7)	TWA	5000 ppm
		700 mg/m3
		200 ppm

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
Cyclohexane (CAS 110-82-7)	TWA	700 mg/m3

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm
Cyclohexane (CAS 110-82-7)	TWA	172 mg/m3
		50 ppm

Ireland. Occupational Exposure Limits

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm
Cyclohexane (CAS 110-82-7)	TWA	700 mg/m3
		200 ppm

Italy. Occupational Exposure Limits

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm
Cyclohexane (CAS 110-82-7)	TWA	350 mg/m3
		100 ppm

Latvia. OELs. Occupational exposure limit values of chemical substances in work environment

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm
Cyclohexane (CAS 110-82-7)	TWA	80 mg/m3
		23 ppm

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m ³
		5000 ppm
Cyclohexane (CAS 110-82-7)	TWA	700 mg/m ³
		200 ppm

Luxembourg. Binding Occupational exposure limit values (Annex I), Memorial A

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m ³
		5000 ppm
Cyclohexane (CAS 110-82-7)	TWA	700 mg/m ³
		200 ppm

Malta. OELs. Occupational Exposure Limit Values (L.N. 227. of Occupational Health and Safety Authority Act (CAP. 424), Schedules I and V)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m ³
		5000 ppm
Cyclohexane (CAS 110-82-7)	TWA	700 mg/m ³
		200 ppm

Netherlands. OELs (binding)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m ³
Cyclohexane (CAS 110-82-7)	STEL	1400 mg/m ³
	TWA	700 mg/m ³

Norway

Components	Type	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA	275 mg/m ³

Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TLV	9000 mg/m ³
		5000 ppm
Cyclohexane (CAS 110-82-7)	TLV	525 mg/m ³
		150 ppm

Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	27000 mg/m ³
	TWA	9000 mg/m ³
Cyclohexane (CAS 110-82-7)	STEL	1000 mg/m ³
	TWA	300 mg/m ³

Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm
Cyclohexane (CAS 110-82-7)	TWA	700 mg/m3
		200 ppm

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm
Cyclohexane (CAS 110-82-7)	TWA	100 ppm

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm
Cyclohexane (CAS 110-82-7)	TWA	700 mg/m3
		200 ppm

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm
Cyclohexane (CAS 110-82-7)	TWA	700 mg/m3
		200 ppm

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm
Cyclohexane (CAS 110-82-7)	TWA	700 mg/m3
		200 ppm

Spain. Occupational Exposure Limits

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9150 mg/m3
		5000 ppm
Cyclohexane (CAS 110-82-7)	TWA	700 mg/m3
		200 ppm

Sweden

Components	Type	Value
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic s, < 5% n-hexane	STEL (STV)	300 ppm
	TWA	200 ppm
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	STEL (STV)	600 mg/m3

Sweden		
Components	Type	Value
	TWA	300 mg/m ³
Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)		
Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	18000 mg/m ³
		10000 ppm
Cyclohexane (CAS 110-82-7)	TWA	9000 mg/m ³
		5000 ppm
	TWA	700 mg/m ³
		200 ppm
Switzerland		
Components	Type	Value
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	TWA	500 ppm
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	STEL	6000 mg/m ³
	TWA	300 mg/m ³
Switzerland. SUVA Grenzwerte am Arbeitsplatz		
Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m ³
		5000 ppm
Cyclohexane (CAS 110-82-7)	STEL	2800 mg/m ³
		800 ppm
	TWA	700 mg/m ³
		200 ppm
UK. EH40 Workplace Exposure Limits (WELs)		
Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	27400 mg/m ³
		15000 ppm
	TWA	9150 mg/m ³
		5000 ppm
Cyclohexane (CAS 110-82-7)	STEL	1050 mg/m ³
		300 ppm
	TWA	350 mg/m ³
		100 ppm
EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU		
Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m ³
		5000 ppm
Cyclohexane (CAS 110-82-7)	TWA	700 mg/m ³
		200 ppm

Biological limit values**Croatia. BLV. Dangerous Substance Exposure Limit Values at Workplace, Annexes 4 (as amended)**

Components	Value	Determinant	Specimen	Sampling Time
Cyclohexane (CAS 110-82-7)	450 µg/l	Cyclohexanol	Blood	*
	3,2 mg/g	Cyclohexanol	Creatinine in urine	*
	150 mg/g	1,2-Cyclohexanediol	Creatinine in urine	*
	3,61 mmol/mol	Cyclohexanol	Creatinine in urine	*
	146 mmol/mol	1,2-Cyclohexanediol	Creatinine in urine	*
	4,49 umol/l	Cyclohexanol	Blood	*

* - For sampling details, please see the source document.

Germany. TRGS 903, BAT List (Biological Limit Values)

Components	Value	Determinant	Specimen	Sampling Time
Cyclohexane (CAS 110-82-7)	150 mg/g	1,2-Cyclohexanediol (nach Hydrolyse)	Creatinine in urine	*

* - For sampling details, please see the source document.

Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)

Components	Value	Determinant	Specimen	Sampling Time
Cyclohexane (CAS 110-82-7)	150 mg/g	Gesamt-1,2-Cyclohexandiol	Creatinine in urine	*

* - For sampling details, please see the source document.

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs)**General Population**

Components	Value	Assessment factor	Notes
Cyclohexane (CAS 110-82-7)			
Long-term, Local, Inhalation	206 mg/m ³	1,7	Repeated dose toxicity
Long-term, Systemic, Dermal	1186 mg/kg bw/day	1,7	Repeated dose toxicity
Long-term, Systemic, Inhalation	206 mg/m ³	1,7	Repeated dose toxicity
Long-term, Systemic, Oral	59,4 mg/kg bw/day	1,7	Repeated dose toxicity
Short-term, Local, Inhalation	412 mg/m ³	1,7	respiratory tract irritation
Short-term, Systemic, Inhalation	412 mg/m ³	1,7	Neurotoxicity
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane (CAS EC921-024-6)			
Long-term, Systemic, Dermal	699 mg/kg bw/day		
Long-term, Systemic, Inhalation	608 mg/m ³		
Long-term, Systemic, Oral	699 mg/kg bw/day		
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (CAS EC919-857-5)			
Long-term, Systemic, Dermal	300 mg/kg		
Long-term, Systemic, Inhalation	900 mg/m ³		
Long-term, Systemic, Oral	300 mg/kg		
Orange, sweet, extract (CAS 8028-48-6)			
Long-term, Systemic, Dermal	4,44 mg/kg bw/day	225	Repeated dose toxicity
Long-term, Systemic, Inhalation	7,78 mg/m ³	225	Repeated dose toxicity

Workers

Components	Value	Assessment factor	Notes
Cyclohexane (CAS 110-82-7)			
Long-term, Local, Inhalation	700 mg/m ³	1	Neurotoxicity
Long-term, Systemic, Dermal	2016 mg/kg bw/day	1	Repeated dose toxicity
Long-term, Systemic, Inhalation	700 mg/m ³	1	Neurotoxicity
Short-term, Local, Inhalation	700 mg/m ³	1	Neurotoxicity
Short-term, Systemic, Inhalation	700 mg/m ³	1	Neurotoxicity
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane (CAS EC921-024-6)			
Long-term, Systemic, Dermal	773 mg/kg bw/day		
Long-term, Systemic, Inhalation	2035 mg/m ³		

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (CAS EC919-857-5)

Long-term, Systemic, Dermal 300 mg/kg
Short-term, Systemic, Inhalation 1500 mg/m³

Orange, sweet, extract (CAS 8028-48-6)

Long-term, Systemic, Inhalation 31,1 mg/m³ 112,5 Repeated dose toxicity
Short-term, Local, Dermal 185,8 µg/cm² 30 Skin Sensitisation

Predicted no effect concentrations (PNECs)

Components	Value	Assessment factor	Notes
Cyclohexane (CAS 110-82-7)			
Freshwater	0,207 mg/l	1	
Sediment (freshwater)	3,627 mg/kg	1	
Soil	2,99 mg/kg	1	
STP	3,24 mg/l	1	
Orange, sweet, extract (CAS 8028-48-6)			
Freshwater	5,4 µg/l	50	
Sediment (freshwater)	1,3 mg/kg		
Soil	0,261 mg/kg		
STP	2,1 mg/l	10	

Exposure guidelines

Croatia ELVs: Skin designation

Cyclohexane (CAS 110-82-7) Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

General information

Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection

Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166.

Skin protection

- Hand protection

When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Nitrile gloves are recommended. Suitable gloves can be recommended by the glove supplier.

- Other

Wear appropriate chemical resistant clothing.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with organic vapour cartridge and full facepiece. (Filter type AX)

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

Hygiene measures

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

Environmental exposure controls

Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Form	Aerosol.
Colour	Colourless to yellow.
Odour	Citrus.
Melting point/freezing point	-74 °C (-101,2 °F) estimated
Boiling point or initial boiling point and boiling range	55 - 190
Flammability (solid, gas)	Not available.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) 0,6 % estimated

Explosive limit – upper (%) 8,4 % estimated

Flash point < 0 °C (< 32,0 °F)

Auto-ignition temperature > 200 °C (> 392 °F)

Decomposition temperature Not available.

pH Not applicable.

Solubility(ies)

Solubility (water) Insoluble in water

Vapour pressure 57300 hPa estimated

Vapour density Not available.

Relative density 0,75 g/cm³ at 20°C

Particle characteristics Not available.

9.2. Other information

9.2.1. Information with regard to physical hazard classes No relevant additional information available.

9.2.2. Other safety characteristics

Explosive properties Not explosive.

Oxidising properties Not oxidising.

VOC 718 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid high temperatures.

10.5. Incompatible materials Strong oxidising agents.

10.6. Hazardous decomposition products Carbon oxides.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms May cause drowsiness or dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

11.1. Information on toxicological effects

Acute toxicity Classification based on calculation method. Based on available data, the classification criteria are not met.

Components	Species	Test Results
Cyclohexane (CAS 110-82-7)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	> 32,88 mg/l
Oral		
LD50	Rat	> 5000 mg/kg

Components	Species	Test Results
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane		
Acute		
Dermal		
LD50	Rat	2920 mg/kg bw/day, 24 h
Inhalation		
LC50	Rat	25200 mg/m ³ , 4 h
Oral		
LD50	Rat	5840 mg/kg bw/day
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg
Oral		
LD50	Rat	> 5000 mg/kg
Orange, sweet, extract (CAS 8028-48-6)		
Acute		
Dermal		
LD50	Rabbit	5000 mg/kg bw/day
Oral		
LD50	Rat	> 2000 mg/kg/day
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory sensitisation	Based on available data, the classification criteria are not met.	
Skin sensitisation	May cause an allergic skin reaction.	
Germ cell mutagenicity	Based on available data, the classification criteria are not met.	
Carcinogenicity	Based on available data, the classification criteria are not met.	
Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)		
Not listed.		
Reproductive toxicity	Based on available data, the classification criteria are not met.	
Specific target organ toxicity - single exposure	May cause drowsiness or dizziness.	
Specific target organ toxicity - repeated exposure	Based on available data, the classification criteria are not met.	
Aspiration hazard	Not likely, due to the form of the product.	
Mixture versus substance information	Not available.	
11.2. Information on other hazards		
Endocrine disrupting properties	The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.	
Other information	Not available.	

SECTION 12: Ecological information

12.1. Toxicity Very toxic to aquatic life with long lasting effects.

Components	Species	Test Results	
Cyclohexane (CAS 110-82-7)			
Aquatic			
<i>Acute</i>			
Algae	EC50	Algae	3,4 mg/l, 72 hours
Crustacea	EC50	Daphnia	0,9 mg/l, 48 hours
Fish	LC50	Fish	4,53 mg/l, 96 hours

Components	Species		Test Results
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane			
Aquatic			
<i>Acute</i>			
Algae	EC50	Algae	> 30 - < 100 mg/l, 72 h
Crustacea	EC50	Daphnia	3 mg/l, 48 h
Fish	LC50	Fish	11,4 mg/l, 96 h
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics			
<i>Acute</i>			
Other	LC50	Pseudokirchnerella subcapitata	> 1000 mg/l, 72 h
Aquatic			
<i>Acute</i>			
Fish	LC50	Oncorhynchus mykiss	> 1000 mg/l
12.2. Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.		
12.3. Bioaccumulative potential			
Partition coefficient n-octanol/water (log Kow)			
Cyclohexane			3,44
Bioconcentration factor (BCF)	Not available.		
12.4. Mobility in soil	No data available.		
12.5. Results of PBT and vPvB assessment	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.		
12.6. Endocrine disrupting properties	The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.		
12.7. Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential. GWP: 0		

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1950
14.2. UN proper shipping name	AEROSOLS, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Hazard No. (ADR)	Not available.
Tunnel restriction code	D
14.4. Packing group	Not available.
14.3. Transport hazard class(es)	
ADR/RID - Classification code:	5F

- 14.5. Environmental hazards yes
 14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

- 14.1. UN number UN1950
 14.2. UN proper shipping name Aerosols, flammable
 14.3. Transport hazard class(es)
 Class 2.1
 Subsidiary risk -
 14.4. Packing group Not available.
 14.5. Environmental hazards yes
 ERG Code 10L
 14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
 Other information
 Passenger and cargo aircraft Allowed with restrictions.
 Cargo aircraft only Allowed with restrictions.


IMDG

- 14.1. UN number UN1950
 14.2. UN proper shipping name Aerosols, flammable, MARINE POLLUTANT
 14.3. Transport hazard class(es)
 Class 2.1
 Subsidiary risk -
 14.4. Packing group Not available.
 14.5. Environmental hazards
 Marine pollutant Yes
 EmS F-D, S-U
 14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
 14.7. Maritime transport in bulk according to IMO instruments Not established.

ADR; IATA; IMDG



Marine pollutant



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

- Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended**
 Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Carbon dioxide (CAS 124-38-9)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Cyclohexane (CAS 110-82-7)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Cyclohexane (CAS 110-82-7)

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

National regulations

This safety data sheet conforms to the following laws, regulations and standards:

Act on the management of packaging and packaging waste of June 13, 2013
Regulation of the Minister of Health of June 11, 2012 on the categories of dangerous substances and dangerous preparations whose packaging should be fitted with child-resistant closures and a tactile warning of danger
REGULATION OF THE MINISTER OF HEALTH of February 2, 2011 on tests and measurements of factors harmful to health in working environments
Regulation of Ministry of Labor and Social Policy of June 6, 2014. On the matter of maximum permissible concentrations and intensities of harmful factors in the work environment (Journal of Laws 2014, item. 817)
Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices Decree No. 25/2000. (IX. 30.) EüM-SzCsM of the Minister of Health and the Minister of Social and Family Affairs on chemical safety at work
Act No. 93 of 1993 on Labour Safety (1993.évi XCIII.), as amended
Government Decree No. 220 of 2004 (VII. 21.) providing rules on the protection of surface waters quality
Government Decree No. 98/2001 (VI. 15.), on the conditions of the activities related to hazardous waste, and Ministry of Environmental Affairs Decree No. 16/2001 (VII. 18.), on the register of waste
s Public Act No. XXV of 2000 on Chemical Safety, and Application Decree No. 44/2000. (XII.27.) EüM [of the Ministry of Health]
Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.
AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).
ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).

CAS: Chemical Abstract Service.
Ceiling: Short Term Exposure Limit Ceiling value.
CEN: European Committee for Standardization.
CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.
GWP: Global Warming Potential.
IATA: International Air Transport Association.
IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.
IMDG: International Maritime Dangerous Goods.
MAC: Maximum Allowed Concentration.
MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).
MARPOL: International Convention for the Prevention of Pollution from Ships.
PBT: Persistent, bioaccumulative and toxic.
REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals).
RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.
STEL: Short term exposure limit.
TLV: Threshold Limit Value.
TWA: Time Weighted Average.
VLE: Exposure Limit Value.
VME: Exposure Average Value.
VOC: Volatile organic compounds.
vPvB: Very persistent and very bioaccumulative.
STEL: Short-term Exposure Limit.
Not available.

References

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under Sections 2 to 15

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

Revision information

HazReg Data: Europe - EU

Training information

Follow training instructions when handling this material.

Disclaimer

CRC Industries Europe bvba cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.