SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

LABEL OFF 50

of the mixture

Registration number

5K2X-285Q-9000-EPUV UFI:

Synonyms None.

BDS001045AE **Product code** 24-March-2022 Issue date

1.1 Version number

Revision date 12-May-2022 Supersedes date 24-March-2022

1.2. Relevant identified uses of the substance or mixture and uses advised against

Cleaners - Precision Identified uses

None known. Uses advised against

1.3. Details of the supplier of the safety data sheet

Company name CRC Industries Europe by

Address Touwslagerstraat 1

> 9240 Zele Belgium

Telephone +32(0)52/45.60.11

> hse@crcind.com www.crcind.com

Company name CRC Industries UK Ltd.

Wylds Road **Address**

> Castlefield Industrial Estate TA6 4DD Bridgwater Somerset

United Kingdom

Telephone +44 1278 727200 Fax +44 1278 425644 E-mail hse.uk@crcind.com Website www.crcind.com

1.4. Emergency telephone

number

Tel.:(+44)(0)1278 72 7200 (office hours: 9-17h CET)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

H222 - Extremely flammable Aerosols Category 1

aerosol.

H229 - Pressurized container: May

burst if heated.

Lieferant | Supplier:

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5

76185 Karlsruhe, Germany

+49 721 5606 0

sicherheit@carlroth.de

Health hazards

Skin corrosion/irritation Category 2 H315 - Causes skin irritation.

Skin sensitisation H317 - May cause an allergic skin Category 1

reaction.

Specific target organ toxicity - single Category 3 narcotic effects H336 - May cause drowsiness or

exposure dizziness.

Material name: LABEL OFF 50 - Kontakt chemie - Europe SDS GREAT BRITAIN

BDS001045AE Version #: 1.1 Revision date: 12-May-2022 Issue date: 24-March-2022

Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard

Category 2

H411 - Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Cyclohexane, Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane, Hydrocarbons, Contains:

C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics, Orange, sweet, extract

Hazard pictograms



Signal word Danger

Hazard statements

Extremely flammable aerosol. H222

Pressurized container: May burst if heated. H229

Causes skin irritation. H315

May cause an allergic skin reaction. H317 May cause drowsiness or dizziness. H336

Toxic to aquatic life with long lasting effects. H411

Precautionary statements

Prevention

Keep out of reach of children. P102

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

Do not spray on an open flame or other ignition source. P211

Do not pierce or burn, even after use. P251

Avoid breathing mist/vapours. P261

Use only outdoors or in a well-ventilated area. P271

Avoid release to the environment. P273

Wear protective gloves. P280

Not assigned. Response

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P410 + P412

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

Regulation (EC) No 648/2004 on detergents: Supplemental label information

aliphatic hydrocarbons > 30 %

perfumes: d-limonene

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation 2.3. Other hazards

(EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or

Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

Mixture

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane	25 - 50	EC921-024-6 921-024-6	01-2119475514-35	-	
Classification		2;H225, Skin Irrit. 2;F quatic Chronic 2;H41	1315, STOT SE 3;H336, As 1	р. Тох.	
Cyclohexane	10 - <25	110-82-7 203-806-2	01-2119463273-41	601-017-00-1	#
Classification	•		l315, STOT SE 3;H336, As Aquatic Chronic 1;H410	р. Тох.	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	10 - 25	EC919-857-5 919-857-5	01-2119463258-33	-	

Classification: Flam. Liq. 3;H226, STOT SE 3;H336, Asp. Tox. 1;H304

SDS GREAT BRITAIN BDS001045AE Version #: 1.1 Revision date: 12-May-2022 Issue date: 24-March-2022

Chemical name	%	CAS-No. / EC No	. REACH Registration No.	Index No.	Notes
Orange, sweet, extract	10 - 25	8028-48-6 232-433-8	01-2119493353-35	-	
Classific		3;H226, Skin Irrit. 2; quatic Chronic 2;H41	H315, Skin Sens. 1;H317, As l1	p. Tox.	
Carbon dioxide	1 - 5	124-38-9 204-696-9	-	-	#
Classific	ation: Press. Ga	s;H280			

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

centre or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth. Ingestion

4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Skin irritation. May cause

redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Extremely flammable aerosol.

5.1. Extinguishing media

Suitable extinguishing

media

Foam. Powder. Carbon dioxide (CO2).

Unsuitable extinguishing

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture Contents under pressure. Pressurised container may explode when exposed to heat or flame.

During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with

face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire fighting procedures

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose

holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. In the

event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

For emergency responders

Keep unnecessary personnel away. Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For

personal protection, see section 8 of the SDS.

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all 6.2. Environmental precautions environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into

drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. The product is immiscible with water and will spread on the water surface. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)

7.3. Specific end use(s)

Not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Exposure Limits (WELs)

Components	Туре	Value	
Carbon dioxide (CAS 124-38-9)	STEL	27400 mg/m3	
		15000 ppm	
	TWA	9150 mg/m3	
		5000 ppm	
Cyclohexane (CAS 110-82-7)	STEL	1050 mg/m3	
		300 ppm	
	TWA	350 mg/m3	
		100 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures

Follow standard monitoring procedures.

Derived no effect levels (DNELs)

General Population

Components	Value	Assessment factor	Notes
Cyclohexane (CAS 110-82-7)			
Long-term, Local, Inhalation	206 mg/m3	1.7	Repeated dose toxicity
Long-term, Systemic, Dermal	1186 mg/kg bw/day	1.7	Repeated dose toxicity
Long-term, Systemic, Inhalation	206 mg/m3	1.7	Repeated dose toxicity
Long-term, Systemic, Oral	59.4 mg/kg bw/day	1.7	Repeated dose toxicity
Short-term, Local, Inhalation	412 mg/m3	1.7	respiratory tract irritation
Short-term, Systemic, Inhalation	412 mg/m3	1.7	Neurotoxicity
Hydrocarbons, C6-C7, n-alkanes,isoalkane	es,cyclics,< 5% n-hexane (CA	S EC921-024-6)	
Long-term, Systemic, Dermal	699 mg/kg bw/day		
Long-term, Systemic, Inhalation Long-term, Systemic, Oral	608 mg/m3 699 mg/kg bw/day		
Hydrocarbons, C9-C11, n-alkanes, isoalka	ines, cyclics, < 2% aromatics	(CAS EC919-857-5)	
Long-term, Systemic, Dermal	300 mg/kg		
Long-term, Systemic, Inhalation	900 mg/m3		

Material name: LABEL OFF 50 - Kontakt chemie - Europe

SDS GREAT BRITAIN

Long-term, Systemic, Oral 300 mg/kg Orange, sweet, extract (CAS 8028-48-6) Long-term, Systemic, Dermal 4.44 mg/kg bw/day 225 Repeated dose toxicity 225 Repeated dose toxicity Long-term, Systemic, Inhalation 7.78 ma/m3 Workers Components Value **Assessment factor Notes** Cyclohexane (CAS 110-82-7) Long-term, Local, Inhalation 700 mg/m3 Neurotoxicity 1 2016 mg/kg bw/day Repeated dose toxicity Long-term, Systemic, Dermal 1 Long-term, Systemic, Inhalation Neurotoxicity 700 mg/m3 1 Neurotoxicity Short-term, Local, Inhalation 700 mg/m3 1 Short-term, Systemic, Inhalation 700 mg/m3 Neurotoxicity Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics, < 5% n-hexane (CAS EC921-024-6) Long-term, Systemic, Dermal 773 mg/kg bw/day Long-term, Systemic, Inhalation 2035 mg/m3 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (CAS EC919-857-5) Long-term, Systemic, Dermal 300 mg/kg Short-term, Systemic, Inhalation 1500 mg/m3 Orange, sweet, extract (CAS 8028-48-6) Long-term, Systemic, Inhalation 31.1 mg/m3 112.5 Repeated dose toxicity Short-term, Local, Dermal 185.8 µg/cm² 30 Skin Sensitisation Predicted no effect concentrations (PNECs) Assessment factor Components Value Notes Cyclohexane (CAS 110-82-7) Freshwater 0.207 mg/l 1 Sediment (freshwater) 3.627 mg/kg 1 Soil 2.99 mg/kg 1 STP 3.24 mg/l 1 Orange, sweet, extract (CAS 8028-48-6) Freshwater 5.4 µg/l 50 Sediment (freshwater) 1.3 mg/kg Soil 0.261 mg/kg STP 2.1 mg/l 10 8.2. Exposure controls Appropriate engineering Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to controls maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower. Individual protection measures, such as personal protective equipment Use personal protective equipment as required. Personal protection equipment should be chosen **General information** according to the CEN standards and in discussion with the supplier of the personal protective equipment. Eye/face protection Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166. Skin protection When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough - Hand protection time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Nitrile gloves are recommended. Suitable gloves can be recommended by the glove supplier. - Other Wear appropriate chemical resistant clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with Respiratory protection organic vapour cartridge and full facepiece. (Filter type AX) Thermal hazards Wear appropriate thermal protective clothing, when necessary. When using do not smoke. Always observe good personal hygiene measures, such as washing Hygiene measures after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace. Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions **Environmental exposure** from ventilation or work process equipment should be checked to ensure they comply with the controls requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable

levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid.
Form Aerosol.

Colour Colourless to yellow.

Odour Citrus.

Odour threshold Not available.

pH Not applicable.

Melting point/freezing point -74 °C (-101.2 °F) estimated

Initial boiling point and boiling

range

55 - 190

Flash point < 0 °C (< 32.0 °F)

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

0.6 % estimated

(%)

Flammability limit - upper

8.4 % estimated

(%)

Vapour pressure 57300 hPa estimated

Vapour density Not available.

Relative density 0.75 g/cm3 at 20°C

Solubility(ies)

Solubility (water) Insoluble in water

Auto-ignition temperature > 200 °C (> 392 °F)

Decomposition temperatureNot available.ViscosityNot available.Explosive propertiesNot explosive.Oxidising propertiesNot oxidising.

9.2. Other information

VOC 718 g/l

SECTION 10: Stability and reactivity

10.1. ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid high temperatures.10.5. Incompatible materials Strong oxidising agents.

10.6. Hazardous decomposition products

Carbon oxides.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Eye contactDirect contact with eyes may cause temporary irritation. **Skin contact**Causes skin irritation. May cause an allergic skin reaction.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms May cause drowsiness or dizziness. Headache. Nausea, vomiting. Skin irritation. May cause

redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

11.1. Information on toxicological effects

Material name: LABEL OFF 50 - Kontakt chemie - Europe SDS GREAT BRITAIN

not met.

Components **Species Test Results** Cyclohexane (CAS 110-82-7)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

LC50 Rat > 32.88 mg/l

Oral

LD50 Rat > 5000 mg/kg

Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane

Acute Dermal

LD50 Rat 2920 mg/kg bw/day, 24 h

Inhalation

LC50 Rat 25200 mg/m³, 4 h

Oral

LD50 Rat 5840 mg/kg bw/day

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Acute Dermal

LD50 Rabbit > 5000 mg/kg

Oral

LD50 Rat > 5000 mg/kg

Orange, sweet, extract (CAS 8028-48-6)

Acute Dermal

LD50 Rabbit 5000 mg/kg bw/day

Oral

LD50 Rat > 2000 mg/kg/day

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Based on available data, the classification criteria are not met. Respiratory sensitisation

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity

Specific target organ toxicity -

single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard Not likely, due to the form of the product.

Mixture versus substance

information

Not available.

SECTION 12: Ecological information

12.1. Toxicity Very toxic to aquatic life with long lasting effects.

Components **Species Test Results** Cyclohexane (CAS 110-82-7) Aquatic Acute Algae EC50 Algae 3.4 mg/l, 72 hours

Crustacea EC50 Daphnia 0.9 mg/l, 48 hours

Material name: LABEL OFF 50 - Kontakt chemie - Europe

SDS GREAT BRITAIN

Test Results Components **Species**

Fish LC50 Fish 4.53 mg/l, 96 hours

Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane

Aquatic

Acute

FC50 > 30 - < 100 mg/l, 72 h Algae Algae

Crustacea EC50 Daphnia 3 mg/l, 48 h Fish LC50 Fish 11.4 mg/l, 96 h

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Acute

Other LC50 Pseudokirchnerella subcapitata > 1000 mg/l, 72 h

Aquatic

Acute

Fish LC50 Oncorhynchus mykiss > 1000 mg/l

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

3.44 Cyclohexane

Bioconcentration factor (BCF) Not available. 12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII.

The product contains volatile organic compounds which have a photochemical ozone creation 12.6. Other adverse effects

> potential. . GWP: 0

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents Disposal methods/information

> under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

UN1950 14.1. UN number

14.2. UN proper shipping AEROSOLS, flammable

14.3. Transport hazard class(es)

2.1 Class Subsidiary risk Label(s) 2.1

Hazard No. (ADR) Not available.

Tunnel restriction code D

14.4. Packing group Not available.

14.5. Environmental hazards

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

RID

UN1950 14.1. UN number

14.2. UN proper shipping AEROSOLS, flammable

14.3. Transport hazard class(es) 2.1 Class Subsidiary risk

Label(s) 2 1

Not available. 14.4. Packing group

14.5. Environmental hazards yes

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

ADN

14.1. UN number UN1950

AEROSOLS, flammable 14.2. UN proper shipping

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk 2.1 Label(s)

14.4. Packing group Not available.

14.5. Environmental hazards yes

Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions

for user

IATA

14.1. UN number UN1950

Aerosols, flammable 14.2. UN proper shipping

name

14.3. Transport hazard class(es)

2.1 Class Subsidiary risk

Not available. 14.4. Packing group

14.5. Environmental hazards yes **ERG Code** 10L

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft

Allowed with restrictions. Cargo aircraft only

IMDG

14.1. UN number UN1950

14.2. UN proper shipping Aerosols, flammable, MARINE POLLUTANT

14.3. Transport hazard class(es)

Class Subsidiary risk

Not available. 14.4. Packing group

14.5. Environmental hazards

Marine pollutant Yes F-D, S-U **EmS**

Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions

for user

14.7. Transport in bulk Not established.

Material name: LABEL OFF 50 - Kontakt chemie - Europe

according to Annex II of MARPOL 73/78 and the IBC

Code

BDS001045AE Version #: 1.1 Revision date: 12-May-2022 Issue date: 24-March-2022



Marine pollutant



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture **Retained direct EU regulations**

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Carbon dioxide (CAS 124-38-9)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Cyclohexane (CAS 110-82-7)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended Cyclohexane (CAS 110-82-7)

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

Material name: LABEL OFF 50 - Kontakt chemie - Europe

SDS GREAT BRITAIN BDS001045AE Version #: 1.1 Revision date: 12-May-2022 Issue date: 24-March-2022

This safety data sheet conforms to the following laws, regulations and standards:

Act on the management of packaging and packaging waste of June 13, 2013

Regulation of the Minister of Health of June 11, 2012 on the categories of dangerous substances and dangerous preparations whose packaging should be fitted with child-resistant closures and a tactile warning of danger

REGULATION OF THE MINISTER OF HEALTH of February 2, 2011 on tests and measurements of factors harmful to health in working environments

Regulation of Ministry of Labor and Social Policy of June 6, 2014. On the matter of maximum permissible concentrations and intensities of harmful factors in the work environment (Journal of Laws 2014, item. 817)

Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices Decree No. 25/2000. (IX. 30.) EüM-SzCsM of the Minister of Health and the Minister of Social and Family Affairs on chemical safety at work

Act No. 93 of 1993 on Labour Safety (1993.évi XCIII.), as amended

Government Decree No. 220 of 2004 (VII. 21.) providing rules on the protection of surface waters quality

Government Decree No. 98/2001 (VI. 15.), on the conditions of the activities related to hazardous waste, and Ministry of Environmental Affairs Decree No. 16/2001 (VII. 18.), on the register of wastes

Public Act No. XXV of 2000 on Chemical Safety, and Application Decree No. 44/2000. (XII.27.) EüM [of the Ministry of Health] Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).

CAS: Chemical Abstract Service.

Ceiling: Short Term Exposure Limit Ceiling value.

CEN: European Committee for Standardization.

CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.

GWP: Global Warming Potential.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals). RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement

International concernant le transport de marchandises dangereuses par chemin de fer).

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit.

TLV: Threshold Limit Value.

TWA: Time Weighted Average. VOC: Volatile organic compounds.

vPvB: Very persistent and very bioaccumulative.

STEL: Short-term Exposure Limit.

Not available.

Information on evaluation method leading to the classification of mixture

References

Sections 2 to 15

Full text of any H-statements not written out in full under

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Material name: LABEL OFF 50 - Kontakt chemie - Europe

SDS GREAT BRITAIN

Revision information Training information Disclaimer

H411 Toxic to aquatic life with long lasting effects.

HazReg Data: Europe - EU

Follow training instructions when handling this material.

CRC Industries Europe byba cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

Material name: LABEL OFF 50 - Kontakt chemie - Europe SDS GREAT BRITAIN 12 / 12