acc. to Safe Work Australia - Code of Practice

Ethanol ROTISOLV® HPLC Gradient Grade

date of compilation: 2018-05-18 article number: P076 Version: GHS 5.1 en

Replaces version of: 2024-03-01

Version: (GHS 5)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance **Ethanol** ROTISOLV® HPLC Gradient Grade

Article number P076 CAS number 64-17-5

Alternative name(s) Ethyl alcohol

Relevant identified uses of the substance or mixture and uses advised against 1.2

Relevant identified uses: Laboratory and analytical use

Laboratory chemical Industrial uses Professional uses

Uses advised against: Do not use for private purposes (household).

Food, drink and animal feedingstuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 Telefax: +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data
Department Health, Safety and Environment

sheet:

e-mail (competent person): sicherheit@carlroth.de

1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital		2145 West- mead, NSW	131126	

SECTION 2: Hazards identification

Classification of the substance or mixture 2.1

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.3	Serious eye damage/eye irritation		Eye Irrit. 2A	H319

For full text of abbreviations: see SECTION 16

Australia (en) Page 1 / 14



Revision: 2024-03-04

acc. to Safe Work Australia - Code of Practice

Ethanol ROTISOLV® HPLC Gradient Grade

article number: P076



The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS02, GHS07



Hazard statements

H225 Highly flammable liquid and vapour

H319 Causes serious eye irritation

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P233 Keep container tightly closed

Precautionary statements - response

P337+P313 If eye irritation persists: Get medical advice/attention

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

Precautionary statements - storage

P403+P235 Store in a well-ventilated place. Keep cool

Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of \geq 0,1%.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance Ethanol Molecular formula C_2H_6O

Molar mass 46.07 g/_{mol}

CAS No 64-17-5

Australia (en) Page 2 / 14



acc. to Safe Work Australia - Code of Practice

Ethanol ROTISOLV® HPLC Gradient Grade

article number: P076



SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In all cases of doubt, or when symptoms persist, seek medical advice.

Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

Irritation, Nausea, Vomiting, Abdominal pain, Breathing difficulties, Vertigo, Drowsiness, Narcosis, Loss of righting reflex, and ataxia

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

Australia (en) Page 3 / 14

acc. to Safe Work Australia - Code of Practice

Ethanol ROTISOLV® HPLC Gradient Grade

article number: P076



5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

Australia (en) Page 4 / 14

acc. to Safe Work Australia - Code of Practice

Ethanol ROTISOLV® HPLC Gradient Grade

article number: P076



7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
AU	ethyl alcohol (ethan- ol)	64-17-5	WES	1,00 0	1,880						WES

Notation

TWA

Ceiling-C STEL

Ceiling value is a limit value above which exposure should not occur Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8

hours time-weighted average (unless otherwise specified)

8.2 **Exposure controls**

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection.

Skin protection





Australia (en) Page 5 / 14

acc. to Safe Work Australia - Code of Practice

Ethanol ROTISOLV® HPLC Gradient Grade

article number: P076





Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 °C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

type of material

Butyl caoutchouc (butyl rubber)

material thickness

0,7mm

breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Respiratory protection





Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Colour colourless
Odour like: - alcohol

Melting point/freezing point -114 °C

Boiling point or initial boiling point and boiling 78 °C at 1,013 hPa

range

Flammability flammable liquid in accordance with GHS criteria

Lower and upper explosion limit 3.1 vol% (LEL) - 27.7 vol% (UEL)

Flash point 12 °C (c.c.)

Auto-ignition temperature 455 °C at 1,013 Pa (DIN 51794)

Decomposition temperature not relevant pH (value) 7 (20 °C)

Australia (en) Page 6 / 14

acc. to Safe Work Australia - Code of Practice

Ethanol ROTISOLV® HPLC Gradient Grade

article number: P076

Kinematic viscosity $1.519 \, ^{\text{mm}^2} /_{\text{s}}$ at 20 °C

Dynamic viscosity 1.2 mPa s at 20 °C

Solubility(ies)

Water solubility $\geq 1,000 \, ^{9}/_{1}$ at 20 °C (ECHA)

Partition coefficient

Partition coefficient n-octanol/water (log value): -0.31 (exp. (TOXNET))

Vapour pressure 59 hPa at 20 °C

Density and/or relative density

Density 0.79 ^g/_{cm³} at 20 °C

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard

classes:

Other safety characteristics:

Miscibility completely miscible with water

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

There is no additional information.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Alkali metals, Alkaline earth metal, Acetic anhydride, Peroxides, Phosphorus oxides (e.g. P2O5), Nitric acid, Nitrate, Perchlorates, => Explosive properties

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

There is no additional information.

Australia (en) Page 7 / 14



acc. to Safe Work Australia - Code of Practice

Ethanol ROTISOLV® HPLC Gradient Grade

article number: P076



Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity

Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	10,470 ^{mg} / _{kg}	rat		ECHA
inhalation: vapour	LC50	124.7 ^{mg} / _l /4h	rat		ECHA

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

vomiting, abdominal pain, nausea, Causes damage to liver through prolonged or repeated exposure if swallowed, loss of righting reflex, and ataxia

• If in eyes

Causes serious eye irritation

If inhaled

drowsiness, narcosis, vertigo, breathing difficulties, Inebriation

Australia (en) Page 8 / 14



40.5 11 1 1 11 11

acc. to Safe Work Australia - Code of Practice

Ethanol ROTISOLV® HPLC Gradient Grade

article number: P076

• If on skin

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation)

Other information

none

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0.1\%$.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)

Endpoint	Value	Species	Source	Exposure time
LC50	15,400 ^{mg} / _l	fish	ECHA	96 h
EC50	>10,000 ^{mg} / _l	aquatic invertebrates	ECHA	48 h
ErC50	22,000 ^{mg} / _l	algae	ECHA	96 h

Aquatic toxicity (chronic)

Endpoint	Value	Species	Source	Exposure time
LC50	1,806 ^{mg} / _l	aquatic invertebrates	ECHA	10 d
ErC50	675 ^{mg} / _l	algae	ECHA	4 d

12.2 Persistence and degradability

Theoretical Oxygen Demand: 2.084 $^{\rm mg}/_{\rm mg}$ Theoretical Carbon Dioxide: 1.911 $^{\rm mg}/_{\rm mg}$

Biodegradation

The substance is readily biodegradable.

Process of degradability

Process	Degradation rate	Time
biotic/abiotic	94 %	d
oxygen depletion	69 %	5 d
oxygen depletion	84 %	10 d
oxygen depletion	97 %	20 d

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

Australia (en) Page 9 / 14



acc. to Safe Work Australia - Code of Practice



Ethanol ROTISOLV® HPLC Gradient Grade

article number: P076

n-octanol/water (log KOW)	-0.31 (Exp. (TOXNET))
BOD5/COD	0.62110553

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of \geq 0,1%.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H3 Flammable liquids

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number

UN RTDG	UN 1170
IMDG-Code	UN 1170
ICAO-TI	UN 1170

14.2 UN proper shipping name

UN RTDG	ETHANOL
IMDG-Code	FTHANOL

Australia (en) Page 10 / 14

acc. to Safe Work Australia - Code of Practice

Ethanol ROTISOLV® HPLC Gradient Grade

article number: P076



	ICAO-TI	Ethanol
14.3	Transport hazard class(es)	
	UN RTDG	3
	IMDG-Code	3
	ICAO-TI	3
14.4	Packing group	
	UN RTDG	II
	IMDG-Code	II
	ICAO-TI	II
14.5	Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport informationNational regulationsAdditional information(UN RTDG)

UN number 1170
Class 3
Packing group II
Danger label(s) 3



Special provisions (SP)

144
UN RTDG

Excepted quantities (EQ)

E2
UN RTDG

Limited quantities (LQ)

1 L
UN RTDG

Emergency Action Code 2YE

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name ETHANOL

Particulars in the shipper's declaration UN1170, ETHANOL, 3, II, 12°C c.c.

Marine pollutant Danger label(s) 3



Special provisions (SP) 144

Australia (en) Page 11 / 14

acc. to Safe Work Australia - Code of Practice

Ethanol ROTISOLV® HPLC Gradient Grade

article number: P076

Excepted quantities (EQ) E2

Limited quantities (LQ) 1 L

EmS F-E, S-D

Stowage category A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Ethanol

Particulars in the shipper's declaration UN1170, Ethanol, 3, II

Danger label(s) 3



Special provisions (SP) A3, A58, A180

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

Substance is listed.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed

Australia (en) Page 12 / 14



acc. to Safe Work Australia - Code of Practice

Ethanol ROTISOLV® HPLC Gradient Grade

article number: P076



Country	Inventory	Status
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

Legend

AIIC
Australian Inventory of Industrial Chemicals
CICR
CCLENCS
Chemical Inventory and Control Regulation
List of Existing and New Chemical Substances (CSCL-ENCS)
DSL
Domestic Substances List (DSL)
ECSI
ECSI
ECSU
Inventory of Existing Chemical Substances Produced or Imported in China
INSQ
National Inventory of Chemical Substances
Korea Existing Chemicals Inventory

NCI National Chemical Inventory
NZIOC New Zealand Inventory of Chemicals
PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg. REACH registered substances

Taiwan Chemical Substance Inventory

Toxic Substance Control Act

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
15.1		National inventories: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations

Australia (en) Page 13 / 14

acc. to Safe Work Australia - Code of Practice

Ethanol ROTISOLV® HPLC Gradient Grade

article number: P076



Abbr.	Descriptions of used abbreviations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
STEL	Short-term exposure limit
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Australia (en) Page 14 / 14