acc. to Safe Work Australia - Code of Practice



date of compilation: 2018-10-04

Revision: 2024-04-09

Potassium dichromate ≥99,5 %, p.a., ACS, ISO

article number: **P744** Version: **GHS 5.0 en** Replaces version of: 2021-12-20 Version: (GHS 4)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Identification of the substance

Article number

CAS number

Potassium dichromate ≥99,5 %, p.a., ACS, ISO

P744

7778-50-9

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Uses advised against:

Laboratory chemical Laboratory and analytical use

Do not use for squirting or spraying. Do not use for products which come into direct contact with the skin. Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household). Food, drink and animal feedingstuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data Department Health, Safety and Environment sheet:

e-mail (competent person):

sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

acc. to Safe Work Australia - Code of Practice

Potassium dichromate ≥99,5 %, p.a., ACS, ISO



article number: P744

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.14	Oxidising solid	2	Ox. Sol. 2	H272
3.10	Acute toxicity (oral)	3	Acute Tox. 3	H301
3.1D	Acute toxicity (dermal)	4	Acute Tox. 4	H312
3.1I	Acute toxicity (inhal.)	2	Acute Tox. 2	H330
3.2	Skin corrosion/irritation	1B	Skin Corr. 1B	H314
3.3	Serious eye damage/eye irritation	1	Eye Dam. 1	H318
3.4R	Respiratory sensitisation	1	Resp. Sens. 1	H334
3.4S	Skin sensitisation	1	Skin Sens. 1	H317
3.5	Germ cell mutagenicity	1B	Muta. 1B	H340
3.6	Carcinogenicity	1B	Carc. 1B	H350
3.7	Reproductive toxicity	1B	Repr. 1B	H360FD
3.8R	Specific target organ toxicity - single exposure (respirat- ory tract irritation)	3	STOT SE 3	H335
3.9	Specific target organ toxicity - repeated exposure	1	STOT RE 1	H372

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. Delayed or immediate effects can be expected after short or long-term exposure.

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS03, GHS05, GHS06, GHS08



Hazard statements

H272 H301	May intensify fire; oxidiser Toxic if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H330	Fatal if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H340	May cause genetic defects
H350	May cause cancer
H360FD	May damage fertility. May damage the unborn child
H372	Causes damage to organs through prolonged or repeated exposure

acc. to Safe Work Australia - Code of Practice

Potassium dichromate ≥99,5 %, p.a., ACS, ISO



article number: P744

Precautionary statements

Precautionary statements - prevention

P210	Keep away from heat/sparks/open flames/hot surfaces No smoking
P260 P280	Do not breathe dusts or mists Wear protective gloves/protective clothing
Precautionary sta	tements - response
P301+P310 P302+P352 P303+P361+P353	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician IF ON SKIN: Wash with plenty of soap and water IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin
P304+P340	with water or shower IF INHALED: Remove victim to fresh air and keep at rest in a position comfort-
	able for breathing
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

P370+P378

Precautionary statements - storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed

For professional users only

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\ge 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance Molecular formula Molar mass CAS No Potassium dichromate K₂Cr₂O₇ 294.2 ^g/_{mol} 7778-50-9

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off immediately all contaminated clothing. Self-protection of the first aider.

Following inhalation

Call a physician immediately. If breathing is irregular or stopped, administer artificial respiration.

acc. to Safe Work Australia - Code of Practice

Potassium dichromate ≥99,5 %, p.a., ACS, ISO



article number: P744

Following skin contact

After contact with skin, wash immediately with plenty of water. Immediate medical treatment required because corrosive injuries that are not treated are hard to cure. In case of skin reactions, consult a physician.

Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

Following ingestion

Rinse mouth immediately and drink plenty of water. If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects). In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

4.2 Most important symptoms and effects, both acute and delayed

Irritation, Corrosion, Cough, Cough, Asthmatic complaints, Dyspnoea, Allergic reactions, Risk of serious damage to eyes, Risk of blindness, Following ingestion: Gastric perforation, Gastrointestinal complaints, Diarrhoea, Spasms, Cardiac arrhythmias, Unconsciousness, Methaemoglobinaemia

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water, foam, alcohol resistant foam, dry extinguishing powder, ABC-powder

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Oxidising property. Non-combustible.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus. Wear full chemical protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe dust.

acc. to Safe Work Australia - Code of Practice

Potassium dichromate ≥99,5 %, p.a., ACS, ISO



article number: P744

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains. Take up mechanically.

Advice on how to clean up a spill

Take up mechanically. Control of dust.

Other information relating to spills and releases

Place in appropriate containers for disposal.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use extractor hood (laboratory). Handle and open container with care. Provision of sufficient ventilation. Avoid exposure. Avoid dust formation. Clear contaminated areas thoroughly.

Measures to prevent fire as well as aerosol and dust generation

Removal of dust deposits. Keep away from combustible material.

Advice on general occupational hygiene

When using do not eat or drink. Thorough skin-cleansing after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Store in a dry place. Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage. Keep/store away from clothing/combustible materials. Take any precaution to avoid mixing with combustibles.

Consideration of other advice:

Store locked up.

Ventilation requirements

Keep any substance that emits harmful vapours or gases in a place that allows these to be permanently extracted. Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

acc. to Safe Work Australia - Code of Practice

® §ROTH

Potassium dichromate ≥99,5 %, p.a., ACS, ISO

article number: P744

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Identifi- er	TWA [mg/ m³]	STEL [mg/ m³]	Ceil- ing-C [mg/ m ³]	Nota- tion	Source
AU	nuisance dusts		WES	10			i	WES

Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur
Inhalable fraction
STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8

VA lime-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Environmental values

Relevant	Relevant PNECs and other threshold levels					
End- point	Threshold level	Organism	Environmental com- partment	Exposure time		
PNEC	0 ^{mg} /I	aquatic organisms	freshwater	short-term (single instance)		
PNEC	0.21 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)		
PNEC	0.15 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)		
PNEC	0.15 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)		
PNEC	0.035 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)		

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection. Wear face protection.

Skin protection



acc. to Safe Work Australia - Code of Practice

Potassium dichromate ≥99,5 %, p.a., ACS, ISO



article number: **P744**

hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

NBR (Nitrile rubber)

material thickness

>0,11 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection



Respiratory protection necessary at: Dust formation. Particulate filter device (EN 143). P3 (filters at least 99,95 % of airborne particles, colour code: White).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	solid
Form	crystalline
Colour	orange
Odour	odourless
Melting point/freezing point	398 °C (ECHA)
Boiling point or initial boiling point and boiling range	not determined
Flammability	non-combustible
Lower and upper explosion limit	not determined
Flash point	not applicable
Auto-ignition temperature	not determined
Decomposition temperature	>400 °C

acc. to Safe Work Australia - Code of Practice

article number: P744

Potassium dichromate ≥99,5 %, p.a., ACS, ISO



	pH (value)	3.5 – 3.6 (in aqueous solution: 100 ^g / _l , 20 °C)
	Kinematic viscosity	not relevant
	Solubility(ies)	
	Water solubility	115 ^g / _l (ECHA)
	Partition coefficient	
	Partition coefficient n-octanol/water (log value):	not relevant (inorganic)
	Vapour pressure	not determined
	Density and/or relative density	
	Density	2.68 ^g / _{cm³} at 20 °C
	Relative vapour density	Information on this property is not available.
	Bulk density	~1,250 ^{kg} / _{m³}
	Particle characteristics	No data available.
	Other safety parameters	
	Oxidising properties	oxidiser
9.2	Other information	
	Information with regard to physical hazard classes:	There is no additional information.
	Other safety characteristics:	There is no additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Oxidising property.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Danger of explosion: Magnesium, Iron, Ammonium nitrate, Boron, Hydrazine, Reducing agents, Sulphuric acid, Acetic anhydride, **Exothermic reaction with:** Strong alkali, Fluorine, **Release of an acute toxic gas:** Metal powder, Acetone

10.4 Conditions to avoid

Keep away from heat. Decompositon takes place from temperatures above: >400 °C.

10.5 Incompatible materials

There is no additional information.

acc. to Safe Work Australia - Code of Practice

Potassium dichromate ≥99,5 %, p.a., ACS, ISO



article number: P744

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Toxic if swallowed. Harmful in contact with skin. Fatal if inhaled.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	67 ^{mg} / _{kg}	rat		ECHA
inhalation: dust/ mist	LC50	83 ^{mg} / _{m³} /4h	rat		ECHA
dermal	LD50	<2,000 ^{mg} / _{kg}	rabbit		ECHA

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Germ cell mutagenicity

May cause genetic defects.

Carcinogenicity

May cause cancer.

Reproductive toxicity

May damage the unborn child. May damage fertility.

Specific target organ toxicity - single exposure

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

vomiting, gastrointestinal complaints, diarrhoea, Spasms, If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects)

• If in eyes

causes burns, Causes serious eye damage, risk of blindness

acc. to Safe Work Australia - Code of Practice

Potassium dichromate ≥99,5 %, p.a., ACS, ISO



article number: P744

If inhaled

Irritation to respiratory tract, May produce an allergic reaction, cough, Dyspnoea

• If on skin

causes severe burns, causes poorly healing wounds, May produce an allergic reaction, pruritis, localised redness

Other information

Other adverse effects: Liver and kidney damage, Cardiac arrhythmias, Methaemoglobinaemia, Unconsciousness

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\ge 0,1\%$.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Data are not available.

- **12.3 Bioaccumulative potential** Data are not available.
- **12.4 Mobility in soil** Data are not available.
- **12.5 Results of PBT and vPvB assessment** Data are not available.
- 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\ge 0,1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

acc. to Safe Work Australia - Code of Practice

Potassium dichromate ≥99,5 %, p.a., ACS, ISO



article number: P744

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H6.1Poisonous (Acute)H11Toxic (Delayed or chronic)

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1	UN number	
	UN RTDG	UN 3086
	IMDG-Code	UN 3086
	ICAO-TI	UN 3086
14.2	UN proper shipping name	
	UN RTDG	TOXIC SOLID, OXIDIZING, N.O.S.
	IMDG-Code	TOXIC SOLID, OXIDIZING, N.O.S.
	ICAO-TI	Toxic solid, oxidizing, n.o.s.
	Technical name	Potassium dichromate
14.3	Transport hazard class(es)	
	UN RTDG	6.1 (5.1)
	IMDG-Code	6.1 (5.1)
	ICAO-TI	6.1 (5.1)
14.4	Packing group	
	UN RTDG	П
	IMDG-Code	II
	ICAO-TI	П
14.5	Environmental hazards	hazardous to the aquatic environment
14.6	Special precautions for user There is no additional information.	
14.7	Transport in bulk according to IMO instruments	
	The cargo is not intended to be carried in bulk.	

14.8 Information for each of the UN Model Regulations

acc. to Safe Work Australia - Code of Practice

Potassium dichromate ≥99,5 %, p.a., ACS, ISO



article number: **P744**

Transport informationNational regulation	ransport informationNational regulationsAdditional information(UN RTDG)			
UN number	3086			
Class	6.1			
Subsidiary risk(s)	5.1			
Environmental hazards	Yes Hazardous to the aquatic environment			
Packing group	П			
Danger label(s)	6.1+5.1 Fish and tree			
Special provisions (SP)	274 UN RTDG			
Excepted quantities (EQ)	E4 UN RTDG			
Limited quantities (LQ)	500 g UN RTDG			
Emergency Action Code	2W			
International Maritime Dangerous Goods (Code (IMDG) - Additional information			
Proper shipping name	TOXIC SOLID, OXIDIZING, N.O.S.			
Particulars in the shipper's declaration	UN3086, TOXIC SOLID, OXIDIZING, N.O.S., (Po- tassium dichromate), 6.1 (5.1), II, MARINE POL- LUTANT			
Marine pollutant	Yes (hazardous to the aquatic environment)			
Danger label(s)	6.1+5.1, "Fish and tree"			
Special provisions (SP)	274			
Excepted quantities (EQ)	E4			
Limited quantities (LQ)	500 g			
EmS	F-A, S-Q			
Stowage category	C			
International Civil Aviation Organization (I	CAO-IATA/DGR) - Additional information			
Proper shipping name	Toxic solid, oxidizing, n.o.s.			
Particulars in the shipper's declaration	UN3086, Toxic solid, oxidizing, n.o.s., (Potassium dichromate), 6.1 (5.1), II			
Environmental hazards	Yes (hazardous to the aquatic environment)			
Danger label(s)	6.1+5.1			

acc. to Safe Work Australia - Code of Practice



Potassium dichromate ≥99,5 %, p.a., ACS, ISO

article number: P744

Special provisions (SP)	A5
Excepted quantities (EQ)	E4
Limited quantities (LQ)	1 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

Substance is listed.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL ECSI	Domestic Substances List (DSL) EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NCI	National Chemical Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

acc. to Safe Work Australia - Code of Practice

® §ROTH

Potassium dichromate ≥99,5 %, p.a., ACS, ISO

article number: **P744**

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
14.8		Emergency Action Code: 2W	yes
15.1		National inventories: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
NLP	No-Longer Polymer
РВТ	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
STEL	Short-term exposure limit
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative

acc. to Safe Work Australia - Code of Practice

Potassium dichromate ≥99,5 %, p.a., ACS, ISO



article number: **P744**

Abbr.	Descriptions of used abbreviations
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H272	May intensify fire; oxidiser.
H301	Toxic if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H340	May cause genetic defects.
H350	May cause cancer.
H360FD	May damage fertility. May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.