acc. to Safe Work Australia - Code of Practice

## Methyl red indicator solution 0,1 %, in ethanol

article number: T121 Version: GHS 2.0 en Revision: 2021-08-03

Replaces version of: 2019-06-21

Version: (GHS 1)

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### **Product identifier** 1.1

Identification of the substance Methyl red indicator solution 0,1 %, in ethanol

Article number T121

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for products which come into contact

with foodstuffs. Do not use for private purposes

(household).

#### 1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

**Telephone:**+49 (0) 721 - 56 06 0 Telefax: +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

e-mail (competent person): sicherheit@carlroth.de

#### 1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

## **SECTION 2: Hazards identification**

#### Classification of the substance or mixture 2.1

## Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.3	Serious eye damage/eye irritation	2A	Eye Irrit. 2A	H319

For full text of abbreviations: see SECTION 16

## The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

Australia (en) Page 1 / 16



date of compilation: 2019-06-21

acc. to Safe Work Australia - Code of Practice

## Methyl red indicator solution 0,1 %, in ethanol

article number: T121



Labelling

Signal word Danger

**Pictograms** 

GHS02, GHS07



## **Hazard statements**

H225 Highly flammable liquid and vapour H319 Causes serious eye irritation

## **Precautionary statements**

## **Precautionary statements - prevention**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P233 Keep container tightly closed

## **Precautionary statements - response**

P337+P313 If eye irritation persists: Get medical advice/attention

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

### Precautionary statements - storage

P403+P235 Store in a well-ventilated place. Keep cool

### **Precautionary statements - disposal**

P501 Dispose of contents/container to industrial combustion plant

## 2.3 Other hazards

### Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

# **SECTION 3: Composition/information on ingredients**

### 3.1 Substances

not relevant (mixture)

### 3.2 Mixtures

### **Description of the mixture**

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Ethanol	CAS No 64-17-5	> 95	Flam. Liq. 2 / H225 Eye Irrit. 2A / H319		IARC: 1

Notes

IARC: 1: IARC group 1: carcinogenic to humans (International Agency for Research on Cancer)

For full text of abbreviations: see SECTION 16

Australia (en) Page 2 / 16



acc. to Safe Work Australia - Code of Practice

## Methyl red indicator solution 0,1 %, in ethanol

article number: T121



## **SECTION 4: First aid measures**

### 4.1 Description of first aid measures



### **General notes**

Take off contaminated clothing.

## Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

## Following skin contact

Rinse skin with water/shower. In all cases of doubt, or when symptoms persist, seek medical advice.

## Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

## Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

## 4.2 Most important symptoms and effects, both acute and delayed

Irritation, Nausea, Vomiting, Abdominal pain, Breathing difficulties, Vertigo, Drowsiness, Narcosis, Loss of righting reflex, and ataxia

### 4.3 Indication of any immediate medical attention and special treatment needed

none

# **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media



## Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO<sub>2</sub>)

### Unsuitable extinguishing media

water jet

## 5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours may form explosive mixtures with air.

### **Hazardous combustion products**

In case of fire may be liberated: Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), May produce toxic fumes of carbon monoxide if burning.

Australia (en) Page 3 / 16

acc. to Safe Work Australia - Code of Practice

## Methyl red indicator solution 0,1 %, in ethanol

article number: T121



## 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures



## For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

## 6.2 Environmental precautions

Keep away from drains, surface and ground water. Danger of explosion.

## 6.3 Methods and material for containment and cleaning up

## Advice on how to contain a spill

Covering of drains.

## Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

# **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Provision of sufficient ventilation.

## Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

## Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

Australia (en) Page 4 / 16

acc. to Safe Work Australia - Code of Practice

## Methyl red indicator solution 0,1 %, in ethanol

article number: T121



#### 7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight.

## **Incompatible substances or mixtures**

Observe hints for combined storage.

### Consideration of other advice:

Ground/bond container and receiving equipment.

## **Ventilation requirements**

Use local and general ventilation.

## Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

#### 7.3 Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

#### 8.1 **Control parameters**

### **National limit values**

## Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
AU	ethyl alcohol (ethan- ol)	64-17-5	WES	1,00 0	1,880						WES

### Notation

Ceiling-C STEL

Ceiling value is a limit value above which exposure should not occur Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

**TWA** Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8

hours time-weighted average (unless otherwise specified)

#### Relevant DNELs of components of the mixture **CAS No Used** in **Exposure time** Name of sub-End-**Threshol Protection** stance point d level goal, route of exposure **Ethanol** 64-17-5 DNEL 1,900 mg/ human, inhalatworker (industry) acute - systemic $m^3$ effects Ethanol 64-17-5 **DNEL** 343 mg/kg human, dermal worker (industry) chronic - systemic effects Ethanol 64-17-5 DNEL 950 mg/m<sup>3</sup> human, inhalatworker (industry) chronic - systemic effects

Australia (en) Page 5 / 16

acc. to Safe Work Australia - Code of Practice

## Methyl red indicator solution 0,1 %, in ethanol

article number: T121



Relevant PNECs	Relevant PNECs of components of the mixture										
Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time					
Ethanol	64-17-5	PNEC	0.79 <sup>mg</sup> / <sub>cm³</sub>	unknown	marine water	intermittent re- lease					
Ethanol	64-17-5	PNEC	2.75 <sup>mg</sup> / <sub>cm³</sub>	unknown	air	intermittent re- lease					
Ethanol	64-17-5	PNEC	3.6 <sup>mg</sup> / <sub>cm³</sub>	unknown	freshwater sedi- ment	intermittent re- lease					
Ethanol	64-17-5	PNEC	580 <sup>mg</sup> / <sub>cm³</sub>	unknown	sewage treatment plant (STP)	intermittent re- lease					
Ethanol	64-17-5	PNEC	0.63 <sup>mg</sup> / <sub>cm³</sub>	unknown	soil	intermittent re- lease					
Ethanol	64-17-5	PNEC	0.96 <sup>mg</sup> / <sub>cm³</sub>	unknown	freshwater	intermittent re- lease					

## 8.2 Exposure controls

Individual protection measures (personal protective equipment)

## **Eye/face protection**





Use safety goggle with side protection.

### Skin protection





### hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

### type of material

Butyl caoutchouc (butyl rubber)

material thickness

0,7mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

Australia (en) Page 6 / 16

acc. to Safe Work Australia - Code of Practice

## Methyl red indicator solution 0,1 %, in ethanol

article number: T121



Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

## **Respiratory protection**





Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

## **Environmental exposure controls**

Keep away from drains, surface and ground water.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state liquid
Colour red

Odour like: - alcohol

Melting point/freezing point -114 °C
Boiling point or initial boiling point and boiling 78 °C

range

Flammability flammable liquid in accordance with GHS criteria

Lower and upper explosion limit 3.1 vol% - 27.7 vol%

Flash point 13 °C Auto-ignition temperature 455 °C

Decomposition temperature not relevant pH (value) not determined Kinematic viscosity not determined

Solubility(ies)

Water solubility miscible in any proportion

Partition coefficient

Partition coefficient n-octanol/water (log value): this information is not available

Vapour pressure 59 hPa at 20 °C

Density  $0.79 \, ^{9}/_{\text{cm}^3}$  at 20 °C

Relative vapour density information on this property is not available

Australia (en) Page 7 / 16



acc. to Safe Work Australia - Code of Practice

## Methyl red indicator solution 0,1 %, in ethanol

article number: T121



Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard

classes:

Flammable liquids

Sustained combustibility yes, sustained combustion was observed

Other safety characteristics:

Miscibility completely miscible with water

## **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

The mixture contains reactive substance(s). Risk of ignition. Vapours may form explosive mixtures with air.

### If heated

Risk of ignition.

### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

## 10.3 Possibility of hazardous reactions

**Violent reaction with:** strong oxidiser, Alkali metals, Alkaline earth metal, Acetic anhydride, Peroxides, Phosphorus oxides (e.g. P2O5), Nitric acid, Nitrate, Perchlorates, => Explosive properties

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5 Incompatible materials

There is no additional information.

## 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

# SECTION 11: Toxicological information

## 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

## **Classification procedure**

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).


Classification acc. to GHS

Australia (en) Page 8 / 16

acc. to Safe Work Australia - Code of Practice

## Methyl red indicator solution 0,1 %, in ethanol

article number: T121



Shall not be classified as acutely toxic.

# Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Ethanol	64-17-5	inhalation: va- pour	LC50	95.6 <sup>mg</sup> / <sub>l</sub> /4h	rat
Ethanol	64-17-5	oral	LD50	7,060 <sup>mg</sup> / <sub>kg</sub>	rat

### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

## Serious eye damage/eye irritation

Causes serious eye irritation.

## Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

## Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

## Carcinogenicity

Shall not be classified as carcinogenic.

## Reproductive toxicity

Shall not be classified as a reproductive toxicant.

## Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

## Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

### **Aspiration hazard**

Shall not be classified as presenting an aspiration hazard.

## Symptoms related to the physical, chemical and toxicological characteristics

### If swallowed

vomiting, abdominal pain, nausea, Causes damage to liver through prolonged or repeated exposure if swallowed, loss of righting reflex, and ataxia

## • If in eyes

Causes serious eye irritation

## • If inhaled

drowsiness, narcosis, vertigo, breathing difficulties, Inebriation

### • If on skin

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation)

## Other information

none

Australia (en) Page 9 / 16



acc. to Safe Work Australia - Code of Practice

## Methyl red indicator solution 0,1 %, in ethanol

article number: T121



None of the ingredients are listed.

# **SECTION 12: Ecological information**

## 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute) of components of the mixture								
Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time			
Ethanol	64-17-5	LC50	8,140 <sup>mg</sup> / <sub>l</sub>	orfe (Leuciscus idus)	96 h			
Ethanol	64-17-5	EC50	9,000 – 14,000 <sup>mg</sup> / <sub>l</sub>	daphnia magna	48 h			

## **Biodegradation**

Data are not available.

## 12.2 Process of degradability

Degradability of components of the mixture							
Name of substance	CAS No	Process	Degrada- tion rate	Time	Method	Source	
Ethanol	64-17-5	biotic/abiotic	94 %	d			

## 12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture							
Name of substance	CAS No	BCF	Log KOW	BOD5/COD			
Ethanol	64-17-5		-0.31				

## 12.4 Mobility in soil

Data are not available.

## 12.5 Results of PBT and vPvB assessment

Data are not available.

## 12.6 Endocrine disrupting properties

None of the ingredients are listed.

### 12.7 Other adverse effects

Data are not available.

Australia (en) Page 10 / 16



acc. to Safe Work Australia - Code of Practice

## Methyl red indicator solution 0,1 %, in ethanol

article number: T121



## **SECTION 13: Disposal considerations**

### Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

## Sewage disposal-relevant information

Do not empty into drains.

## Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

## Relevant provisions relating to waste(Basel Convention)

## Properties of waste which render it hazardous

**H3** Flammable liquids

#### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

## **SECTION 14: Transport information**

### 14.1 UN number

	UN RTDG	UN 1170
	IMDG-Code	UN 1170
	ICAO-TI	UN 1170
14.2	UN proper shipping name	
	UN RTDG	ETHANOL
	IMDG-Code	ETHANOL
	ICAO-TI	Ethanol
14.3	Transport hazard class(es)	
	UN RTDG	3
	IMDG-Code	3
	ICAO-TI	3
14.4	Packing group	

**UN RTDG** II **IMDG-Code** II ICAO-TI II

14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

gerous goods regulations

Australia (en) Page 11 / 16

acc. to Safe Work Australia - Code of Practice

## Methyl red indicator solution 0,1 %, in ethanol

article number: T121



There is no additional information.

## 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

## 14.8 Information for each of the UN Model Regulations

Transport informationNational regulationsAdditional information(UN RTDG)

UN number 1170
Class 3
Packing group II
Danger label(s) 3

Special provisions (SP) 144

**UN RTDG** 

Excepted quantities (EQ)

UN RTDG

Limited quantities (LQ) 1 L

UN RTDG

## International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name ETHANOL

Particulars in the shipper's declaration UN1170, ETHANOL, 3, II, 13°C c.c.

Marine pollutant Danger label(s) 3



Special provisions (SP) 144
Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

EmS F-E, S-D

Stowage category A

## International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Ethanol

Particulars in the shipper's declaration UN1170, Ethanol, 3, II

Danger label(s) 3



Special provisions (SP) A3, A58, A180

Excepted quantities (EQ) E2

Australia (en) Page 12 / 16



acc. to Safe Work Australia - Code of Practice

## Methyl red indicator solution 0,1 %, in ethanol

article number: T121

Limited quantities (LQ)



## 1 L

## **SECTION 15: Regulatory information**

## Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

## National regulations(Australia)

## Australian Inventory of Chemical Substances(AICS)

All ingredients are listed or exempt from listing.

## **National inventories**

Country	Inventory	Status
AU	AICS	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

AICS CICR Australian Inventory of Chemical Substances

Chemical Inventory and Control Regulation List of Existing and New Chemical Substances (CSCL-ENCS) CSCL-ENCS DSL ECSI IECSC

Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China National Inventory of Chemical Substances

Korea Existing Chemicals Inventory New Zealand Inventory of Chemicals Philippine Inventory of Chemicals and Chemical Substances (PICCS)

REACH Reg.

REACH registered substances Taiwan Chemical Substance Inventory Toxic Substance Control Act

TSCA

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

Australia (en) Page 13 / 16

acc. to Safe Work Australia - Code of Practice

## Methyl red indicator solution 0,1 %, in ethanol

article number: T121



## **SECTION 16: Other information**

## Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals

("Purple book").

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1		The most important adverse physicochemical, human health and environmental effects: The product is combustible and can be ignited by potential ignition sources.	yes
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Danger		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes

## **Abbreviations and acronyms**

aboreviations and acronyms		
Abbr.	Descriptions of used abbreviations	
BCF	Bioconcentration factor	
BOD	Biochemical Oxygen Demand	
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)	
Ceiling-C	Ceiling value	
COD	Chemical oxygen demand	
DGR	Dangerous Goods Regulations (see IATA/DGR)	
DNEL	Derived No-Effect Level	
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval	
EINECS	European Inventory of Existing Commercial Chemical Substances	
ELINCS	European List of Notified Chemical Substances	
EmS	Emergency Schedule	
Eye Dam.	Seriously damaging to the eye	

Australia (en) Page 14 / 16

acc. to Safe Work Australia - Code of Practice

## Methyl red indicator solution 0,1 %, in ethanol

article number: T121



Abbr.	Descriptions of used abbreviations
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
log KOW	n-Octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
STEL	Short-term exposure limit
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne conatminants

## Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

## **Classification procedure**

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Australia (en) Page 15 / 16

acc. to Safe Work Australia - Code of Practice

## Methyl red indicator solution 0,1 %, in ethanol

article number: **T121** 



Code	Text
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Australia (en) Page 16 / 16