2-Propanol ROTISOLV® ≥99,8 %, UV/IR-Grade

acc. to Regulation (EC) No. 1907/2006 (REACH)

date of compilation: 2015-11-27 Revision: 2024-03-02

article number: **T910** Version: **6.0 en** Replaces version of: 2022-12-20 Version: (5)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Identification of the substance	2-Propanol ROTISOLV® ≥99,8 %, UV/IR-Grade			
Article number	Т910			
Index No (GB CLP)	603-117-00-0			
EC number	200-661-7			
CAS number	67-63-0			

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Uses advised against:

Do not use for private purposes (household). Food, drink and animal feedingstuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data Department Health, Safety and Environment sheet:

e-mail (competent person):

sicherheit@carlroth.de

Laboratory chemical

Laboratory and analytical use

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

acc. to Regulation (EC) No. 1907/2006 (REACH)

2-Propanol ROTISOLV® ≥99,8 %, UV/IR-Grade



article number: T910

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS02, GHS07



Hazard statements

H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P233 Keep container tightly closed

Precautionary statements - response

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\ge 0,1\%$.

acc. to Regulation (EC) No. 1907/2006 (REACH)

2-Propanol ROTISOLV® ≥99,8 %, UV/IR-Grade



article number: T910

3.1

SECTION 3: Composition/information on ingredients

Substances	
Name of substance	2-Propanol
Molecular formula	C_3H_8O
Molar mass	60,1 ^g / _{mol}
CAS No	67-63-0
EC No	200-661-7
Index No (GB CLP)	603-117-00-0

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In all cases of doubt, or when symptoms persist, seek medical advice.

Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

- **4.2 Most important symptoms and effects, both acute and delayed** Vomiting, Irritation, Dizziness, Drowsiness, Narcosis
- **4.3 Indication of any immediate medical attention and special treatment needed** none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

acc. to Regulation (EC) No. 1907/2006 (REACH)

2-Propanol ROTISOLV® ≥99,8 %, UV/IR-Grade



article number: **T910**

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapourair mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

acc. to Regulation (EC) No. 1907/2006 (REACH)

2-Propanol ROTISOLV® ≥99,8 %, UV/IR-Grade



article number: T910

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

Conditions for safe storage, including any incompatibilities 7.2

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
GB	propan-2-ol	67-63-0	WEL	400	999	500	1.250				EH40/ 2005

Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur

Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 STEL

TWA hours time-weighted average (unless otherwise specified)

acc. to Regulation (EC) No. 1907/2006 (REACH)

2-Propanol ROTISOLV® ≥99,8 %, UV/IR-Grade



article number: T910

Human health	Human health values										
Relevant DNELs and other threshold levels											
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time							
DNEL	500 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects							
DNEL	1.000 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects							
DNEL	888 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic effects							

Environmental values

Relevant	Relevant PNECs and other threshold levels										
End- point	Threshold level	Organism	Environmental com- partment	Exposure time							
PNEC	140,9 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)							
PNEC	140,9 ^{mg} / _l	140,9 ^{mg} / _l aquatic organisms marine water	marine water	short-term (single instance)							
PNEC	2.251 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)							
PNEC	552 ^{mg} / _{kg}	52 ^{mg} / _{kg} aquatic organisms freshwater s		short-term (single instance)							
PNEC	552 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)							
PNEC	28 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)							

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a consider-able reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

acc. to Regulation (EC) No. 1907/2006 (REACH)

2-Propanol ROTISOLV® ≥99,8 %, UV/IR-Grade



article number: T910

• type of material

NBR (Nitrile rubber)

material thickness

0.4 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Flame-retardant protective clothing.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > $65 \circ$ C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	like: - alcohol
Odour threshold	1 – 196 ppm
Melting point/freezing point	-89 °C
Boiling point or initial boiling point and boiling range	82 – 83 °C at 1.013 hPa
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	2 vol% (LEL) - 13,4 vol% (UEL)
Flash point	12 °C (c.c.)
Auto-ignition temperature	425 °C (DIN 51794)
Decomposition temperature	not relevant
pH (value)	7 (20 °C)
Kinematic viscosity	2,785 ^{mm²} / _s at 20 °C
Dynamic viscosity	2,2 mPa s at 20 °C
Solubility(ies)	
Water solubility	miscible in any proportion

acc. to Regulation (EC) No. 1907/2006 (REACH)

2-Propanol ROTISOLV® ≥99,8 %, UV/IR-Grade



article number: **T910**

Partition coefficient	
Partition coefficient n-octanol/water (log value):	0,05
Vapour pressure	43 hPa at 20 °C
Density and/or relative density	
Density	0,79 ^g / _{cm³} at 20 °C
Relative vapour density	2,07 (air = 1)
Particle characteristics	not relevant (liquid)
Other safety parameters	
Oxidising properties	none
Other information	
Information with regard to physical hazard classes:	There is no additional information.
Other safety characteristics:	
Miscibility	completely miscible with water

SECTION 10: Stability and reactivity

10.1 Reactivity

9.2

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air. May form explosive peroxides.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Exothermic reaction with: strong oxidiser, Iron, Nitric acid, Strong acid, Aldehydes, Aluminium, Amines, **Danger of explosion:** Chlorates, Nitro compound, Hydrogen peroxide, Phosgene

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

plastic and rubber

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5. Peroxides.

acc. to Regulation (EC) No. 1907/2006 (REACH)

2-Propanol ROTISOLV® ≥99,8 %, UV/IR-Grade



article number: **T910**

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4. May be harmful if inhaled.

Acute toxicity									
Exposure route	Endpoint	Value	Species	Method	Source				
inhalation: vapour	LC50	4h/ _ا /4h	rat		OECD-403				
oral	LD50	5.045 ^{mg} / _{kg}	rat		RTECS				
dermal	LD50	12.800 ^{mg} / _{kg}	rabbit		RTECS				

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

vomiting, nausea

• If in eyes

Causes serious eye irritation

• If inhaled

dizziness, fatigue, narcosis

acc. to Regulation (EC) No. 1907/2006 (REACH)

2-Propanol ROTISOLV® ≥99,8 %, UV/IR-Grade



article number: T910

• If on skin

repeated exposure may cause skin dryness or cracking

Other information

Other adverse effects: Headache, Vertigo, Dyspnoea

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\ge 0,1\%$.

11.3 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)								
Endpoint	Value	Species	Source	Exposure time				
LC50	10.000 ^{mg} / _l	fish	ECHA	96 h				

12.2 Persistence and degradability

Theoretical Oxygen Demand: 2,396 ^{mg}/_{mg} Theoretical Carbon Dioxide: 2,197 ^{mg}/_{mg}

Biodegradation

The substance is readily biodegradable.

Process of degradability		
Process	Degradation rate	Time
biotic/abiotic	95 %	21 d
oxygen depletion	53 %	5 d

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	0,05
---------------------------	------

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\ge 0,1\%$.

12.7 Other adverse effects

Data are not available.

acc. to Regulation (EC) No. 1907/2006 (REACH)

2-Propanol ROTISOLV® ≥99,8 %, UV/IR-Grade



article number: **T910**

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Properties of waste which render it hazardous

- HP 3 flammable
- HP 4 irritant skin irritation and eye damage

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number or ID number

	ADRRID	UN 1219
	IMDG-Code	UN 1219
	ICAO-TI	UN 1219
14.2	UN proper shipping name	
	ADRRID	ISOPROPANOL
	IMDG-Code	ISOPROPANOL
	ICAO-TI	Isopropanol
14.3	Transport hazard class(es)	
	ADRRID	3
	IMDG-Code	3
	ICAO-TI	3
14.4	Packing group	
	ADRRID	II
	IMDG-Code	II
	ICAO-TI	II

acc. to Regulation (EC) No. 1907/2006 (REACH)

® Roth

2-Propanol ROTISOLV® ≥99,8 %, UV/IR-Grade

article number: **T910**

- **14.5** Environmental hazardsnon-environmentally hazardous acc. to the dan-
gerous goods regulations
- 14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Agreement concerning the International C information	Carriage of Dangerous Goods by Road (ADR)Additional
Proper shipping name	ISOPROPANOL
Particulars in the transport document	LIN1219 ISOPROPANOL 3 II (D/F)

Particulars in the transport document	UN1219, ISOPROPANOL, 3, II, (D/E)
Classification code	F1
Danger label(s)	3
Special provisions (SP)	601
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D/E
Hazard identification No	33
Emergency Action Code	2YE
Regulations concerning the International Carri information	age of Dangerous Goods by Rail (RID)Additional
Regulations concerning the International Carri information Classification code	age of Dangerous Goods by Rail (RID)Additional
information	
information Classification code	F1
information Classification code	F1
information Classification code Danger label(s)	F1 3
information Classification code Danger label(s) Operation Special provisions (SP)	F1 3 601
information Classification code Danger label(s) \checkmark Special provisions (SP) Excepted quantities (EQ)	F1 3 601 E2

acc. to Regulation (EC) No. 1907/2006 (REACH)

2-Propanol ROTISOLV® ≥99,8 %, UV/IR-Grade



article number: **T910**

International Maritime Dangerous Goods	Code (IMDG) - Additional information
Proper shipping name	ISOPROPANOL
Particulars in the shipper's declaration	UN1219, ISOPROPANOL, 3, II, 12°C c.c.
Marine pollutant	-
Danger label(s)	3
Special provisions (SP)	-
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-E, S-D
Stowage category	В
International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information
Proper shipping name	Isopropanol
Particulars in the shipper's declaration	UN1219, Isopropanol, 3, II
Danger label(s)	3
Special provisions (SP)	A180
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Seveso Directive

2012/18/EU (Seveso III)				
Νο	Dangerous substance/hazard categories	categories Qualifying quantity (tonnes) for the application of lower and upper-tier requirements		
P5c	flammable liquids (cat. 2, 3)	5.000 50.000	51)	

Notation

51) Flammable liquids, categories 2 or 3 not covered by P5a and P5b

Deco-Paint Directive

acc. to Regulation (EC) No. 1907/2006 (REACH)

2-Propanol ROTISOLV® ≥99,8 %, UV/IR-Grade



article number: **T910**

VOC content	100 %
VOC content	790 ^g / _l

Industrial Emissions Directive (IED)

VOC content	100 %
VOC content	790 ^g / _l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

Water Framework Directive (WFD)

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
2-Propanol	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment		a)	

Legend

a) Indicative list of the main pollutants

Regulation on the marketing and use of explosives precursors

not listed

Regulation on drug precursors

not listed

Regulation on substances that deplete the ozone layer (ODS)

not listed

Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

Regulation on persistent organic pollutants (POP)

not listed

National regulations(GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list not listed

acc. to Regulation (EC) No. 1907/2006 (REACH)

2-Propanol ROTISOLV® ≥99,8 %, UV/IR-Grade



article number: **T910**

estrictions according to GB REACH, Annex 17			
Dangerous substances with restrictions (GB REACH, Annex 17)			
Name of substance	Name acc. to inventory	CAS No	Νο
2-Propanol	this product meets the criteria for classi- fication in accordance with Regulation No 1272/2008/EC		3
2-Propanol	flammable / pyrophoric		40

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
СА	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
JP	ISHA-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

Legend

AIIC CICR	Australian Inventory of Industrial Chemicals Chemical Inventory and Control Regulation
	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EÌNEĆS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NCI	National Chemical Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance.

acc. to Regulation (EC) No. 1907/2006 (REACH)



2-Propanol ROTISOLV® ≥99,8 %, UV/IR-Grade

article number: **T910**

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
15.1	VOC content: 100 % 790 ^g / _l	VOC content: 100 %	yes
15.1		VOC content: 790 ^g / _l	yes
15.1		National inventories: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations	
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concern- ing the International Carriage of Dangerous Goods by Road)	
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)	
Ceiling-C	Ceiling value	
DGR	Dangerous Goods Regulations (see IATA/DGR)	
DNEL	Derived No-Effect Level	
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identi- fier of substances commercially available within the EU (European Union)	
ED	Endocrine disruptor	
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-li- cence/)	
EINECS	European Inventory of Existing Commercial Chemical Substances	
ELINCS	European List of Notified Chemical Substances	
EmS	Emergency Schedule	
GB CLP	The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/720 (as amended)	
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)	
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions	
IATA	International Air Transport Association	
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)	
ICAO	International Civil Aviation Organization	
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air	
IMDG	International Maritime Dangerous Goods Code	
IMDG-Code	International Maritime Dangerous Goods Code	

acc. to Regulation (EC) No. 1907/2006 (REACH)

® §ROTH

2-Propanol ROTISOLV® ≥99,8 %, UV/IR-Grade

article number: **T910**

Abbr.	Descriptions of used abbreviations	
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008	
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval	
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval	
LEL	Lower explosion limit (LEL)	
NLP	No-Longer Polymer	
PBT	Persistent, Bioaccumulative and Toxic	
PNEC	Predicted No-Effect Concentration	
ppm	Parts per million	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals	
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)	
STEL	Short-term exposure limit	
TWA	Time-weighted average	
UEL	Upper explosion limit (UEL)	
VOC	Volatile Organic Compounds	
vPvB	Very Persistent and very Bioaccumulative	
WEL	Workplace exposure limit	

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.