acc. to Regulation (EC) No. 1907/2006 (REACH)

#### Diisopropyl ether ROTIPURAN® ≥99 %, p.a., stabilized

article number: T919 date of compilation: 2017-03-17 Version: **4.0 en** Revision: 2024-03-04

Replaces version of: 2021-12-15

Version: (3)



## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### **Product identifier** 1.1

Identification of the substance **Diisopropyl ether** ROTIPURAN® ≥99 %, p.a., sta-

bilized

Article number T919

Index No (GB CLP) 603-045-00-X EC number 203-560-6 CAS number 108-20-3

#### Relevant identified uses of the substance or mixture and uses advised against 1.2

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for private purposes (household).

Food, drink and animal feedingstuffs.

#### 1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

**Telephone:**+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data Department Health, Safety and Environment

sheet:

e-mail (competent person): sicherheit@carlroth.de

#### **Emergency telephone number** 1.4

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification acc. to GHS

Section	Hazard class		Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

United Kingdom (en) Page 1 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

# Diisopropyl ether ROTIPURAN® ≥99 %, p.a., stabilized





#### Supplemental hazard information

Code	Supplemental hazard information				
EUH019	may form explosive peroxides				
EUH066	repeated exposure may cause skin dryness or cracking				

For full text of abbreviations: see SECTION 16

#### The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

#### 2.2 Label elements

#### Labelling

Signal word Danger

#### **Pictograms**

GHS02, GHS07



#### **Hazard statements**

H225 Highly flammable liquid and vapour H336 May cause drowsiness or dizziness

#### **Precautionary statements**

#### **Precautionary statements - prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking

P243 Take action to prevent static discharges

#### **Precautionary statements - response**

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing

#### **Precautionary statements - storage**

P403+P233 Store in a well-ventilated place. Keep container tightly closed

#### **Supplemental hazard information**

EUH019 May form explosive peroxides.

EUH066 Repeated exposure may cause skin dryness or cracking.

#### 2.3 Other hazards

#### Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

#### **Endocrine disrupting properties**

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq$  0,1%.

United Kingdom (en) Page 2 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

#### Diisopropyl ether ROTIPURAN® ≥99 %, p.a., stabilized

article number: T919



## **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Name of substance Diisopropyl ether

Molecular formula C<sub>6</sub>H<sub>14</sub>O

Molar mass 102,2 g/<sub>mol</sub>

CAS No 108-20-3

EC No 203-560-6

Index No (GB CLP) 603-045-00-X

#### To stabilise:

Name of substance	Identifier	Wt%
Butylated hydroxytoluene	CAS No 128-37-0	< 0,01
	EC No 204-881-4	

#### **Remarks**

For full text of abbreviations: see SECTION 16

#### **SECTION 4: First aid measures**

## 4.1 Description of first aid measures



#### **General notes**

Take off contaminated clothing.

#### **Following inhalation**

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

#### **Following skin contact**

Rinse skin with water/shower.

## Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

#### **Following ingestion**

Rinse mouth. Call a doctor if you feel unwell.

#### 4.2 Most important symptoms and effects, both acute and delayed

Vertigo, Nausea, Headache, Cough, Dyspnoea, Dizziness, Drowsiness, Narcosis

#### 4.3 Indication of any immediate medical attention and special treatment needed

none

United Kingdom (en) Page 3 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

#### Diisopropyl ether ROTIPURAN® ≥99 %, p.a., stabilized

article number: T919



## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media



#### Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

water jet

#### 5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air

#### **Hazardous combustion products**

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

#### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures



#### For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

#### **6.2** Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

#### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

#### Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

United Kingdom (en) Page 4 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

#### Diisopropyl ether ROTIPURAN® ≥99 %, p.a., stabilized

article number: T919



#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Provision of sufficient ventilation. Use extractor hood (laboratory). Avoid: Aerosol or mist formation.

#### Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed.

#### **Incompatible substances or mixtures**

Observe hints for combined storage.

#### Protect against external exposure, such as

direct light irradiation, contact with air/oxygen

#### Consideration of other advice:

Ground/bond container and receiving equipment.

#### **Ventilation requirements**

Use local and general ventilation.

#### Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

#### 7.3 Specific end use(s)

No information available.

United Kingdom (en) Page 5 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

#### Diisopropyl ether ROTIPURAN® ≥99 %, p.a., stabilized

article number: T919



## SECTION 8: Exposure controls/personal protection

#### **Control parameters** 8.1

#### **National limit values**

#### **Occupational exposure limit values (Workplace Exposure Limits)**

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
GB	diisopropyl ether	108-20-3	WEL	250	1.060	310	1.310				EH40/ 2005

#### Notation

Ceiling-C STEL

Ceiling value is a limit value above which exposure should not occur

Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified) TWA

#### **Human health values**

Relevant DNE	Relevant DNELs and other threshold levels								
Endpoint	Threshold Protection goal, level route of exposure		Used in	Exposure time					
DNEL	850 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects					
DNEL	1.700 mg/m³	human, inhalatory	worker (industry)	acute - systemic effects					
DNEL	121,4 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects					

#### **Relevant DNELs of components** Name of sub-**CAS No** End-**Threshol Used** in **Exposure time Protection** point d level goal, route of stance exposure 19 mg/kg bw/day Butylated hydroxy-128-37-0 DNEL human, dermal acute - systemic worker (industry) effects toluene Butylated hydroxy-128-37-0 DNEL 18 mg/m<sup>3</sup> human, inhalatworker (industry) acute - systemic toluene effects ory human, inhalat-Butylated hydroxy-128-37-0 DNEL 3,5 mg/m<sup>3</sup> worker (industry) chronic - systemic toluene ory effects Butylated hydroxy-128-37-0 DNEL 0,5 mg/kg human, dermal worker (industry) chronic - systemic toluene bw/day effects

#### **Environmental values**

Relevant PNECs and other threshold levels								
End- point	Threshold level	Organism	Environmental com- partment	Exposure time				
PNEC	0,19 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single instance)				
PNEC	0,019 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	marine water	short-term (single instance)				

United Kingdom (en) Page 6 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

#### Diisopropyl ether ROTIPURAN® ≥99 %, p.a., stabilized

article number: T919

**PNEC** 



short-term (single instance)

#### **Relevant PNECs and other threshold levels Threshold Organism Environmental com-Exposure time** point level partment 37 <sup>mg</sup>/<sub>I</sub> sewage treatment plant **PNEC** aquatic organisms short-term (single instance) (STP) 2,79 mg/kg **PNEC** freshwater sediment aquatic organisms short-term (single instance) **PNEC** $0,28 \, {\rm mg/_{kg}}$ aquatic organisms marine sediment short-term (single instance)

soil

terrestrial organisms

# **Relevant PNECs of components**

 $0.47 \, ^{mg}/_{kg}$ 

Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time
Butylated hydroxy- toluene	128-37-0	PNEC	8,33 <sup>mg</sup> / <sub>kg</sub>	aquatic organ- isms	water	short-term (single instance)
Butylated hydroxy- toluene	128-37-0	PNEC	1,99 <sup>µg</sup> / <sub>l</sub>	aquatic organ- isms	water	intermittent re- lease
Butylated hydroxy- toluene	128-37-0	PNEC	0,199 <sup>µg</sup> / <sub>l</sub>	aquatic organ- isms	freshwater	short-term (single instance)
Butylated hydroxy- toluene	128-37-0	PNEC	0,02 <sup>µg</sup> / <sub>I</sub>	aquatic organ- isms	marine water	short-term (single instance)
Butylated hydroxy- toluene	128-37-0	PNEC	0,17 <sup>mg</sup> / <sub>l</sub>	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
Butylated hydroxy- toluene	128-37-0	PNEC	99,6 <sup>µg</sup> / <sub>kg</sub>	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
Butylated hydroxy- toluene	128-37-0	PNEC	9,96 <sup>µg</sup> / <sub>kg</sub>	aquatic organ- isms	marine sediment	short-term (single instance)
Butylated hydroxy- toluene	128-37-0	PNEC	47,69 <sup>µg</sup> / <sub>kg</sub>	terrestrial organ- isms	soil	short-term (single instance)

## 8.2 Exposure controls

Individual protection measures (personal protective equipment)

**Eye/face protection** 





Use safety goggle with side protection.

Skin protection





United Kingdom (en) Page 7 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

#### Diisopropyl ether ROTIPURAN® ≥99 %, p.a., stabilized

article number: T919



#### hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

#### type of material

Butyl caoutchouc (butyl rubber)

#### material thickness

0,7mm

#### breakthrough times of the glove material

>480 minutes (permeation: level 6)

#### • Splash protection - Protective gloves

• type of material: NBR (Nitrile rubber)

material thickness: >0,3 mm

• breakthrough times of the glove material: >240 minutes (permeation: level 5)

#### other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

#### Respiratory protection





Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

#### **Environmental exposure controls**

Keep away from drains, surface and ground water.

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state liquid
Colour colourless

Odour like ether

Melting point/freezing point -86 °C at 1.013 hPa

Boiling point or initial boiling point and boiling

range

67 – 70 °C at 1.013 hPa

Flammability flammable liquid in accordance with GHS criteria

Lower and upper explosion limit 45 g/m³ (LEL) - 900 g/m³ (UEL) / 1 vol% (LEL) - 21 vol% (UEL)

United Kingdom (en) Page 8 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)



article number: T919

Flash point -28 °C at 1.013 hPa (c.c.)

415 °C at 1.019 hPa (ECHA) Auto-ignition temperature

Decomposition temperature not relevant

(20 °C) (neutral) pH (value)

 $0,4597 \, \text{mm}^2/_{\text{S}} \, \text{at } 293,2 \, \text{K}$ Kinematic viscosity

Dynamic viscosity 0,331 mPa s at 293,2 K

Solubility(ies)

Water solubility 3,11 <sup>g</sup>/<sub>l</sub> at 20,2 °C (ECHA)

Partition coefficient

Partition coefficient n-octanol/water (log value): 2,4 (pH value: 6,7, 20 °C) (ECHA)

175 hPa at 20 °C 248 hPa at 30 °C Vapour pressure

Density and/or relative density

0,72 <sup>g</sup>/<sub>cm³</sub> at 20 °C Density

Relative vapour density 3,52 (air = 1)

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard

classes:

There is no additional information.

Other safety characteristics:

Gas group (explosion group)

Maximum Experimental Safe Gap value; MESG >

0,9 mm

Maximum explosion pressure 9,3 bar

Refractive index 1,368

United Kingdom (en) Page 9 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

#### Diisopropyl ether ROTIPURAN® ≥99 %, p.a., stabilized

article number: T919



## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air. May form explosive peroxides.

#### If heated

Risk of ignition.

## 10.2 Chemical stability

Reactivity if exposed to light. Reactivity if exposed to air.

#### 10.3 Possibility of hazardous reactions

**Violent reaction with:** strong oxidiser, Aldehydes, Amines, Acids, Oxygen, => Explosive properties

#### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### 10.5 Incompatible materials

different plastics

#### 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5. Peroxides.

# **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Classification acc. to GHS

#### **Acute toxicity**

Shall not be classified as acutely toxic.

Acute toxicity								
Exposure route	Endpoint	Value	Species	Method	Source			
oral	LD50	8.470 <sup>mg</sup> / <sub>kg</sub>	rat		TOXNET			
inhalation: vapour	LC50	162 <sup>mg</sup> / <sub>l</sub> /4h	rat		TOXNET			

#### Acute toxicity of components Name of substance **CAS No Exposure Endpoint Value Species** route $>6.000 \, \text{mg/}_{kg}$ Butylated hydroxytoluene 128-37-0 LD50 oral rat >2.000 <sup>mg</sup>/<sub>kg</sub> Butylated hydroxytoluene 128-37-0 dermal LD50 rat

#### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

#### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

United Kingdom (en) Page 10 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

#### Diisopropyl ether ROTIPURAN® ≥99 %, p.a., stabilized

article number: T919



Shall not be classified as a respiratory or skin sensitiser.

#### **Germ cell mutagenicity**

Shall not be classified as germ cell mutagenic.

#### Carcinogenicity

Shall not be classified as carcinogenic.

#### **Reproductive toxicity**

Shall not be classified as a reproductive toxicant.

#### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

#### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

## **Aspiration hazard**

Shall not be classified as presenting an aspiration hazard.

#### Symptoms related to the physical, chemical and toxicological characteristics

#### If swallowed

vomiting, nausea

#### • If in eyes

Data are not available.

#### • If inhaled

vertigo, nausea, headache, cough, Dyspnoea, dizziness, fatigue, narcosis

#### • If on skin

repeated exposure may cause skin dryness or cracking

#### Other information

none

#### 11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq 0.1\%$ .

#### 11.3 Information on other hazards

There is no additional information.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)							
Endpoint	Endpoint Value		Source	Exposure time			
EC50	190 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	ECHA	48 h			

United Kingdom (en) Page 11 / 20



acc. to Regulation (EC) No. 1907/2006 (REACH)



article number: T919



Aquatic toxicity (acute) of components									
Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time				
Butylated hydroxy- toluene	128-37-0	LC50	>0,57 <sup>mg</sup> / <sub>l</sub>	fish	96 h				
Butylated hydroxy- toluene	128-37-0	EC50	0,48 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	48 h				
Butylated hydroxy-	128-37-0	ErC50	>0,4 <sup>mg</sup> / <sub>I</sub>	algae	72 h				

## **Aquatic toxicity (chronic)**

toluene

Endpoint	Value	Species	Source	Exposure time
EC50	3.155 <sup>mg</sup> / <sub>l</sub>	microorganisms	ECHA	3 h

# Aquatic toxicity (chronic) of components

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
Butylated hydroxy- toluene	128-37-0	EC50	0,096 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	21 d

#### 12.2 Persistence and degradability

Theoretical Oxygen Demand: 2,818  $^{\rm mg}/_{\rm mg}$  Theoretical Carbon Dioxide: 2,584  $^{\rm mg}/_{\rm mg}$ 

_	•			•••
Process	A+ A	00K26	Inhi	1: <b>4</b> \
		ieui au	14111	III V

Process	Degradation rate	Time
oxygen depletion	0 %	28 d

## **Degradability of components**

Name of substance	CAS No	Process	Degrada- tion rate	Time	Method	Source
Butylated hy- droxytoluene	128-37-0	biotic/abiotic	<10 %	20 d		

## 12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW) 2,4 (pH value: 6,7, 20 °C) (ECHA)	n-octanol/water (log KOW)	2,4 (pH value: 6,7, 20 °C) (ECHA)
---	---------------------------	-----------------------------------

#### **Bioaccumulative potential of components**

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Butylated hydroxytoluene	128-37-0	598,4	5,1	

## 12.4 Mobility in soil

Data are not available.

United Kingdom (en) Page 12 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

#### Diisopropyl ether ROTIPURAN® ≥99 %, p.a., stabilized

article number: T919



#### 12.5 Results of PBT and vPvB assessment

Data are not available.

#### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq 0.1\%$ .

#### 12.7 Other adverse effects

Data are not available.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Sewage disposal-relevant information

Do not empty into drains.

#### Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

#### 13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

#### Properties of waste which render it hazardous

**HP3** flammable

**HP 15** waste capable of exhibiting a hazardous property listed above not directly displayed by the original waste

#### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

## **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADRRID UN 1159
IMDG-Code UN 1159
ICAO-TI UN 1159

#### 14.2 UN proper shipping name

ADRRID DIISOPROPYL ETHER

IMDG-Code DIISOPROPYL ETHER

ICAO-TI Diisopropyl ether

#### 14.3 Transport hazard class(es)

United Kingdom (en) Page 13 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

#### Diisopropyl ether ROTIPURAN® ≥99 %, p.a., stabilized

article number: T919

**ADRRID** 3 **IMDG-Code** 3 ICAO-TI

14.4 Packing group

**ADRRID** II **IMDG-Code** ΙΙ ICAO-TI II

14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

3

gerous goods regulations

#### 14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

#### 14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

#### 14.8 Information for each of the UN Model Regulations

#### Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)Additional information

Proper shipping name DIISOPROPYL ETHER

Particulars in the transport document UN1159, DIISOPROPYL ETHER, 3, II, (D/E)

Classification code F1 Danger label(s) 3



Excepted quantities (EQ) E2 1 L Limited quantities (LQ) Transport category (TC) 2 Tunnel restriction code (TRC) D/E Hazard identification No 33 **Emergency Action Code** 3YE

#### Regulations concerning the International Carriage of Dangerous Goods by Rail (RID)Additional information

Classification code F1 3 Danger label(s)



**Excepted quantities (EQ)** E2 Limited quantities (LQ) 1 L **Transport category (TC)** 2

United Kingdom (en) Page 14 / 20



acc. to Regulation (EC) No. 1907/2006 (REACH)

#### Diisopropyl ether ROTIPURAN® ≥99 %, p.a., stabilized

article number: T919

lazard identification No

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name DIISOPROPYL ETHER

Particulars in the shipper's declaration UN1159, DIISOPROPYL ETHER, 3, II, -28°C c.c.

Marine pollutant Danger label(s) 3

3

Special provisions (SP)

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

EmS F-E, S-D

Stowage category E

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Diisopropyl ether

Particulars in the shipper's declaration UN1159, Diisopropyl ether, 3, II

Danger label(s) 3



Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

#### **Seveso Directive**

2012/18/EU (Seveso III)						
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements		Notes		
P5c	flammable liquids (cat. 2, 3)	5.000	50.000	51)		

#### Notation

51) Flammable liquids, categories 2 or 3 not covered by P5a and P5b

#### **Deco-Paint Directive**

United Kingdom (en) Page 15 / 20



## Hazard identification No

33

acc. to Regulation (EC) No. 1907/2006 (REACH)



#### Diisopropyl ether ROTIPURAN® ≥99 %, p.a., stabilized

article number: T919

VOC content	100 %
VOC content	720 <sup>g</sup> / <sub>l</sub>

#### **Industrial Emissions Directive (IED)**

VOC content	100 %
VOC content	720 <sup>g</sup> / <sub>l</sub>

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

Water Framework Directive (WFD)

not listed

Regulation on the marketing and use of explosives precursors

not listed

**Regulation on drug precursors** 

not listed

Regulation on substances that deplete the ozone layer (ODS)

not listed

Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

Regulation on persistent organic pollutants (POP)

not listed

National regulations(GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list not listed

Restrictions according to GB REACH, Annex 17

# Dangerous substances with restrictions (GB REACH, Annex 17) Name of substance Name acc. to inventory CAS No No Diisopropyl ether this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC 3 Diisopropyl ether flammable / pyrophoric 40

#### Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

United Kingdom (en) Page 16 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

#### Diisopropyl ether ROTIPURAN® ≥99 %, p.a., stabilized

article number: T919





Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

Legend

AIIC Australian Inventory of Industrial Chemicals
CSCL-ENCS List of Existing and New Chemical Substances (CSCL-ENCS)
DSL Domestic Substances List (DSL)
ECSI EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC Inventory of Existing Chemical Substances Produced or Imported in China
INSQ National Inventory of Chemical Substances
KECI Korea Existing Chemicals Inventory
NCI National Chemical Inventory
NZIOC New Zealand Inventory of Chemicals
PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg. REACH registered substances
TCSI Taiwan Chemical Substance Inventory

Taiwan Chemical Substance Inventory Toxic Substance Control Act

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance.

## **SECTION 16: Other information**

#### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Danger		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes

United Kingdom (en) Page 17 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

## Diisopropyl ether ROTIPURAN® ≥99 %, p.a., stabilized

article number: **T919** 




Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
14.8		Regulations concerning the International Car- riage of Dangerous Goods by Rail (RID)Addition- al information	yes
14.8		Classification code: F1	yes
14.8		Danger label(s): 3	yes
14.8		Danger label(s): change in the listing (table)	yes
14.8		Excepted quantities (EQ): E2	yes
14.8		Limited quantities (LQ): 1 L	yes
14.8		Transport category (TC): 2	yes
14.8		Hazard identification No: 33	yes
15.1	Restrictions according to REACH, Annex XVII		yes
15.1		Dangerous substances with restrictions (REACH, Annex XVII): change in the listing (table)	yes
15.1	List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list: Not listed.		yes
15.1	VOC content: 100 % , 720 <sup>g</sup> / <sub>l</sub>	VOC content: 100 %	yes
15.1		VOC content: 720 <sup>g</sup> / <sub>l</sub>	yes
15.1		National regulations(GB)	yes
15.1		List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list: not listed	yes
15.1		Restrictions according to GB REACH, Annex 17	yes
15.1		Dangerous substances with restrictions (GB REACH, Annex 17): change in the listing (table)	yes
15.1		National inventories: change in the listing (table)	yes

United Kingdom (en) Page 18 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

## Diisopropyl ether ROTIPURAN® ≥99 %, p.a., stabilized

article number: **T919** 





Abbr.	Descriptions of used abbreviations
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
ED	Endocrine disruptor
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-li- cence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GB CLP	The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/720 (as amended)
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
log KOW	n-Octanol/water

United Kingdom (en) Page 19 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)



article number: T919



Abbr.	Descriptions of used abbreviations
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)
STEL	Short-term exposure limit
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

#### Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

#### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H336	May cause drowsiness or dizziness.

#### **Disclaimer**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United Kingdom (en) Page 20 / 20