



# Specification

---

Item number: 3067

## Limesoil

CAS No.:

print date:

01.01.2024

formula:

density:

molecular weight:

---

Super lubricant® for quick fit connections and stopcocks. Protects glass against seizing and metals against corrosion. Produces a non-tearing film and is resistant against aggressive substances such as methylisobutylketone, IPA, etc. No flowing, no pulling strings. Temperature range: -40 to +185 °C. Steam pressure:  $9.33 \times 10^{-4}$  N/m<sup>2</sup> (7 x 10<sup>-6</sup> Torr) at +20 °C and 1.33 N/m<sup>2</sup> (10<sup>-2</sup> Torr) at +100 °C.

Our products are tested for laboratory use only.

The stated information refers to the current status of product quality.

We reserve the right to implement necessary changes.

---

**Dr. R. Niemand**

*Head of Quality Assurance*

**S. Lorsee**

*Head of Quality Management*

*This document is computer printout and has therefore not been signed by hand.*

---

**Carl Roth GmbH + Co. KG**

Schoemperlenstraße 3-5

76185 Karlsruhe

Telefon 0721/5606-0

Telefax 0721/5606-149

E-Mail: [info@carlroth.de](mailto:info@carlroth.de)

Die Firma ist eine Kommanditgesellschaft mit Sitz in Karlsruhe, Reg. Gericht Mannheim HRA 100055. Persönlich haftende Gesellschafterin ist die Firma Roth Chemie GmbH mit Sitz in Karlsruhe, Reg. Gericht Mannheim HRB 100428. Geschäftsführer: André Houdelet

