

Firm and Unit of manufacture:	ZVG Zellstoff-Vertriebs GmbH & Co. KG Urbacher Straße 4+5. D-53842 Troisdorf
Basic type description:	Code: 30250-90 overshoe in Secutex fabric. Elasticated ankles. size: 40x16cm
Color:	White
Category : (according to 89/686/EEC)	III
Packing:	Interior: 10pcs/roll, 100pcs/clear polybag, Exterior: 400pcs/ctn Carton dimension: 32x32x26cm
Use destination:	Breathable laminated fabric with soft, durable, breathable, anti-static, anti-bacterial features. Suitable for: <ul style="list-style-type: none">• pharmaceutical manufacturing• electronic assembly and insulation laying• industrial manufacturing and maintenance
Standards	EN ISO 13688:2013 EN 13034:2005 + A1:2009 EN 14126:2003 EN 1149-5:2008
SIZES:	One size fits all Customized size available

MATERIALS

Fabric:	Microporous non woven: polypropylene 58%-polyethylene 42%, Weight: 65g/m ² Colour: white,
Elastic:	1/8x0.35 rubber, Latex-free
Seams:	Polyester, three thread overlock

ANTISTATIC PROPERTIES: the product is made following EN1149-5 dissipate electro-static energy.

- the person wearing the electrostatic dissipative protective clothing shall be properly earthed. The resistance between the person and the earth shall be less than 10⁶Ω e.g. by wearing adequate footwear;
 - electrostatic dissipative protective clothing shall not be open or removed whilst in presence of flammable or explosive atmospheres or while handling flammable or explosive substances;
 - electrostatic dissipative protective clothing shall not be used in oxygen enriched atmospheres without prior approval of the responsible safety engineer;
 - the electrostatic dissipative performance of the electrostatic dissipative protective clothing can be affected by wear and tear, laundering and possible contamination;
- electrostatic dissipative protective clothing shall permanently cover all non-complying materials during normal use (including bending and movements).

TYPE PB(6) partial body protection has not been tested to the whole suit test

NB: the protection characteristics are valid only if the item is correctly dressed. The manufacturer doesn't take any responsibilities for any improper use of the garment.

MAINTENANCE AND CLEANING: disposable item - barred symbols

APPROVED	DATE 14/01/16	DOC. TEC. N° 101/02	PAGE 1 of 3
----------	------------------	------------------------	----------------

				
DONT wash	DONT bleach	DONT tumbler dry	DONT iron	DONT dry wash

CONSERVATION AND DISCARDING: The item should be conserved in a dry place away from sources of light and heat. If not contaminated the product can be treated as a common. If contaminated it should be treated as harmful garbage and discarded according to country laws.

EXPIRATION: it is suggested to use the product within a period of five years from the date of production written on label

WARNINGS: make sure that the size correspond s with the user. Do not make any modifications on product.

- Check that the product has no defect and is in good condition (no holes, unsewed parts, etc.)
- The disposable item should be replaced after every use
- Abandon the place of work immediately in case of damage of the product
- These garments are flammable - Keep away from fire

Protect uncovered body parts (hands, respiratory areas) with protective gloves and boots taped to the coverall.
Choose products compatible with area of work.

PERFORMANCE – LEVELS AND CLASSES

EC Type examination and Article 11 approval conducted by Centro Tessile Cottoniero & Abbigliamento S.p.A. piazza S. Anna 2, 21052 Busto Arsizio VA, Italy. Notified Body Number 0624.

<i>Test on material</i>	<i>Result</i>	<i>Class</i>
Resistance to penetration (EN 368- EN ISO 6530)		
<i>H₂SO₄ 30%</i>	0.0%	3/3
<i>NaOH 10%</i>	0.0%	3/3
<i>o-xylene</i>	0.0%	3/3
<i>Butan 1 ol</i>	0.0%	3/3
Repellency to Liquid (EN 368- ISO 6530)		
<i>H₂SO₄ 30%</i>	98.6%	3/3
<i>NaOH 10%</i>	97.7%	3/3
<i>o-xylene</i>	94.7%	2/3
<i>Butan 1 ol</i>	95.3%	3/3
Abrasion Resistance (EN530 met2)	>500 cycles	3/6
Trapezoidal tear resistance (EN ISO 9073-4)	35.4 N warp 81.5 N weft	2/6
Tensile strength (EN ISO 13934-1)	48 N warp 120 N weft	1/6
Puncture resistance (EN 863)	9.09 N	2/6
Resistance to penetration by blood-borne phatogens - phi-x174 bacteriophage test - ISO 16603/16604	20 kPa	Class 6/6
Resistance to penetration by infective agents due to mechanical contact with substances containing contaminated liquids - ISO 22610 (test microorganism: staphylococcus aureus)	> 75 min	Class 6/6
Resistance to penetration by contaminated liquid aerosols - ISO DIS 22611 (test microorganism: staphylococcus aureus)	Log > 5	Class 3/3
Resistance to penetration by contaminated solid particles - EN ISO 22612 (test microorganism: spores of Bacillus subtilis)	Log CFU ≤ 1	Class 3/3
Surface resistivity (EN 1149-1)	2.49 x 10 ⁹ Ω	pass

