

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



n-Pentane ROTISOLV® ≥99 %, UV/IR-Grade

article number: **4443**
Version: **GHS 6.0 en**
Replaces version of: 2022-12-19
Version: (GHS 5)

date of compilation: 2016-07-05
Revision: 2024-03-02

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance **n-Pentane ROTISOLV® ≥99 %, UV/IR-Grade**
Article number 4443
CAS number 109-66-0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical
Laboratory and analytical use
Uses advised against: Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household). Food, drink and animal feeding-stuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG
Schoemperlenstr. 3-5
D-76185 Karlsruhe
Germany

Telephone:+49 (0) 721 - 56 06 0
Telefax: +49 (0) 721 - 56 06 149
e-mail: sicherheit@carlroth.de
Website: www.carlroth.de

Competent person responsible for the safety data sheet: Department Health, Safety and Environment

e-mail (competent person): sicherheit@carlroth.de

1.4 Emergency telephone number

| Name | Street | Postal code/city | Telephone | Website |
|--|-----------------|--------------------|-----------|---------|
| NSW Poisons Information Centre Childrens Hospital | Hawkesbury Road | 2145 Westmead, NSW | 131126 | |

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

| Section | Hazard class | Category | Hazard class and category | Hazard statement |
|---------|---|----------|---------------------------|------------------|
| 2.6 | Flammable liquid | 1 | Flam. Liq. 1 | H224 |
| 3.8D | Specific target organ toxicity - single exposure (narcotic effects, drowsiness) | 3 | STOT SE 3 | H336 |
| 3.10 | Aspiration hazard | 1 | Asp. Tox. 1 | H304 |

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



n-Pentane ROTISOLV® ≥99 %, UV/IR-Grade

article number: 4443

Supplemental hazard information

| Code | Supplemental hazard information |
|--------|--|
| AUH066 | repeated exposure may cause skin dryness or cracking |

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling

Signal word

Danger

Pictograms

GHS02, GHS07,
GHS08



Hazard statements

H224 Extremely flammable liquid and vapour
H304 May be fatal if swallowed and enters airways
H336 May cause drowsiness or dizziness

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Precautionary statements - response

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P331 Do NOT induce vomiting
P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

Precautionary statements - storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed
P403+P235 Store in a well-ventilated place. Keep cool

Supplemental hazard information

AUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



n-Pentane ROTISOLV® ≥99 %, UV/IR-Grade

article number: 4443

SECTION 3: Composition/information on ingredients

3.1 Substances

| | |
|-------------------|--------------------------------|
| Name of substance | n-Pentane |
| Molecular formula | C ₅ H ₁₂ |
| Molar mass | 72.15 g/mol |
| CAS No | 109-66-0 |

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Call a physician immediately. Observe aspiration hazard if vomiting occurs.

4.2 Most important symptoms and effects, both acute and delayed

Irritant effects, Aspiration hazard, Dizziness, Drowsiness, Narcosis

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings!
water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



n-Pentane ROTISOLV® ≥99 %, UV/IR-Grade

article number: **4443**

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



n-Pentane ROTISOLV® ≥99 %, UV/IR-Grade

article number: 4443

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

| Country | Name of agent | CAS No | Identifier | TWA [ppm] | TWA [mg/m ³] | STEL [ppm] | STEL [mg/m ³] | Ceiling-C [ppm] | Ceiling-C [mg/m ³] | Notation | Source |
|---------|---------------|----------|------------|-----------|--------------------------|------------|---------------------------|-----------------|--------------------------------|----------|--------|
| AU | pentane | 109-66-0 | WES | 600 | 1,770 | 750 | 2,210 | | | | WES |

Notation

Ceiling-C
STEL

Ceiling value is a limit value above which exposure should not occur

Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Human health values

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



n-Pentane ROTISOLV® ≥99 %, UV/IR-Grade

article number: 4443

| Relevant DNELs and other threshold levels | | | | |
|---|-------------------------|------------------------------------|-------------------|----------------------------|
| Endpoint | Threshold level | Protection goal, route of exposure | Used in | Exposure time |
| DNEL | 3,000 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| DNEL | 432 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |

Environmental values

| Relevant PNECs and other threshold levels | | | | |
|---|-----------------|-----------------------|------------------------------|------------------------------|
| End-point | Threshold level | Organism | Environmental compartment | Exposure time |
| PNEC | 230 µg/l | aquatic organisms | freshwater | short-term (single instance) |
| PNEC | 230 µg/l | aquatic organisms | marine water | short-term (single instance) |
| PNEC | 3,600 µg/l | aquatic organisms | sewage treatment plant (STP) | short-term (single instance) |
| PNEC | 1.2 mg/kg | aquatic organisms | freshwater sediment | short-term (single instance) |
| PNEC | 1.2 mg/kg | aquatic organisms | marine sediment | short-term (single instance) |
| PNEC | 0.55 mg/kg | terrestrial organisms | soil | short-term (single instance) |

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

NBR (Nitrile rubber)

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



n-Pentane ROTISOLV® ≥99 %, UV/IR-Grade

article number: 4443

- **material thickness**

>0,3 mm

- **breakthrough times of the glove material**


>480 minutes (permeation: level 6)

- **other protection measures**

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: AX (gas filters and combined filters against low-boiling point organic compounds, colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|--|
| Physical state | liquid |
| Colour | colourless |
| Odour | characteristic - like: - Gasoline |
| Melting point/freezing point | -130 °C |
| Boiling point or initial boiling point and boiling range | 35 – 36 °C |
| Flammability | flammable liquid in accordance with GHS criteria |
| Lower and upper explosion limit | 1.4 vol% (LEL) - 8 vol% (UEL) |
| Flash point | -40 °C (ECHA) |
| Auto-ignition temperature | 260 °C (ECHA) |
| Decomposition temperature | not relevant |
| pH (value) | not determined |
| Kinematic viscosity | 0.35 mm ² /s at 25 °C |
| Dynamic viscosity | 0.22 mPa s at 25 °C |
| <u>Solubility(ies)</u> | |
| Water solubility | <0.1 g/l at 20 °C |
| <u>Partition coefficient</u> | |
| Partition coefficient n-octanol/water (log value): | 3.45 (pH value: 7, 25 °C) (ECHA) |
| Soil organic carbon/water (log KOC) | 2.9 (ECHA) |

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



n-Pentane ROTISOLV® ≥99 %, UV/IR-Grade

article number: 4443

| | |
|--|--|
| Vapour pressure | 570 hPa at 20 °C |
| <u>Density and/or relative density</u> | |
| Density | 0.63 g/cm ³ at 20 °C (ECHA) |
| Relative vapour density | 2.49 (air = 1) |
| Particle characteristics | not relevant (liquid) |
| <u>Other safety parameters</u> | |
| Oxidising properties | none |

9.2 Other information

| | |
|---|---|
| Information with regard to physical hazard classes: | There is no additional information. |
| Other safety characteristics: | |
| Gas group (explosion group) | IIA Maximum Experimental Safe Gap value; MESG > 0,9 mm |
| Maximum explosion pressure | 9.5 bar |

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Halogens, Nitric acid,
=> Explosive properties

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

Rubber articles, different plastics

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



n-Pentane ROTISOLV® ≥99 %, UV/IR-Grade

article number: 4443

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4. May be harmful if inhaled.

| Acute toxicity | | | | | |
|--------------------|----------|---------------|---------|--------|--------|
| Exposure route | Endpoint | Value | Species | Method | Source |
| oral | LD50 | >5,000 mg/kg | rat | | ECHA |
| inhalation: vapour | LC50 | >25.3 mg/l/4h | rat | | ECHA |

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

- **If swallowed**

aspiration hazard

- **If in eyes**

causes slight to moderate irritation

- **If inhaled**

headache, vertigo, dizziness, fatigue, narcosis

- **If on skin**

irritation and significant inflammation of the skin (dermatitis) due to the defatting properties of the

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



n-Pentane ROTISOLV® ≥99 %, UV/IR-Grade

article number: 4443

product may be caused by repeated or prolonged exposure

• Other information

none

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

| Aquatic toxicity (acute) | | | | |
|--------------------------|-----------|-------------------------------------|--------|---------------|
| Endpoint | Value | Species | Source | Exposure time |
| LC50 | 4.26 mg/l | rainbow trout (Oncorhynchus mykiss) | ECHA | 96 h |
| EC50 | 2.7 mg/l | daphnia magna | ECHA | 48 h |

12.2 Persistence and degradability

Theoretical Oxygen Demand: 3.548 mg/mg
Theoretical Carbon Dioxide: 3.05 mg/mg

Biodegradation

The substance is readily biodegradable.

| Process of degradability | | |
|--------------------------|------------------|------|
| Process | Degradation rate | Time |
| oxygen depletion | 87 % | 28 d |

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

| | |
|---------------------------|----------------------------------|
| n-octanol/water (log KOW) | 3.45 (pH value: 7, 25 °C) (ECHA) |
| BCF | 171 (ECHA) |

12.4 Mobility in soil

| | |
|--|------------|
| The Organic Carbon normalised adsorption coefficient | 2.9 (ECHA) |
|--|------------|

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.

12.7 Other adverse effects

Data are not available.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



n-Pentane ROTISOLV® ≥99 %, UV/IR-Grade

article number: 4443

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H3 Flammable liquids
H11 Toxic (Delayed or chronic)

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number

| | |
|----------------|---------|
| UN RTDG | UN 1265 |
| IMDG-Code | UN 1265 |
| ICAO-TI | UN 1265 |

14.2 UN proper shipping name

| | |
|----------------|----------|
| UN RTDG | PENTANES |
| IMDG-Code | PENTANES |
| ICAO-TI | Pentanes |

14.3 Transport hazard class(es)

| | |
|----------------|---|
| UN RTDG | 3 |
| IMDG-Code | 3 |
| ICAO-TI | 3 |

14.4 Packing group

| | |
|----------------|----|
| UN RTDG | II |
| IMDG-Code | II |
| ICAO-TI | II |

14.5 Environmental hazards

hazardous to the aquatic environment

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



n-Pentane ROTISOLV® ≥99 %, UV/IR-Grade

article number: 4443

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport information National regulations Additional information (UN RTDG)

| | |
|-----------------------|---|
| UN number | 1265 |
| Class | 3 |
| Environmental hazards | Yes Hazardous to the aquatic environment |
| Packing group | II |
| Danger label(s) | 3 Fish and tree |



| | |
|--------------------------|----------------|
| Special provisions (SP) | - UN RTDG |
| Excepted quantities (EQ) | E2 UN RTDG |
| Limited quantities (LQ) | 1 L UN RTDG |
| Emergency Action Code | 3YE |

International Maritime Dangerous Goods Code (IMDG) - Additional information

| | |
|--|---|
| Proper shipping name | PENTANES |
| Particulars in the shipper's declaration | UN1265, PENTANES, 3, II, -40°C c.c., MARINE POLLUTANT |
| Marine pollutant | yes (hazardous to the aquatic environment) |
| Danger label(s) | 3, "Fish and tree" |



| | |
|--------------------------|----------|
| Special provisions (SP) | - |
| Excepted quantities (EQ) | E2 |
| Limited quantities (LQ) | 1 L |
| EmS | F-E, S-D |
| Stowage category | E |

Safety data sheet Safety data sheet


acc. to Safe Work Australia - Code of Practice



n-Pentane ROTISOLV® ≥99 %, UV/IR-Grade

article number: 4443

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

| | |
|---|--|
| Proper shipping name | Pentanes |
| Particulars in the shipper's declaration | UN1265, Pentanes, 3, II |
| Environmental hazards | yes (hazardous to the aquatic environment) |
| Danger label(s) | 3 |
|  | |
| Excepted quantities (EQ) | E2 |
| Limited quantities (LQ) | 1 L |

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

Substance is listed.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

| Country | Inventory | Status |
|---------|------------|------------------------------|
| AU | AIIC | substance is listed |
| CA | DSL | substance is listed |
| CN | IECSC | substance is listed |
| EU | ECSI | substance is listed |
| EU | REACH Reg. | substance is listed |
| JP | CSCL-ENCS | substance is listed |
| KR | KECI | substance is listed |
| MX | INSQ | substance is listed |
| NZ | NZIoC | substance is listed |
| PH | PICCS | substance is listed |
| TR | CICR | substance is listed |
| TW | TCSI | substance is listed |
| US | TSCA | substance is listed (ACTIVE) |
| VN | NCI | substance is listed |

Legend

| | |
|-----------|--|
| AIIC | Australian Inventory of Industrial Chemicals |
| CICR | Chemical Inventory and Control Regulation |
| CSCL-ENCS | List of Existing and New Chemical Substances (CSCL-ENCS) |
| DSL | Domestic Substances List (DSL) |

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



n-Pentane ROTISOLV® ≥99 %, UV/IR-Grade

article number: 4443

Legend

| | |
|------------|---|
| ECSI | EC Substance Inventory (EINECS, ELINCS, NLP) |
| IECSC | Inventory of Existing Chemical Substances Produced or Imported in China |
| INSQ | National Inventory of Chemical Substances |
| KECI | Korea Existing Chemicals Inventory |
| NCI | National Chemical Inventory |
| NZIoC | New Zealand Inventory of Chemicals |
| PICCS | Philippine Inventory of Chemicals and Chemical Substances (PICCS) |
| REACH Reg. | REACH registered substances |
| TCSI | Taiwan Chemical Substance Inventory |
| TSCA | Toxic Substance Control Act |

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

| Section | Former entry (text/value) | Actual entry (text/value) | Safety-relevant |
|---------|--|---|-----------------|
| 2.1 | | Supplemental hazard information: change in the listing (table) | yes |
| 2.2 | | Supplemental hazard information | yes |
| 2.2 | | Supplemental hazard information: change in the listing (table) | yes |
| 2.3 | Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB. | | yes |
| 2.3 | | Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%. | yes |
| 15.1 | | National inventories: change in the listing (table) | yes |

Abbreviations and acronyms

| Abbr. | Descriptions of used abbreviations |
|-----------|--|
| BCF | Bioconcentration factor |
| CAS | Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances) |
| Ceiling-C | Ceiling value |
| DGR | Dangerous Goods Regulations (see IATA/DGR) |
| DNEL | Derived No-Effect Level |
| EC50 | Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval |
| ED | Endocrine disruptor |
| EINECS | European Inventory of Existing Commercial Chemical Substances |
| ELINCS | European List of Notified Chemical Substances |
| EmS | Emergency Schedule |
| GHS | "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations |

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



n-Pentane ROTISOLV® ≥99 %, UV/IR-Grade

article number: 4443

| Abbr. | Descriptions of used abbreviations |
|-----------|---|
| IATA | International Air Transport Association |
| IATA/DGR | Dangerous Goods Regulations (DGR) for the air transport (IATA) |
| ICAO | International Civil Aviation Organization |
| ICAO-TI | Technical instructions for the safe transport of dangerous goods by air |
| IMDG | International Maritime Dangerous Goods Code |
| IMDG-Code | International Maritime Dangerous Goods Code |
| LC50 | Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval |
| LD50 | Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval |
| LEL | Lower explosion limit (LEL) |
| NLP | No-Longer Polymer |
| PBT | Persistent, Bioaccumulative and Toxic |
| PNEC | Predicted No-Effect Concentration |
| ppm | Parts per million |
| STEL | Short-term exposure limit |
| TWA | Time-weighted average |
| UEL | Upper explosion limit (UEL) |
| UN RTDG | UN Recommendations on the Transport of Dangerous Good |
| vPvB | Very Persistent and very Bioaccumulative |
| WES | Safe Work Australia: Workplace exposure standards for airborne contaminants |

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

| Code | Text |
|------|---|
| H224 | Extremely flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H336 | May cause drowsiness or dizziness. |

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.